

Package ‘dnet’

March 27, 2017

Type Package

Title Integrative Analysis of Omics Data in Terms of Network, Evolution and Ontology

Version 1.0.11

Date 2017-3-27

Author Hai Fang and Julian Gough

Maintainer Hai Fang <hfang@well.ox.ac.uk>

Depends R (>= 3.1.0), igraph, supraHex

Imports graph, Rgraphviz, Matrix, Biobase

Suggests limma, survival, foreach, doParallel

Description The focus of the dnet is to make sense of omics data (such as gene expression and mutations) from different angles including: integration with molecular networks, enrichments using ontologies, and relevance to gene evolutionary ages. Integration is achieved to identify a gene subnetwork from the whole gene network whose nodes/genes are labelled with informative data (such as the significant levels of differential expression or survival risks). To help make sense of identified gene networks, enrichment analysis is also supported using a wide variety of pre-compiled ontologies and phylostratific gene age information in major organisms including: human, mouse, rat, chicken, C.elegans, fruit fly, zebrafish and arabidopsis. Add-on functionalities are supports for calculating semantic similarity between ontology terms (and between genes) and for calculating network affinity based on random walk; both can be done via high-performance parallel computing.

URL <http://dnet.r-forge.r-project.org>, <https://github.com/hfang-bristol/dnet>, <http://supfam.org/dnet>

Collate 'dBUMfit.r'

'dBUMscore.r'

'dCheckParallel.r'

'dCommSignif.r'

'dContrast.r'

'dDAGancestor.r'

'dDAGannotate.r'

'dDAGgeneSim.r'

'dDAGinduce.r'

'dDAGlevel.r'

'dDAGreverse.r'

'dDAGroot.r'

'dDAGtermSim.r'

'dDAGtip.r'

'dEnricher.r'
 'dEnricherView.r'
 'dFDRscore.r'
 'dFunArgs.r'
 'dGSEA.r'
 'dGSEAview.r'
 'dGSEAwrite.r'
 'dNetConfidence.r'
 'dNetFind.r'
 'dNetInduce.r'
 'dNetPipeline.r'
 'dNetReorder.r'
 'dPvalAggregate.r'
 'dRDataLoader.r'
 'dRWR.r'
 'dRWRcontact.r'
 'dRWRpipeline.r'
 'dSVDsignif.r'
 'visBoxplotAdv.r'
 'visDAG.r'
 'visGSEA.r'
 'visNet.r'
 'visNetAnimate.r'
 'visNetArc.r'
 'visNetCircle.r'
 'visNetMul.r'
 'visNetReorder.r'

License GPL-2

biocViews Bioinformatics

R topics documented:

CLL	5
dBUMfit	6
dBUMscore	8
dCheckParallel	9
dCommSignif	10
dContrast	11
dDAGancestor	12
dDAGannotate	13
dDAGgeneSim	15
dDAGinduce	17
dDAGlevel	18
dDAGreverse	19
dDAGroot	20
dDAGtermSim	21
dDAGtip	22
dEnricher	23
dEnricherView	27
dFDRscore	28
dFunArgs	29

dGSEA	30
dGSEAView	33
dGSEAWrite	35
dNetConfidence	36
dNetFind	37
dNetInduce	39
dNetPipeline	40
dNetReorder	41
dPvalAggregate	44
dRDataLoader	45
dRWR	48
dRWRcontact	50
dRWRpipeline	52
dSVDsignif	54
GWAS2EF	56
GWAS_LD	56
Hiratani_TableS1	57
ig.DO	58
ig.GOBP	59
ig.GOCC	59
ig.GOMF	60
ig.HPCM	61
ig.HPMA	61
ig.HPMI	62
ig.HPPA	63
ig.MP	63
IlluminaHumanHT	64
IlluminaOmniExpress	65
ImmunoBase	65
ImmunoBase_LD	66
JKscience_expression	67
JKscience_genotype	68
JKscience_TS2A	69
JKscience_TS2B	69
JKscience_TS3A	70
org.At.eg	71
org.At.egGOBP	71
org.At.egGOCC	72
org.At.egGOMF	73
org.At.egPS	74
org.At.egSF	75
org.At.string	75
org.Ce.eg	76
org.Ce.egGOBP	77
org.Ce.egGOCC	78
org.Ce.egGOMF	78
org.Ce.egPS	79
org.Ce.egSF	80
org.Ce.string	81
org.Da.eg	82
org.Da.egGOBP	82
org.Da.egGOCC	83

org.Da.egGOMF	84
org.Da.egPS	85
org.Da.egSF	86
org.Da.string	86
org.Dm.eg	87
org.Dm.egGOBP	88
org.Dm.egGOCC	89
org.Dm.egGOMF	89
org.Dm.egPS	90
org.Dm.egSF	91
org.Dm.string	92
org.Gg.eg	93
org.Gg.egGOBP	93
org.Gg.egGOCC	94
org.Gg.egGOMF	95
org.Gg.egPS	96
org.Gg.egSF	97
org.Gg.string	97
org.Hs.eg	98
org.Hs.egDGIdb	99
org.Hs.egDO	100
org.Hs.egGOBP	100
org.Hs.egGOCC	101
org.Hs.egGOMF	102
org.Hs.egHPCM	103
org.Hs.egHPMA	103
org.Hs.egHPMI	104
org.Hs.egHPPA	105
org.Hs.egMP	105
org.Hs.egMsigdbC1	106
org.Hs.egMsigdbC2BIOCARTA	107
org.Hs.egMsigdbC2CGP	108
org.Hs.egMsigdbC2CP	108
org.Hs.egMsigdbC2CPall	109
org.Hs.egMsigdbC2KEGG	110
org.Hs.egMsigdbC2REACTOME	111
org.Hs.egMsigdbC3MIR	111
org.Hs.egMsigdbC3TFT	112
org.Hs.egMsigdbC4CGN	113
org.Hs.egMsigdbC4CM	114
org.Hs.egMsigdbC5BP	114
org.Hs.egMsigdbC5CC	115
org.Hs.egMsigdbC5MF	116
org.Hs.egMsigdbC6	116
org.Hs.egMsigdbC7	117
org.Hs.egMsigdbH	118
org.Hs.egPS	118
org.Hs.egSF	120
org.Hs.PCommons_DN	120
org.Hs.PCommons_DN.source	122
org.Hs.PCommons_UN	123
org.Hs.string	125

org.Mm.eg	126
org.Mm.egDO	126
org.Mm.egGOBP	127
org.Mm.egGOCC	128
org.Mm.egGOMF	129
org.Mm.egHPCM	129
org.Mm.egHPMA	130
org.Mm.egHPMI	131
org.Mm.egHPPA	132
org.Mm.egMP	132
org.Mm.egPS	133
org.Mm.egSF	134
org.Mm.string	135
org.Rn.eg	136
org.Rn.egGOBP	137
org.Rn.egGOCC	137
org.Rn.egGOMF	138
org.Rn.egPS	139
org.Rn.egSF	140
org.Rn.string	140
RegulomeDB_SNPs	141
TCGA_mutations	142
UCSC_genes	143
visBoxplotAdv	143
visDAG	146
visGSEA	149
visNet	150
visNetAnimate	152
visNetArc	155
visNetCircle	157
visNetMul	159
visNetReorder	161
Index	164

CLL	<i>Transcriptome dataset for Chronic Lymphocytic Leukemia patients from Chuang et al. (2012)</i>
-----	--

Description

This dataset involves 130 patients with chronic lymphocytic leukemia (CLL). When enrolled in the study, these CLL patients had not received prior therapy for CLL. Additional covariate about the time to treatment (i.e. prognosis) is available. The dataset has been normalised and log2-transformed, and provided as an 'ExpressionSet' object.

Usage

```
CLL <- dRDataLoader(RData='CLL')
```

Value

an object of class "ExpressionSet". It has slots for "assayData", "phenoData", and "featureData":

- assayData: a matrix of 54675 features X 130 samples
- phenoData: variables describing sample phenotypes (i.e. columns in assayData), including information about samples: "Name" for sample names, "Time" for sampling time to first treatment (years) and "Treatment" for treatment event (1:yes, 0:no)
- featureData: variables describing features (i.e. rows in assayData), including information about features/genes: "EntrezID" for gene EntrezID, "Symbol" for gene symbol and "Desc" for gene description

References

Chuang et al. (2012). Subnetwork-based analysis of chronic lymphocytic leukemia identifies pathways that associate with disease progression. *Blood*, 120(13):2639-49.

Examples

```
CLL <- dRDataLoader(RData='CLL')
CLL
library(Biobase)
# extract information about the first 5 samples
pData(CLl)[1:5,]
# extract information about the first 5 features
fData(CLl)[1:5,]
```

dBUMfit

Function to fit a p-value distribution under beta-uniform mixture model

Description

dBUMfit is supposed to take as input a vector of p-values for deriving their distribution under beta-uniform mixture model (see Note below). The density distribution of input p-values is expressed as a mixture of two components: one for the null hypothesis (the noise component) and the other for the alternative hypothesis (the signal component). The noise component is the uniform density, while the signal component is the remainder of the mixture distribution. It returns an object of class "BUM".

Usage

```
dBUMfit(x, ntry = 1, hist.bum = T, contour.bum = T, verbose = T)
```

Arguments

x	a vector containing input p-values
ntry	an integer specifying how many tries are used to find the optimised parameters by maximum likelihood estimation
hist.bum	logical to indicate whether the histogram graph should be drawn

contour.bum	logical to indicate whether a contour plot should be drawn to show the log likelihood as a function of two parameters (a and lambda) in the beta-uniform mixture model
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

an object of class "BUM", a list with following elements:

- lambda: estimated mixture parameter
- a: estimated shape parameter
- NLL: Negative log-likelihood
- pvalues: the input pvalues
- call: the call that produced this result

Note

The probability density function of p-values under the Beta-Uniform Mixture model is formulated as: $f(x|\lambda, a) = \lambda + (1 - \lambda) * a * x^{a-1}$. The model names after mixing two distributions:

- the uniform distribution with the density function as $\frac{1}{b-a} \Big|_{a=0}^{b=1} = 1$
- the beta distribution with the density function as $\frac{\Gamma(a+b)}{\Gamma(a)\Gamma(b)} * x^{a-1} * (1-x)^{b-1} \Big|_{b=1} = a * x^{a-1}$

Both are mixed via λ . The mixture parameter λ measures the contribution from the uniform distribution. Accordingly, $1 - \lambda$ measures the contribution from the beta distribution. Notably, the probability density function of the beta distribution can be splitted into two parts (rather than the exclusive signal):

- the constant part as noise: $a * x^{a-1} \Big|_{x=1} = a$
- the rest part as signal: $a * (x^{a-1} - 1)$

In other words, there is no signal at $x = 1$ but all being noise. It is a conservative, upper bound estimation of the noise. Therefore, the probability density function in the model can be decomposed into signal-noise components:

- the signal component: $(1 - \lambda) * a * (x^{a-1} - 1)$
- the noise component: $\lambda + (1 - \lambda) * a$

It is misleading to simply view λ as the noise component and $(1 - \lambda) * a * x^{a-1}$ as the signal component, just as wrongly do in the literatures (e.g. <http://www.ncbi.nlm.nih.gov/pubmed/18586718>)

See Also

[dBUMscore](#)

Examples

```
# 1) generate an vector consisting of random values from beta distribution
x <- rbeta(1000, shape1=0.5, shape2=1)

# 2) fit a p-value distribution under beta-uniform mixture model
fit <- dBUMfit(x)
fit$lambda
fit$a
```

dBUMscore

Function to transform p-values into scores according to the fitted beta-uniform mixture model and/or after controlling false discovery rate

Description

dBUMscore is supposed to take as input a vector of p-values, which are transformed into scores according to the fitted beta-uniform mixture model. Also if the FDR threshold is given, it is used to make sure that p-values below this are considered significant and thus scored positively. Instead, those p-values above the given FDR are considered insignificant and thus scored negatively.

Usage

```
dBUMscore(fit, method = c("pdf", "cdf"), fdr = NULL, scatter.bum = T)
```

Arguments

fit	an object of class "BUM"
method	the method used for the transformation. It can be either "pdf" for the method based on the probability density function of the fitted model, or "cdf" for the method based on the cumulative distribution function of the fitted model
fdr	the given FDR threshold. By default, it is set to NULL, meaning there is no constraint. If given, those p-values with the FDR below this are considered significant and thus scored positively. Instead, those p-values with the FDR above this given FDR are considered insignificant and thus scored negatively
scatter.bum	logical to indicate whether the scatter graph of scores against p-values should be drawn. Also indicated is the p-value (called tau) corresponding to the given FDR threshold (if any)

Value

- scores: a vector of scores

Note

The transformation from the input p-value x to the score $S(x)$ is based on the fitted beta-uniform mixture model with two parameters λ and a : $f(x|\lambda, a) = \lambda + (1 - \lambda) * a * x^{a-1}$. Specifically, it considers the log-likelihood ratio between the signal and noise component of the model. The probability density function (pdf) of the signal component and the noise component are $(1 - \lambda) * a * (x^{a-1} - 1)$ and $\lambda + (1 - \lambda) * a$, respectively. Accordingly, the cumulative distribution function (cdf) of the signal component and the noise component are $\int_0^x (1 - \lambda) * a * (x^{a-1} - 1) dx$ and $\int_0^x \lambda + (1 - \lambda) * a dx$. In order to take into account the significance of the p-value, the *fdr* threshold

is also used for down-weighting the score. According to how to measure both components, there are two methods implemented for deriving the score $S(x)$:

- The method "pdf": $S(x) = \log_2 \frac{(1-\lambda)*a*(x^{a-1}-1)}{\lambda+(1-\lambda)*a} - \log_2 \frac{(1-\lambda)*a*(\tau^{a-1}-1)}{\lambda+(1-\lambda)*a} = \log_2 \left(\frac{x^{a-1}-1}{\tau^{a-1}-1} \right)$.
For the purpose of down-weighting scores, it must ensure $\log_2 \frac{(1-\lambda)*a*(\tau^{a-1}-1)}{\lambda+(1-\lambda)*a} \geq 0$, that is, the constraint via $\tau \leq \left(\frac{\lambda+2*a*(1-\lambda)}{a*(1-\lambda)} \right)^{\frac{1}{a-1}}$
- The method "cdf": $S(x) = \log_2 \frac{\int_0^x (1-\lambda)*a*(x^{a-1}-1) dx}{\int_0^x \lambda+(1-\lambda)*a dx} - \log_2 \frac{\int_0^\tau (1-\lambda)*a*(\tau^{a-1}-1) dx}{\int_0^\tau \lambda+(1-\lambda)*a dx} = \log_2 \frac{(1-\lambda)*(x^{a-1}-a)}{\lambda+(1-\lambda)*a} - \log_2 \frac{(1-\lambda)*(\tau^{a-1}-a)}{\lambda+(1-\lambda)*a} = \log_2 \left(\frac{x^{a-1}-a}{\tau^{a-1}-a} \right)$. For the purpose of down-weighting scores, it must ensure $\log_2 \frac{(1-\lambda)*(\tau^{a-1}-a)}{\lambda+(1-\lambda)*a} \geq 0$, that is, the constraint via $\tau \leq \left(\frac{\lambda+2*a*(1-\lambda)}{1-\lambda} \right)^{\frac{1}{a-1}}$
- Where $\tau = \left[\frac{\lambda+(1-\lambda)*a-fdr*\lambda}{fdr*(1-\lambda)} \right]^{\frac{1}{a-1}}$, i.e. the p-value corresponding to the exact fdr threshold.
It can be deduced from the definition of the false discovery rate: $fdr \doteq \frac{\int_0^\tau \lambda+(1-\lambda)*a dx}{\int_0^\tau \lambda+(1-\lambda)*a*x^{a-1} dx}$.
Notably, if the calculated τ exceeds the constraint, it will be reset to the maximum end of that constraint

See Also

[dBUMfit](#)

Examples

```
# 1) generate an vector consisting of random values from beta distribution
x <- rbeta(1000, shape1=0.5, shape2=1)

# 2) fit a p-value distribution under beta-uniform mixture model
fit <- dBUMfit(x)

# 3) calculate the scores according to the fitted BUM and fdr=0.01
# using "pdf" method
scores <- dBUMscore(fit, method="pdf", fdr=0.01)
# using "cdf" method
scores <- dBUMscore(fit, method="cdf", fdr=0.01)
```

dCheckParallel

Function to check whether parallel computing should be used and how

Description

dCheckParallel is used to check whether parallel computing should be used and how

Usage

```
dCheckParallel(multicores = NULL, verbose = T)
```

Arguments

multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

TRUE for using parallel computing; FALSE otherwise

Note

Whether parallel computation with multicores is used is system-specific. Also, it will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: `source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach", "doParallel"))`.

See Also

[dRWR](#), [dRWRcontact](#), [dRWRpipeline](#), [dDAGtermSim](#), [dDAGgeneSim](#)

Examples

```
#dCheckParallel(multicores=2)
```

dCommSignif

Function to test the significance of communities within a graph

Description

dCommSignif is supposed to test the significance of communities within a graph. For a community of the graph, it first calculates two types of degrees for each node: degrees based on partners only within the community itself, and the degrees based on its partners NOT in the community but in the graph. Then, it performs two-sample Wilcoxon tests on these two types of degrees to produce the significance level (p-value)

Usage

```
dCommSignif(g, comm)
```

Arguments

g	an object of class "igraph" or "graphNEL"
comm	an object of class "communities". Details on this class can be found at http://igraph.org/r/doc/communities.html

Value

- significance: a vector of p-values (significance)

Note

none

See Also

[dCommSignif](#)

Examples

```
# 1) generate an vector consisting of random values from beta distribution
x <- rbeta(1000, shape1=0.5, shape2=1)

# 2) fit a p-value distribution under beta-uniform mixture model
fit <- dBUMfit(x, ntry=1, hist.bum=FALSE, contour.bum=FALSE)

# 3) calculate the scores according to the fitted BUM and fdr=0.01
# using "pdf" method
scores <- dBUMscore(fit, method="pdf", fdr=0.05, scatter.bum=FALSE)
names(scores) <- as.character(1:length(scores))

# 4) generate a random graph according to the ER model
g <- erdos.renyi.game(1000, 1/100)

# 5) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 6) find the module with the maximum score
module <- dNetFind(subg, scores)

# 7) find the module and test its significance
comm <- walktrap.community(module, modularity=TRUE)
significance <- dCommSignif(module, comm)
```

dContrast

Function to help build the contrast matrix

Description

dContrast is used to help build the contrast matrix

Usage

```
dContrast(level_sorted, contrast.type = c("average", "zero",
"sequential",
"pairwise"))
```

Arguments

level_sorted	a vector of levels (usually sorted) which are contrasted to each other
contrast.type	the type of the contrast. It can be one of either 'average' for the contrast against the average of all levels, 'zero' for the contrast against the zero, 'sequential' for the contrast in a sequential order (it requires the levels being sorted properly), or 'pairwise' for the pairwise contrast.

Value

a list with following components:

- each: the contrast being specified
- name: the name of the contrast

Note

none

Examples

```
level_sorted <- c("L1", "L2", "L3", "L4")

# the contrast against the average of all levels
contrasts <- dContrast(level_sorted, contrast.type="average")

# the contrast against the zero
contrasts <- dContrast(level_sorted, contrast.type="zero")

# the contrast in a sequential order
contrasts <- dContrast(level_sorted, contrast.type="sequential")

# the pairwise contrast
contrasts <- dContrast(level_sorted, contrast.type="pairwise")
```

dDAGancestor	<i>Function to find common ancestors of two terms/nodes from a direct acyclic graph (DAG)</i>
--------------	---

Description

dDAGancestor is supposed to find a list of common ancestors shared by two terms/nodes, given a direct acyclic graph (DAG; an ontology). If two terms are given as NULL, then a sparse matrix of children x ancestors is built for all terms. If one of them is null, then a sparse matrix of children x ancestors is built but only for non-null input terms.

Usage

```
dDAGancestor(g, term1 = NULL, term2 = NULL, verbose = T)
```

Arguments

g	an object of class "igraph" or "graphNEL"
term1	the first term/node as input
term2	the second term/node as input
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

- When two terms are given: a list of terms/nodes that are common ancestors for two input terms/nodes
- When two terms are given as NULL: a sparse matrix of children x ancestors is built for all terms, with '1' for the reachable and otherwise '0'.
- When one of terms is given as NULL: a sparse matrix of children x ancestors is built but only for non-null input terms, with '1' for the reachable and otherwise '0'.

Note

none

See Also

[dDAGinduce](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) randomly give two terms
term1 <- sample(V(g)$name,1)
term2 <- sample(V(g)$name,1)

# 3) find common ancestors
dDAGancestor(g, term1, term2)
```

dDAGannotate

Function to generate a subgraph of a direct acyclic graph (DAG) induced by the input annotation data

Description

dDAGannotate is supposed to produce a subgraph induced by the input annotation data, given a direct acyclic graph (DAG; an ontology). The input is a graph of "igraph" or "graphNET" object, a list of the vertices containing annotation data, and the mode defining the paths to the root of DAG. The induced subgraph contains vertices (with annotation data) and their ancestors along with the defined paths to the root of DAG. The annotations at these vertices (including their ancestors) are also updated according to the true-path rule: a gene annotated to a term should also be annotated by its all ancestor terms.

Usage

```
dDAGannotate(g, annotations, path.mode = c("all_paths",
"shortest_paths",
"all_shortest_paths"), verbose = TRUE)
```

Arguments

<code>g</code>	an object of class "igraph" or "graphNEL"
<code>annotations</code>	the vertices/nodes for which annotation data are provided
<code>path.mode</code>	the mode of paths induced by vertices/nodes with input annotation data. It can be "all_paths" for all possible paths to the root, "shortest_paths" for only one path to the root (for each node in query), "all_shortest_paths" for all shortest paths to the root (i.e. for each node, find all shortest paths with the equal lengths)
<code>verbose</code>	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

- `subg`: an induced subgraph, an object of class "igraph". In addition to the original attributes to nodes and edges, the return subgraph is also appended by new node attributes: "annotations", which contains a list of genes either as original annotations or inherited annotations; "IC", which stands for information content defined as negative 10-based log-transformed frequency of genes annotated to that term.

Note

For the mode "shortest_paths", the induced subgraph is the most concise, and thus informative for visualisation when there are many nodes in query, while the mode "all_paths" results in the complete subgraph.

See Also

[dDAGinduce](#), [dDAGlevel](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) load human genes annotated by HPPA
org.Hs.egHPPA <- dRDataLoader(RData='org.Hs.egHPPA')
GS <- org.Hs.egHPPA # as 'GS' object

# 3) prepare for annotation data
# randomly select vertices with annotation data
annotations <- GS$gs[sample(1:length(GS$gs),5)]

# 4) obtain the induced subgraph
# 4a) based on all possible paths (i.e. the complete subgraph induced)
dDAGannotate(g, annotations, path.mode="all_paths", verbose=TRUE)
# 4b) based on shortest paths (i.e. the most concise subgraph induced)
dag <- dDAGannotate(g, annotations, path.mode="shortest_paths",
verbose=TRUE)

# 5) color-code nodes/terms according to the number of annotations
data <- sapply(V(dag)$annotations, length)
names(data) <- V(dag)$name
visDAG(g=dag, data=data, node.info="both")
```

dDAGgeneSim	<i>Function to calculate pair-wise semantic similarity between genes based on a direct acyclic graph (DAG) with annotated data</i>
-------------	--

Description

dDAGgeneSim is supposed to calculate pair-wise semantic similarity between genes based on a direct acyclic graph (DAG) with annotated data. It first calculates semantic similarity between terms and then derives semantic similarity between genes from terms-term semantic similarity. Parallel computing is also supported for Linux or Mac operating systems.

Usage

```
dDAGgeneSim(g, genes = NULL, method.gene = c("BM.average", "BM.max",
"BM.complete", "average", "max"), method.term = c("Resnik", "Lin",
"Schlicker", "Jiang", "Pesquita"), force = TRUE, fast = TRUE,
parallel = TRUE, multicores = NULL, verbose = TRUE)
```

Arguments

g	an object of class "igraph" or "graphNEL". It must contain a vertex attribute called 'annotations' for storing annotation data (see example for howto)
genes	the genes between which pair-wise semantic similarity is calculated. If NULL, all genes annotatable in the input dag will be used for calculation, which is very prohibitively expensive!
method.gene	the method used for how to derive semantic similarity between genes from semantic similarity between terms. It can be "average" for average similarity between any two terms (one from gene 1, the other from gene 2), "max" for the maximum similarity between any two terms, "BM.average" for best-matching (BM) based average similarity (i.e. for each term of either gene, first calculate maximum similarity to any term in the other gene, then take average of maximum similarity; the final BM-based average similarity is the pre-calculated average between two genes in pair), "BM.max" for BM based maximum similarity (i.e. the same as "BM.average", but the final BM-based maximum similarity is the maximum of the pre-calculated average between two genes in pair), "BM.complete" for BM-based complete-linkage similarity (inspired by complete-linkage concept: the least of any maximum similarity between a term of one gene and a term of the other gene). When comparing BM-based similarity between genes, "BM.average" and "BM.max" are sensitive to the number of terms involved; instead, "BM.complete" is much robust in this aspect. By default, it uses "BM.average".
method.term	the method used to measure semantic similarity between terms. It can be "Resnik" for information content (IC) of most informative common ancestor (MICA) (see http://arxiv.org/pdf/cmp-1g/9511007.pdf), "Lin" for $2 \cdot \text{IC}$ at MICA divided by the sum of IC at pairs of terms (see https://www.cse.iitb.ac.in/~cs626-449/Papers/WordSimilarity/3.pdf), "Schlicker" for weighted version of 'Lin' by the $1 - \text{prob}(\text{MICA})$ (see http://www.ncbi.nlm.nih.gov/pubmed/16776819), "Jiang" for $1 - \text{difference between the sum of IC at pairs of terms and } 2 \cdot \text{IC at MICA}$ (see http://arxiv.org/pdf/cmp-1g/9709008).

	pdf), "Pesquita" for graph information content similarity related to Tanimoto-Jacard index (ie. summed information content of common ancestors divided by summed information content of all ancestors of term1 and term2 (see http://www.ncbi.nlm.nih.gov/pubmed/18460186))
force	logical to indicate whether the only most specific terms (for each gene) will be used. By default, it sets to true. It is always advisable to use this since it is computationally fast but without compromising accuracy (considering the fact that true-path-rule has been applied when running dDAGannotate)
fast	logical to indicate whether a vectorised fast computation is used. By default, it sets to true. It is always advisable to use this vectorised fast computation; since the conventional computation is just used for understanding scripts
parallel	logical to indicate whether parallel computation with multicores is used. By default, it sets to true, but not necessarily does so. It will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: <code>source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach","doParallel"))</code> . If not yet installed, this option will be disabled
multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer. This option only works when parallel computation is enabled
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

It returns a sparse matrix containing pair-wise semantic similarity between input genes. This sparse matrix can be converted to the full matrix via the function `as.matrix`

Note

For the mode "shortest_paths", the induced subgraph is the most concise, and thus informative for visualisation when there are many nodes in query, while the mode "all_paths" results in the complete subgraph.

See Also

[dDAGtermSim](#), [dDAGinduce](#), [dDAGtip](#), [dCheckParallel](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) load human genes annotated by HPPA
org.Hs.egHPPA <- dRDataLoader(RData='org.Hs.egHPPA')

# 3) prepare for ontology and its annotation information
dag <- dDAGannotate(g, annotations=org.Hs.egHPPA,
path.mode="all_paths", verbose=TRUE)

# 4) calculate pair-wise semantic similarity between 5 randomly chosen genes
allgenes <- unique(unlist(V(dag)$annotations))
genes <- sample(allgenes,5)
```



```
sim <- dDAGgeneSim(g=dag, genes=genes, method.gene="BM.average",
method.term="Resnik", parallel=FALSE, verbose=TRUE)
sim
```

dDAGinduce	<i>Function to generate a subgraph of a direct acyclic graph (DAG) induced by given vertices</i>
------------	--

Description

dDAGinduce is supposed to produce a subgraph induced by given vertices, given a direct acyclic graph (DAG; an ontology). The input is a graph of "igraph" or "graphNEL" object, a list of the vertices of the graph, and the mode defining the paths to the root of DAG. The resultant subgraph inherits the class from the input one. The induced subgraph contains exactly the vertices of interest and their defined paths to the root of DAG.

Usage

```
dDAGinduce(g, nodes_query, path.mode = c("all_paths", "shortest_paths",
"all_shortest_paths"))
```

Arguments

g	an object of class "igraph" or "graphNEL"
nodes_query	the vertices for which the calculation is performed
path.mode	the mode of paths induced by nodes in query. It can be "all_paths" for all possible paths to the root, "shortest_paths" for only one path to the root (for each node in query), "all_shortest_paths" for all shortest paths to the root (i.e. for each node, find all shortest paths with the equal lengths)

Value

- subg: an induced subgraph, an object of class "igraph" or "graphNEL"

Note

For the mode "shortest_paths", the induced subgraph is the most concise, and thus informative for visualisation when there are many nodes in query, while the mode "all_paths" results in the complete subgraph.

See Also

[dDAGroot](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) randomly select vertices as the query nodes
# the query nodes can be igraph vertex sequences
```

```

nodes_query <- sample(V(g),5)
# more commonly, the query nodes can be term id
nodes_query <- sample(V(g),5)$name

# 3) obtain the induced subgraph
# 3a) based on all possible paths (i.e. the complete subgraph induced)
subg <- dDAGinduce(g, nodes_query, path.mode="all_paths")
# 3b) based on shortest paths (i.e. the most concise subgraph induced)
subg <- dDAGinduce(g, nodes_query, path.mode="shortest_paths")

```

dDAGlevel	<i>Function to define/calculate the level of nodes in a direct acyclic graph (DAG)</i>
-----------	--

Description

dDAGlevel is supposed to calculate the level of nodes, given a direct acyclic graph (DAG; an ontology). The input is a graph of "igraph" or "graphNET" object, and the definition of the node level. The return can be the level for each node or the nodes for each level.

Usage

```

dDAGlevel(g, level.mode = c("longest_path", "shortest_path"),
return.mode = c("node2level", "level2node"))

```

Arguments

g	an object of class "igraph" or "graphNEL"
level.mode	the mode of how to define the level of nodes in DAG. It can be "longest_path" for defining the node level as the length of the longest path from the node to the root, and "shortest_paths" for defining the node level as the length of the shortest path from the node to the root
return.mode	the mode of how to return the node level information. It can be "node2level" for returning a named vector (i.e. the level for each node), and "level2node" for returning a named list (i.e. nodes for each level)

Value

When "return.mode" is "node2level", it returns a named vector: for each named node (i.e. Term ID), it stores its level. When "return.mode" is "level2node", it returns a named list: for each named level, it contains the names (i.e. Term ID) of nodes belonging to this level.

Note

The level for the root is 1. The level based on the longest path will ensure that nodes at the same level will never be reachable (i.e. in the same path), while the level based on the shortest path will not be necessary. The "longest path" based level can be useful in visiting nodes from the tipmost level to the root: 1) for the current node, all children have been visited; 2) nodes at the same level can be looked at independantly. The "shortest path" based level can be useful in deriving nodes according to their closeness to the root.

See Also

[dDAGroot](#), [dDAGreverse](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) randomly select vertices as the query nodes
nodes_query <- sample(V(g),5)$name

# 3) obtain the complete subgraph induced
subg <- dDAGinduce(g, nodes_query)

# 4) calculate the node levels
# 4a) definition based on the longest path
dDAGlevel(subg, level.mode="longest_path")
# 4b) definition based on the shortest path
dDAGlevel(subg, level.mode="shortest_path")
# 4c) definition based on the longest path, and return nodes for each level
dDAGlevel(subg, level.mode="longest_path", return.mode="level2node")
```

dDAGreverse

Function to reverse the edge direction of a direct acyclic graph (DAG)

Description

dDAGreverse is supposed to reverse the edge direction of a direct acyclic graph (DAG; an ontology). The return graph remains all attributes associated on nodes and edges.

Usage

```
dDAGreverse(g)
```

Arguments

g an object of class "igraph" or "graphNEL"

Value

- gr: a graph being reversed, an object of class "igraph" or "graphNEL"

Note

none

See Also

[dDAGreverse](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <-dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) the graph with reverse edge direction
gr <- dDAGreverse(g)
gr
```

dDAGroot

Function to find the root node of a direct acyclic graph (DAG)

Description

dDAGroot is supposed to find the root node of a direct acyclic graph (DAG; an ontology). It return the name (i.e Term ID) of the root node.

Usage

```
dDAGroot(g)
```

Arguments

g an object of class "igraph" or "graphNEL"

Value

- root: the root name (i.e. Term ID)

Note

none

See Also

[dDAGroot](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <-dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) find the root
root <- dDAGroot(g)
root
```

dDAGtermSim	<i>Function to calculate pair-wise semantic similarity between input terms based on a direct acyclic graph (DAG) with annotated data</i>
-------------	--

Description

dDAGtermSim is supposed to calculate pair-wise semantic similarity between input terms based on a direct acyclic graph (DAG) with annotated data. Parallel computing is also supported for Linux or Mac operating systems.

Usage

```
dDAGtermSim(g, terms = NULL, method = c("Resnik", "Lin", "Schlicker",
"Jiang", "Pesquita"), fast = T, parallel = TRUE, multicores = NULL,
verbose = T)
```

Arguments

g	an object of class "igraph" or "graphNEL". It must contain a vertex attribute called 'annotations' for storing annotation data (see example for howto)
terms	the terms/nodes between which pair-wise semantic similarity is calculated. If NULL, all terms in the input DAG will be used for calculation, which is very prohibitively expensive!
method	the method used to measure semantic similarity between input terms. It can be "Resnik" for information content (IC) of most informative common ancestor (MICA) (see http://arxiv.org/pdf/cmp-lg/9511007.pdf), "Lin" for $2 \cdot \text{IC}$ at MICA divided by the sum of IC at pairs of terms (see https://www.cse.iitb.ac.in/~cs626-449/Papers/WordSimilarity/3.pdf), "Schlicker" for weighted version of 'Lin' by the $1 - \text{prob}(\text{MICA})$ (see http://www.ncbi.nlm.nih.gov/pubmed/16776819), "Jiang" for $1 - \text{difference between the sum of IC at pairs of terms and } 2 \cdot \text{IC at MICA}$ (see http://arxiv.org/pdf/cmp-lg/9709008.pdf), "Pesquita" for graph information content similarity related to Tanimoto-Jacard index (ie. summed information content of common ancestors divided by summed information content of all ancestors of term1 and term2 (see http://www.ncbi.nlm.nih.gov/pubmed/18460186)). By default, it uses "Schlicker" method
fast	logical to indicate whether a vectorised fast computation is used. By default, it sets to true. It is always advisable to use this vectorised fast computation; since the conventional computation is just used for understanding scripts
parallel	logical to indicate whether parallel computation with multicores is used. By default, it sets to true, but not necessarily does so. It will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: <code>source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach", "doParallel"))</code> . If not yet installed, this option will be disabled
multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer. This option only works when parallel computation is enabled
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

It returns a sparse matrix containing pair-wise semantic similarity between input terms. This sparse matrix can be converted to the full matrix via the function `as.matrix`

Note

none

See Also

[dDAGinduce](#), [dDAGancestor](#), [dDAGgeneSim](#), [dCheckParallel](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) load human genes annotated by HPPA
org.Hs.egHPPA <- dRDataLoader(RData='org.Hs.egHPPA')

# 3) prepare for ontology and its annotation information
dag <- dDAGannotate(g, annotations=org.Hs.egHPPA,
  path.mode="all_paths", verbose=TRUE)

# 4) calculate pair-wise semantic similarity between 5 randomly chosen terms
terms <- sample(V(dag)$name, 5)
sim <- dDAGtermSim(g=dag, terms=terms, method="Schlicker",
  parallel=FALSE)
sim
```

dDAGtip

Function to find the tip node(s) of a direct acyclic graph (DAG)

Description

dDAGtip is supposed to find the tip node(s) of a direct acyclic graph (DAG; an ontology). It return the name (i.e Term ID) of the tip node(s).

Usage

```
dDAGtip(g)
```

Arguments

`g` an object of class "igraph" or "graphNEL"

Value

- tip: the tip name (i.e. Term ID)

Note

none

See Also[dDAGtip](#)**Examples**

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) find tips
tips <- dDAGtip(g)
tips
```

dEnricher

Function to conduct enrichment analysis given the input data and the ontology in query

Description

dEnricher is supposed to conduct enrichment analysis given the input data and the ontology in query. It returns an object of class "eTerm". Enrichment analysis is based on either Fisher's exact test or Hypergeometric test. The test can respect the hierarchy of the ontology.

Usage

```
dEnricher(data, identity = c("symbol", "entrez"),
check.symbol.identity = FALSE, genome = c("Hs", "Mm", "Rn", "Gg", "Ce",
"Dm", "Da", "At"), ontology = c("GOBP", "GOMF", "GOCC", "PS", "PS2",
"SF",
"DO", "HPPA", "HPMI", "HPCM", "HPMA", "MP", "MsigdbH", "MsigdbC1",
"MsigdbC2CGP", "MsigdbC2CP", "MsigdbC2KEGG", "MsigdbC2REACTOME",
"MsigdbC2BIOCARTA", "MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN",
"MsigdbC4CM",
"MsigdbC5BP", "MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7",
"DGIdb"),
sizeRange = c(10, 1000), min.overlap = 3, which_distance = NULL,
test = c("HypergeoTest", "FisherTest", "BinomialTest"),
p.adjust.method = c("BH", "BY", "bonferroni", "holm", "hochberg",
"hommel"),
ontology.algorithm = c("none", "pc", "elim", "lea"), elim.pvalue =
0.01,
lea.depth = 2, verbose = T,
RData.location =
"https://github.com/hfang-bristol/RDataCentre/blob/master/dnet/1.0.7")
```

Arguments

data	an input vector. It contains either Entrez Gene ID or Symbol
identity	the type of gene identity (i.e. row names of input data), either "symbol" for gene symbols (by default) or "entrez" for Entrez Gene ID. The option "symbol" is preferred as it is relatively stable from one update to another; also it is possible to search against synonyms (see the next parameter)

check.symbol.identity	logical to indicate whether synonyms will be searched against when gene symbols cannot be matched. By default, it sets to FALSE since it may take a while to do such check using all possible synoymns
genome	the genome identity. It can be one of "Hs" for human, "Mm" for mouse, "Rn" for rat, "Gg" for chicken, "Ce" for c.elegans, "Dm" for fruitfly, "Da" for zebrafish, and "At" for arabidopsis
ontology	the ontology supported currently. It can be "GOBP" for Gene Ontology Biological Process, "GOMF" for Gene Ontology Molecular Function, "GOCC" for Gene Ontology Cellular Component, "PS" for phylostratific age information, "PS2" for the collapsed PS version (inferred ancestors being collapsed into one with the known taxonomy information), "SF" for domain superfamily assignments, "DO" for Disease Ontology, "HPPA" for Human Phenotype Phenotypic Abnormality, "HPMI" for Human Phenotype Mode of Inheritance, "HPCM" for Human Phenotype Clinical Modifier, "HPMA" for Human Phenotype Mortality Aging, "MP" for Mammalian Phenotype, and Drug-Gene Interaction database (DGIdb) and the molecular signatures database (Msigdb) only in human (including "MsigdbH", "MsigdbC1", "MsigdbC2CGP", "MsigdbC2CP", "MsigdbC2KEGG", "MsigdbC2REACTOME", "MsigdbC2BIOCARTA", "MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN", "MsigdbC4CM", "MsigdbC5BP", "MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7"). Note: These four ("GOBP", "GOMF", "GOCC" and "PS") are availble for all genomes/species; for "Hs" and "Mm", these six ("DO", "HPPA", "HPMI", "HPCM", "HPMA" and "MP") are also supported; all "Msigdb" are only supported in "Hs". For details on the eligibility for pairs of input genome and ontology, please refer to the online Documentations at http://supfam.org/dnet/docs.html
sizeRange	the minimum and maximum size of members of each gene set in consideration. By default, it sets to a minimum of 10 but no more than 1000
min.overlap	the minimum number of overlaps. Only those gene sets that overlap with input data at least min.overlap (3 by default) will be processed
which_distance	which distance of terms in the ontology is used to restrict terms in consideration. By default, it sets to 'NULL' to consider all distances
test	the statistic test used. It can be "FisherTest" for using fisher's exact test, "HypergeoTest" for using hypergeometric test, or "BinomialTest" for using binomial test. Fisher's exact test is to test the independence between gene group (genes belonging to a group or not) and gene annotation (genes annotated by a term or not), and thus compare sampling to the left part of background (after sampling without replacement). Hypergeometric test is to sample at random (without replacement) from the background containing annotated and non-annotated genes, and thus compare sampling to background. Unlike hypergeometric test, binomial test is to sample at random (with replacement) from the background with the constant probability. In terms of the ease of finding the significance, they are in order: hypergeometric test > binomial test > fisher's exact test. In other words, in terms of the calculated p-value, hypergeometric test < binomial test < fisher's exact test
p.adjust.method	the method used to adjust p-values. It can be one of "BH", "BY", "bonferroni", "holm", "hochberg" and "hommel". The first two methods "BH" (widely used) and "BY" control the false discovery rate (FDR: the expected proportion of false discoveries amongst the rejected hypotheses); the last four methods "bonferroni", "holm", "hochberg" and "hommel" are designed to give strong control of

	the family-wise error rate (FWER). Notes: FDR is a less stringent condition than FWER
ontology.algorithm	the algorithm used to account for the hierarchy of the ontology. It can be one of "none", "pc", "elim" and "lea". For details, please see 'Note'
elim.pvalue	the parameter only used when "ontology.algorithm" is "elim". It is used to control how to declare a significantly enriched term (and subsequently all genes in this term are eliminated from all its ancestors)
lea.depth	the parameter only used when "ontology.algorithm" is "lea". It is used to control how many maximum depth is used to consider the children of a term (and subsequently all genes in these children term are eliminated from the use for the recalculation of the significance at this term)
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to false for no display
RData.location	the characters to tell the location of built-in RData files. By default, it remotely locates at https://github.com/hfang-bristol/RDataCentre/blob/master/dnet and http://dnet.r-forge.r-project.org/RData . Be aware of several versions and the latest one is matched to the current package version. For the user equipped with fast internet connection, this option can be just left as default. But it is always advisable to download these files locally. Especially when the user needs to run this function many times, there is no need to ask the function to remotely download every time (also it will unnecessarily increase the runtime). For examples, these files (as a whole or part of them) can be first downloaded into your current working directory, and then set this option as: <code>RData.location = "."</code> . Surely, the location can be anywhere as long as the user provides the correct path pointing to (otherwise, the script will have to remotely download each time). Here is the UNIX command for downloading all RData files (preserving the directory structure): <code>wget -r -l2 -A "*.RData" -np -nH --cut-dirs = 0 http://dnet.r-forge.r-project.org/RData</code>

Value

an object of class "eTerm", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene set in consideration, and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"
- `data`: a vector containing input data in consideration. It is not always the same as the input data as only those mappable are retained
- `overlap`: a list of overlapped gene sets, each storing genes overlapped between a gene set and the given input data (i.e. the genes of interest). Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"
- `zscore`: a vector containing z-scores
- `pvalue`: a vector containing p-values
- `adjp`: a vector containing adjusted p-values. It is the p value but after being adjusted for multiple comparisons
- `call`: the call that produced this result

Note

The interpretation of the algorithms used to account for the hierarchy of the ontology is:

- "none": does not consider the ontology hierarchy at all.
- "lea": computes the significance of a term in terms of the significance of its children at the maximum depth (e.g. 2). Precisely, once genes are already annotated to any children terms with a more significance than itself, then all these genes are eliminated from the use for the recalculation of the significance at that term. The final p-values takes the maximum of the original p-value and the recalculated p-value.
- "elim": computes the significance of a term in terms of the significance of its all children. Precisely, once genes are already annotated to a significantly enriched term under the cutoff of e.g. $pvalue < 1e-2$, all these genes are eliminated from the ancestors of that term).
- "pc": requires the significance of a term not only using the whole genes as background but also using genes annotated to all its direct parents/ancestors as background. The final p-value takes the maximum of both p-values in these two calculations.
- "Notes": the order of the number of significant terms is: "none" > "lea" > "elim" > "pc".

See Also

[dEnricherView](#)

Examples

```
# load data
library(Biobase)
TCGA_mutations <- dRDataLoader(RData='TCGA_mutations')
symbols <- as.character(fData(TCGA_mutations)$Symbol)

# Enrichment analysis using Disease Ontology (DO)
data <- symbols[1:100] # select the first 100 human genes
eTerm <- dEnricher(data, identity="symbol", genome="Hs", ontology="DO")

# visualise the top significant terms in the ontology hierarchy
ig.DO <- dRDataLoader(RData='ig.DO')
g <- ig.DO
nodes_query <- names(sort(eTerm$adjp)[1:5])
nodes.highlight <- rep("red", length(nodes_query))
names(nodes.highlight) <- nodes_query
subg <- dDAGinduce(g, nodes_query)
# color-code terms according to the adjust p-values (taking the form of 10-based negative logarithm)
visDAG(g=subg, data=-1*log10(eTerm$adjp[V(subg)$name]),
node.info="both", zlim=c(0,2), node.attrs=list(color=nodes.highlight))
# color-code terms according to the z-scores
visDAG(g=subg, data=eTerm$zscore[V(subg)$name], node.info="both",
colormap="darkblue-white-darkorange",
node.attrs=list(color=nodes.highlight))
```

dEnricherView	<i>Function to view enrichment results of dEnricher</i>
---------------	---

Description

dEnricherView is supposed to view results of enrichment analysis by [dEnricher](#).

Usage

```
dEnricherView(eTerm, top_num = 10, sortBy = c("adjp", "pvalue",  
"zscore",  
"nAnno", "nOverlap", "none"), decreasing = NULL, details = F)
```

Arguments

eTerm	an object of class "eTerm"
top_num	the maximum number of gene sets (terms) will be viewed
sortBy	which statistics will be used for sorting and viewing gene sets (terms). It can be "adjp" for adjusted p value, "pvalue" for p value, "zscore" for enrichment z-score, "nAnno" for the number of sets (terms), "nOverlap" for the number in overlaps, and "none" for ordering according to ID of gene sets (terms)
decreasing	logical to indicate whether to sort in a decreasing order. If it is null, it would be true for "zscore", "nAnno" or "nOverlap"; otherwise it would be false
details	logical to indicate whether the detailed information of gene sets (terms) is also viewed. By default, it sets to false for no inclusion

Value

a data frame with following components:

- setID: term ID; as rownames
- name: term name
- nAnno: number in gene members annotated by a term
- nOverlap: number in overlaps
- zscore: enrichment z-score
- pvalue: nominal p value
- adjp: adjusted p value
- namespace: term namespace; optional, it is only appended when "details" is true
- distance: term distance; optional, it is only appended when "details" is true
- members: members (represented as Gene Symbols) in overlaps; optional, it is only appended when "details" is true

Note

none

See Also

[dEnricher](#)

Examples

```
#dEnricherView(eTerm, top_num=10, sortBy="adjp", decreasing=FALSE, details=TRUE)
```

dFDRscore	<i>Function to transform fdr into scores according to log-likelihood ratio between the true positives and the false positivies and/or after controlling false discovery rate</i>
-----------	--

Description

dFDRscore is supposed to take as input a vector of fdr, which are transformed into scores according to log-likelihood ratio between the true positives and the false positivies. Also if the FDR threshold is given, it is used to make sure that fdr below threshold are considered significant and thus scored positively. Instead, those fdr above the given threshold are considered insignificant and thus scored negatively.

Usage

```
dFDRscore(fdr, fdr.threshold = NULL, scatter = F)
```

Arguments

fdr	a vector containing a list of input fdr
fdr.threshold	the given FDR threshold. By default, it is set to NULL, meaning there is no constraint. If given, those fdr with the FDR below threshold are considered significant and thus scored positively. Instead, those fdr with the FDR above given threshold are considered insignificant and thus scored negatively
scatter	logical to indicate whether the scatter graph of scores against p-values should be drawn. Also indicated is the score corresponding to the given FDR threshold (if any)

Value

- scores: a vector of scores

Note

none

See Also

[dSVDsignif](#), [dNetPipeline](#)

Examples

```
# 1) generate data with an iid matrix of 1000 x 9
data <- cbind(matrix(rnorm(1000*3,mean=0,sd=1), nrow=1000, ncol=3),
matrix(rnorm(1000*3,mean=0.5,sd=1), nrow=1000, ncol=3),
matrix(rnorm(1000*3,mean=-0.5,sd=1), nrow=1000, ncol=3))

# 2) calculate the significance according to SVD
# using "fdr" significance
```

```
fdr <- dSVDsignif(data, signif="fdr", num.permutation=10)

# 3) calculate the scores according to the fitted BUM and fdr=0.01
# no fdr threshold
scores <- dFDRscore(fdr)
# using fdr threshold of 0.01
scores <- dFDRscore(fdr, fdr.threshold=0.1, scatter=TRUE)
```

dFunArgs	<i>Function to assign (and evaluate) arguments with default values for an input function</i>
----------	--

Description

dFunArgs is supposed to assign (and evaluate) arguments with default values for an input function.

Usage

```
dFunArgs(fun, action = F, verbose = T)
```

Arguments

fun	an input function name (character string)
action	logical to indicate whether the function will act as it should be (with assigned values in the current environment). By default, it sets to FALSE
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to TRUE for display

Value

a list containing arguments and their default values

Note

This function is potentially useful when debugging. Because the developer does not have to specify default values for all arguments except those arguments are of interest

See Also

[dNetPipeline](#)

Examples

```
fun <- "dNetPipeline"
dFunArgs(fun)
```

dGSEA

Function to conduct gene set enrichment analysis given the input data and the ontology in query

Description

dGSEA is supposed to conduct gene set enrichment analysis given the input data and the ontology in query. It returns an object of class "eTerm".

Usage

```
dGSEA(data, identity = c("symbol", "entrez"), check.symbol.identity =
FALSE,
genome = c("Hs", "Mm", "Rn", "Gg", "Ce", "Dm", "Da", "At"),
ontology = c("GOBP", "GOMF", "GOCC", "PS", "PS2", "SF", "DO", "HPPA",
"HPMI", "HPCM", "HPMA", "MP", "MsigdbH", "MsigdbC1", "MsigdbC2CGP",
"MsigdbC2CP", "MsigdbC2KEGG", "MsigdbC2REACTOME", "MsigdbC2BIOCARTA",
"MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN", "MsigdbC4CM",
"MsigdbC5BP",
"MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7", "DGIdb",
"Customised"),
customised.genesets = NULL, sizeRange = c(10, 20000),
which_distance = NULL, weight = 1, nperm = 1000, fast = T,
sigTail = c("two-tails", "one-tail"), p.adjust.method = c("BH", "BY",
"bonferroni", "holm", "hochberg", "hommel"), verbose = T,
RData.location =
"https://github.com/hfang-bristol/RDataCentre/blob/master/dnet/1.0.7")
```

Arguments

data	a data frame or matrix of input data. It must have row names, either Entrez Gene ID or Symbol
identity	the type of gene identity (i.e. row names of input data), either "symbol" for gene symbols (by default) or "entrez" for Entrez Gene ID. The option "symbol" is preferred as it is relatively stable from one update to another; also it is possible to search against synonyms (see the next parameter)
check.symbol.identity	logical to indicate whether synonyms will be searched against when gene symbols cannot be matched. By default, it sets to FALSE since it may take a while to do such check using all possible synonyms
genome	the genome identity. It can be one of "Hs" for human, "Mm" for mouse, "Rn" for rat, "Gg" for chicken, "Ce" for c.elegans, "Dm" for fruitfly, "Da" for zebrafish, and "At" for arabidopsis
ontology	the ontology supported currently. It can be "GOBP" for Gene Ontology Biological Process, "GOMF" for Gene Ontology Molecular Function, "GOCC" for Gene Ontology Cellular Component, "PS" for phylostratific age information, "PS2" for the collapsed PS version (inferred ancestors being collapsed into one with the known taxonomy information), "SF" for domain superfamily assignments, "DO" for Disease Ontology, "HPPA" for Human Phenotype Phenotypic Abnormality, "HPMI" for Human Phenotype Mode of Inheritance,

"HPCM" for Human Phenotype Clinical Modifier, "HPMA" for Human Phenotype Mortality Aging, "MP" for Mammalian Phenotype, and Drug-Gene Interaction database (DGIdb) and the molecular signatures database (Msigdb) only in human (including "MsigdbH", "MsigdbC1", "MsigdbC2CGP", "MsigdbC2CP", "MsigdbC2KEGG", "MsigdbC2REACTOME", "MsigdbC2BIOCARTA", "MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN", "MsigdbC4CM", "MsigdbC5BP", "MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7"). Note: These four ("GOBP", "GOMF", "GOCC" and "PS") are available for all genomes/species; for "Hs" and "Mm", these six ("DO", "HPPA", "HPMI", "HPCM", "HPMA" and "MP") are also supported; all "Msigdb" are only supported in "Hs". For details on the eligibility for pairs of input genome and ontology, please refer to the online Documentations at <http://supfam.org/dnet/docs.html>. Also supported are the user-customised gene sets; in doing so, the option "Customised" should be used together with the input of the next parameter "customised.genesets"

customised.genesets	an input vector/matrix/list which only works when the user chooses "Customised" in the previous parameter "ontology". It contains either Entrez Gene ID or Symbol
sizeRange	the minimum and maximum size of members of each gene set in consideration. By default, it sets to a minimum of 10 but no more than 1000
which_distance	which distance of terms in the ontology is used to restrict terms in consideration. By default, it sets to 'NULL' to consider all distances
weight	type of score weight. It can be "0" for unweighted (an equivalent to Kolmogorov-Smirnov, only considering the rank), "1" for weighted by input gene score (by default), and "2" for over-weighted, and so on
nperm	the number of random permutations. For each permutation, gene-score associations will be permuted so that permutation of gene-term associations is realised
fast	logical to indicate whether to fast calculate expected results from permuted data. By default, it sets to true
sigTail	the tail used to calculate the statistical significance. It can be either "two-tails" for the significance based on two-tails or "one-tail" for the significance based on one tail
p.adjust.method	the method used to adjust p-values. It can be one of "BH", "BY", "bonferroni", "holm", "hochberg" and "hommel". The first two methods "BH" (widely used) and "BY" control the false discovery rate (FDR: the expected proportion of false discoveries amongst the rejected hypotheses); the last four methods "bonferroni", "holm", "hochberg" and "hommel" are designed to give strong control of the family-wise error rate (FWER). Notes: FDR is a less stringent condition than FWER
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to false for no display
RData.location	the characters to tell the location of built-in RData files. By default, it remotely locates at https://github.com/hfang-bristol/RDataCentre/blob/master/dnet and http://dnet.r-forge.r-project.org/RData . Be aware of several versions and the latest one is matched to the current package version. For the user equipped with fast internet connection, this option can be just left as default. But it is always advisable to download these files locally. Especially when the user needs to run this function many times, there is no need to ask the function to remotely download every time (also it will unnecessarily increase the

runtime). For examples, these files (as a whole or part of them) can be first downloaded into your current working directory, and then set this option as: *RData.location = "."*. Surely, the location can be anywhere as long as the user provides the correct path pointing to (otherwise, the script will have to remotely download each time). Here is the UNIX command for downloading all RData files (preserving the directory structure): *wget -r -l2 -A "*.RData" -np -nH --cut-dirs = 0 http://dnet.r-forge.r-project.org/RData*

Value

an object of class "eTerm", a list with following components:

- *set_info*: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene set in consideration, and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- *gs*: a list of gene sets, each storing gene members. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"
- *data*: a matrix of nGene X nSample containing input data in consideration. It is not always the same as the input data as only those mappable are retained
- *es*: a matrix of nSet X nSample containing enrichment score, where nSample is the number of samples (i.e. the number of columns in input data)
- *nes*: a matrix of nSet X nSample containing normalised enrichment score. It is the version of enrichment score but after being normalised by gene set size
- *pvalue*: a matrix of nSet X nSample containing nominal p value
- *adjp*: a matrix of nSet X nSample containing adjusted p value. It is the p value but after being adjusted for multiple comparisons
- *gadjp*: a matrix of nSet X nSample containing globally adjusted p value in terms of all samples
- *fdr*: a matrix of nSet X nSample containing false discovery rate (FDR). It is the estimated probability that the normalised enrichment score represents a false positive finding
- *qvalue*: a matrix of nSet X nSample containing q value. It is the monotonically increasing FDR
- *weight*: the input type of score weight
- *call*: the call that produced this result

Note

The interpretation of returned components:

- "es": enrichment score for the gene set is the degree to which this gene set is overrepresented at the top or bottom of the ranked list of genes in each column of input data;
- "nes": normalised enrichment score for the gene set is enrichment score that has already normalised by gene set size. It is comparable across analysed gene sets;
- "pvalue": nominal p value is the statistical significance of the enrichment score. It is not adjusted for multiple hypothesis testing, and thus is of limited use in comparing gene sets;
- "adjp": adjusted p value by Benjamini & Hochberg method. It is comparable across gene sets;
- "gadjp": globally adjusted p value by Benjamini & Hochberg method. Unlike "adjp", it is adjusted in terms of all samples;

- "fdr": false discovery rate is the estimated probability that the normalised enrichment score represents a false positive finding. Unlike "adjp" or "gadjp" (also aliased as "fdr") that is derived from a list of p values, this version of fdr is directly calculate from the statistic (i.e. normalised enrichment score);
- "qvalue": q value is the monotonically increasing FDR so that the higher "nes", the lower "qvalue".

See Also

[dGSEAvieW](#), [dGSEAwrite](#), [visGSEA](#)

Examples

```
# load data
library(Biobase)
TCGA_mutations <- dRDataLoader(RData='TCGA_mutations')

# gene set enrichment analysis (GSEA) using KEGG pathways
## calculate the total mutations for each gene
tol <- apply(exprs(TCGA_mutations), 1, sum)
data <- data.frame(tol=tol)
eTerm <- dGSEA(data, identity="symbol", genome="Hs",
  ontology="MsigdbC2KEGG")
res <- dGSEAvieW(eTerm, which_sample=1, top_num=5, sortBy="adjp",
  decreasing=FALSE, details=TRUE)
visGSEA(eTerm, which_sample=1, which_term=rownames(res)[1])
output <- dGSEAwrite(eTerm, which_content="gadjp", which_score="gadjp",
  filename="eTerm.txt")

## based on customised gene sets
eTerm <- dGSEA(data, identity="symbol", genome="Hs",
  ontology="Customised", customised_genesets=sample(rownames(data),100))
res <- dGSEAvieW(eTerm, which_sample=1, top_num=5, sortBy="adjp",
  decreasing=FALSE, details=TRUE)
visGSEA(eTerm, which_sample=1, which_term=rownames(res)[1])
```

dGSEAvieW

Function to view enrichment results in a sample-specific manner

Description

dGSEAvieW is supposed to view results of gene set enrichment analysis but for a specific sample.

Usage

```
dGSEAvieW(eTerm, which_sample = 1, top_num = 10, sortBy = c("adjp",
  "gadjp", "ES", "nES", "pvalue", "FWER", "FDR", "qvalue", "none"),
  decreasing = NULL, details = F)
```

Arguments

eTerm	an object of class "eTerm"
which_sample	which sample will be viewed
top_num	the maximum number of gene sets will be viewed
sortBy	which statistics will be used for sorting and viewing gene sets. It can be "adjp" for adjusted p value, "gadjp" for globally adjusted p value, "ES" for enrichment score, "nES" for normalised enrichment score, "pvalue" for p value, "FWER" for family-wise error rate, "FDR" for false discovery rate, "qvalue" for q value, "none" for sorting by setID
decreasing	logical to indicate whether to sort in a decreasing order. If it is null, it would be true for "ES" or "nES"; otherwise it would be false
details	logical to indicate whether the detail information of gene sets is also viewed. By default, it sets to false for no inclusion

Value

a data frame with following components:

- setID: term ID
- ES: enrichment score
- nES: normalised enrichment score
- pvalue: nominal p value
- adjp: adjusted p value
- gadjp: globally adjusted p value
- FDR: false discovery rate
- qvalue: q value
- setSize: the number of genes in the set; optional, it is only appended when "details" is true
- name: term name; optional, it is only appended when "details" is true
- namespace: term namespace; optional, it is only appended when "details" is true
- distance: term distance; optional, it is only appended when "details" is true

Note

none

See Also

[dGSEA](#)

Examples

```
#dGSEAView(eTerm, which_sample=1, top_num=10, sortBy="adjp", decreasing=FALSE, details=TRUE)
```

dGSEAwrite

*Function to write out enrichment results***Description**

dGSEAwrite is supposed to write out enrichment results.

Usage

```
dGSEAwrite(eTerm, which_content = c("gadjp", "adjp", "pvalue", "FWER",
  "FDR",
  "qvalue", "nES", "ES"), which_score = c("gadjp", "adjp", "FWER", "FDR",
  "qvalue", "nES"), cutoff = 0.1, filename = NULL, keep.significance = T)
```

Arguments

eTerm	an object of class "eTerm"
which_content	the content will be written out. It includes two categories: i) based on "adjp" for adjusted p value, "gadjp" for globally adjusted p value, "pvalue" for p value, "FWER" for family-wise error rate, "FDR" for false discovery rate, "qvalue" for q value; ii) based on "ES" for enrichment score, "nES" for normalised enrichment score. For the former, the content is : first $-1 \cdot \log_{10}$ -transformed, and then multiplied by -1 if nES is negative.
which_score	which statistics/score will be used for declaring the significance. It can be "adjp" for adjusted p value, "gadjp" for globally adjusted p value, "FWER" for family-wise error rate, "FDR" for false discovery rate, "qvalue" for q value
cutoff	a cutoff to declare the significance. It should be used together with 'which_score'
filename	a character string naming a filename
keep.significance	logical to indicate whether or not to mask those insignificant by NA. By default, it sets to true to mask those insignificant by NA

Value

a data frame with following components:

- setID: term ID
- setSize: the number of genes in the set
- name: term name
- namespace: term namespace
- distance: term distance
- sample names: sample names in the next columns

Note

If "filename" is not NULL, a tab-delimited text file will be also written out.

See Also

[dGSEA](#)

Examples

```
#output <- dGSEAwrite(eTerm, which_content="gadjp", which_score="gadjp", filename="eTerm.txt")
```

dNetConfidence	<i>Function to append the confidence information from the source graphs into the target graph</i>
----------------	---

Description

eConsensusGraph is supposed to append the confidence information (extracted from a list of the source graphs) into the target graph. The confidence information is about how often a node (or an edge) in the target graph that can be found in the input source graphs. The target graph is an object of class "igraph" or "graphNEL", and the source graphs are a list of objects of class "igraph" or "graphNEL". It also returns an object of class "igraph" or "graphNEL"; specifically, the same as the input target graph but appended with the "nodeConfidence" attribute to the nodes and the "edgeConfidence" attribute to the edges.

Usage

```
dNetConfidence(target, sources, plot = F)
```

Arguments

target	the target graph, an object of class "igraph" or "graphNEL"
sources	a list of the source graphs, each with an object of class "igraph" or "graphNEL". These source graphs will be used to calculate how often a node (or an edge) in the target graph that can be found with them.
plot	logical to indicate whether the returned graph (i.e. the target graph plus the confidence information on nodes and edges) should be plotted. If it sets true, the plot will display the returned graph with the size of nodes indicative of the node confidence (the frequency that a node appears in the source graphs), and with the width of edges indicative of the edge confidence (the frequency that an edge appears in the source graphs)

Value

an object of class "igraph" or "graphNEL", which is a target graph but appended with the "nodeConfidence" attribute to the nodes and the "edgeConfidence" attribute to the edges

Note

None

See Also

[visNet](#)

Examples

```
# 1) generate a target graph according to the ER model
g <- erdos.renyi.game(100, 1/100)
target <- dNetInduce(g, V(g), knn=0)

# 2) generate a list source graphs according to the ER model
sources <- lapply(1:100, function(x) erdos.renyi.game(100*runif(1),
1/10))

# 3) append the confidence information from the source graphs into the target graph
g <- dNetConfidence(target=target, sources=sources)

# 4) visualise the confidence target graph
visNet(g, vertex.size=V(g)$nodeConfidence/10,
edge.width=E(g)$edgeConfidence)
```

dNetFind

*Function to find heuristically maximum scoring subgraph***Description**

dNetFind is supposed to find the maximum scoring subgraph from an input graph and scores imposed on its nodes. The input graph and the output subgraph are both of "igraph" or "graphNEL" object. The input scores imposed on the nodes in the input graph can be divided into two parts: the positive nodes and the negative nodes. The searching for maximum scoring subgraph is deduced to find the connected subgraph containing the positive nodes as many as possible, but the negative nodes as few as possible. To this end, a heuristic search is used (see Note below).

Usage

```
dNetFind(g, scores)
```

Arguments

g	an object of class "igraph" or "graphNEL"
scores	a vector of scores. For each element, it must have the name that could be mapped onto the input graph. Also, the names in input "scores" should contain all those in the input graph "g", but the reverse is not necessary

Value

a subgraph with a maximum score, an object of class "igraph" or "graphNEL"

Note

The search procedure is heuristic to find the subgraph with the maximum score:

- i) transform the input graph into a new graph by collapsing connected positive nodes into a meta-node. As such, meta-nodes are isolated to each other but are linked via negative nodes (single-nodes). Clearly, meta-nodes have positive scores, and negative scores for the single-nodes.

- ii) append the weight attribute to the edges in the transformed graph. There are two types of edges: 1) the single-single edge with two single-nodes as two ends, and 2) single-meta edge with a single-node as one end and a meta-node as the other end. The weight for a single-single edge is the absolute sum of the scores in its two-end single-nodes but normalised by their degrees. The weight for a single-meta edge is simply the absolute score in its single-node end normalised by the degree. As such, weights are all non-negative.
- iii) find minimum spanning tree (MST) in the weighted transformed graph using Prim's greedy algorithm. A spanning tree of the weighted graph is a subgraph that is tree and connects all the node together. The MST is a spanning tree with the sum of its edge weights minimised amongst all possible spanning trees.
- iv) find all shortest paths between any pair of meta-nodes in the MST. Within the weighted transformed graph in ii), a subgraph is induced containing nodes (only occuring in these shortest paths) and all edges between them.
- v) within the induced subgraph, identify single-nodes that are direct neighbors of meta-nodes. For each of these single-nodes, also make sure it has the absolute scores no more than the sum of scores in its neighboring meta-nodes. These single-nodes meeting both criteria are called "linkers".
- vi) still within the induced subgraph in v), find the linker graph that contains only linkers and edges between them. Similarly to iii), find MST of the linker graph, called 'linker MST'. Notably, this linker MST serves as the scaffold, which only contains linkers but has meta-nodes being directly attached to.
- vii) in linker MST plus its attached meta-nodes, find the optimal path that has the sum of scores of its nodes and attached meta-nodes maximised amongst all possible paths. Nodes along this optimal path plus their attached meta-nodes are called 'subgraph nodes'.
- viii) finally, from the input graph extract a subgraph (called 'subgraph') that only contains subgraph nodes and edges between them. This subgraph is the maximum scoring subgraph containing the positive nodes as many as possible, but the negative nodes as few as possible.

See Also

[dNetFind](#)

Examples

```
# 1) generate an vector consisting of random values from beta distribution
x <- rbeta(1000, shape1=0.5, shape2=1)

# 2) fit a p-value distribution under beta-uniform mixture model
fit <- dBUMfit(x, ntry=1, hist.bum=FALSE, contour.bum=FALSE)

# 3) calculate the scores according to the fitted BUM and fdr=0.01
# using "pdf" method
scores <- dBUMscore(fit, method="pdf", fdr=0.05, scatter.bum=FALSE)
names(scores) <- as.character(1:length(scores))

# 4) generate a random graph according to the ER model
g <- erdos.renyi.game(1000, 1/100)

# 5) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 6) find the subgraph with the maximum score
subgraph <- dNetFind(subg, scores)
```

dNetInduce	<i>Function to generate a subgraph induced by given vertices and their k nearest neighbors</i>
------------	--

Description

dNetInduce is supposed to produce a subgraph induced by given vertices and its k nearest neighbors. The input is a graph of "igraph" or "graphNEL" object, a list of the vertices of the graph, and a k value for finding k nearest neighbors for these vertices. The output is a subgraph induced by given vertices plus their k neighbours. The resultant subgraph inherits the class from the input one. The induced subgraph contains exactly the vertices of interest, and all the edges between them.

Usage

```
dNetInduce(g, nodes_query, knn = 0, remove.loops = F, largest.comp = T,
min.comp.size = 1)
```

Arguments

g	an object of class "igraph" or "graphNEL"
nodes_query	the vertices for which the calculation is performed
knn	an integer specifying how many k steps are used to find the nearest neighbours of the given vertices. By default, knn is set to zero; it means no neighbors will be considered. When knn is 1, the immediate neighbors of the given vertices will be also considered for inducing the subgraph. The same is true when knn is 2, etc
remove.loops	logical to indicate whether the loop edges are to be removed. By default, it sets to false
largest.comp	logical to indicate whether the largest component is only retained. By default, it sets to true for the largest component being left
min.comp.size	an integer specifying the minimum size of component that will be retained. This parameter only works when setting the false to keep the largest component. By default, it sets to 1 meaning all nodes will be retained

Value

- subg: an induced subgraph, an object of class "igraph" or "graphNEL"

Note

The given vertices plus their k nearest neighbors will be used to induce the subgraph.

See Also

[dNetInduce](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) select the first 10 vertices as the query nodes
nodes_query <- V(g)[1:10]

# 3) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, nodes_query, knn=0)

# 4) produce the induced subgraph based on the nodes in query and their immediate neighbours
subg <- dNetInduce(g, nodes_query, knn=1)
```

dNetPipeline

Function to setup the pipeline for finding maximum-scoring subgraph from an input graph and the significance imposed on its nodes

Description

dNetPipeline is supposed to finish ab initio maximum-scoring subgraph identification for the input graph with the node information on the significance (p-value or fdr). It returns an object of class "igraph" or "graphNEL".

Usage

```
dNetPipeline(g, pval, method = c("pdf", "cdf", "customised"),
significance.threshold = NULL, nsize = NULL, plot = F, verbose = T)
```

Arguments

g	an object of class "igraph" or "graphNEL"
pval	a vector containing input p-values (or fdr). For each element, it must have the name that could be mapped onto the input graph. Also, the names in input "pval" should contain all those in the input graph "g", but the reverse is not necessary
method	the method used for the transformation. It can be either "pdf" for the method based on the probability density function of the fitted model, or "cdf" for the method based on the cumulative distribution function of the fitted model
significance.threshold	the given significance threshold. By default, it is set to NULL, meaning there is no constraint. If given, those p-values below this are considered significant and thus scored positively. Instead, those p-values above this given significance threshold are considered insignificant and thus scored negatively
nsize	the desired number of nodes constrained to the resulting subgraph. It is not null, a wide range of significance thresholds will be scanned to find the optimal significance threshold leading to the desired number of nodes in the resulting subgraph. Notably, the given significance threshold will be overwritten by this option.
plot	logical to indicate whether the histogram plot, contour plot and scatter plot should be drawn. By default, it sets to false for no plotting
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

a subgraph with a maximum score, an object of class "igraph" or "graphNEL"

Note

The pipeline sequentially consists of:

- ia) if the method is either "pdf" or "cdf", `dBUMfit` used to fit the p-value distribution under beta-uniform mixture model, and `dBUMscore` used to calculate the scores according to the fitted BUM and the significance threshold.
- ib) if the method is either "customised", then the user input list of `fdr` (or p-values) and the significance threshold will be directly used for score transformation by `dFDRscore`.
- ii) if there is the desired number of nodes constrained to the resulting subgraph, a wide range of significance thresholds (including rough stage with large intervals, and finetune stage with smaller intervals) will be scanned to find the significance threshold to meet the desired number of nodes.
- iii) `dNetFind` used to find maximum-scoring subgraph from the input graph and scores imposed on its nodes.

See Also

`dBUMfit`, `dBUMscore`, `dFDRscore`, `dNetFind`

Examples

```
# 1) generate an vector consisting of random values from beta distribution
x <- rbeta(1000, shape1=0.5, shape2=1)
names(x) <- as.character(1:length(x))

# 2) generate a random graph according to the ER model
g <- erdos.renyi.game(1000, 1/100)

# 3) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 4) find maximum-scoring subgraph based on the given significance threshold
# 4a) assume the input is a list of p-values (controlling fdr=0.1)
subgraph <- dNetPipeline(g=subg, pval=x, significance.threshold=0.1)
# 4b) assume the input is a list of customised significance (eg FDR directly)
subgraph <- dNetPipeline(g=subg, pval=x, method="customised",
significance.threshold=0.1)

# 5) find maximum-scoring subgraph with the desired node number nsize=20
subgraph <- dNetPipeline(g=subg, pval=x, nsize=20)
```

dNetReorder

Function to reorder the multiple graph colorings within a sheet-shape rectangle grid

Description

dNetReorder is reorder the multiple graph colorings within a sheet-shape rectangle grid

Usage

```
dNetReorder(g, data, feature = c("node", "edge"), node.normalise =
c("none",
"degree"), xdim = NULL, ydim = NULL, amplifier = NULL,
metric = c("none", "pearson", "spearman", "kendall", "euclidean",
"manhattan", "cos", "mi"), init = c("linear", "uniform", "sample"),
algorithm = c("sequential", "batch"), alphaType = c("invert", "linear",
"power"), neighKernel = c("gaussian", "bubble", "cutgaussian", "ep",
"gamma"))
```

Arguments

<code>g</code>	an object of class "igraph" or "graphNEL"
<code>data</code>	an input data matrix used to color-code vertices/nodes. One column corresponds to one graph node coloring. The input matrix must have row names, and these names should include all node names of input graph, i.e. $V(g)$name, since there is a mapping operation. After mapping, the length of the pattern vector should be the same as the number of nodes of input graph. The way of how to color-code is to map values in the pattern onto the whole colormap (see the next arguments: colormap, ncolors, xlim and colorbar)$
<code>feature</code>	the type of the features used. It can be one of either 'edge' for the edge feature or 'node' for the node feature. See 'Note' for explanations.
<code>node.normalise</code>	the normalisation of the nodes. It can be one of either 'none' for no normalisation or 'degree' for a node being penalised by its degree.
<code>xdim</code>	an integer specifying x-dimension of the grid
<code>ydim</code>	an integer specifying y-dimension of the grid
<code>amplifier</code>	an integer specifying the amplifier (3 by default) of the number of component planes. The product of the component number and the amplifier constitutes the number of rectangles in the sheet grid
<code>metric</code>	distance metric used to define the similarity between component planes. It can be "none", which means directly using column-wise vectors of codebook/data matrix. Otherwise, first calculate the covariance matrix from the codebook/data matrix. The distance metric used for calculating the covariance matrix between component planes can be: "pearson" for pearson correlation, "spearman" for spearman rank correlation, "kendall" for kendall tau rank correlation, "euclidean" for euclidean distance, "manhattan" for cityblock distance, "cos" for cosine similarity, "mi" for mutual information.
<code>init</code>	an initialisation method. It can be one of "uniform", "sample" and "linear" initialisation methods
<code>algorithm</code>	the training algorithm. Currently, only "sequential" algorithm has been implemented
<code>alphaType</code>	the alpha type. It can be one of "invert", "linear" and "power" alpha types
<code>neighKernel</code>	the training neighbor kernel. It can be one of "gaussian", "bubble", "cutgaussian", "ep" and "gamma" kernels

Value

an object of class "sReorder", a list with following components:

- nHex: the total number of rectangles in the grid

- `xdim`: x-dimension of the grid
- `ydim`: y-dimension of the grid
- `uOrder`: the unique order/placement for each component plane that is reordered to the "sheet"-shape grid with rectangular lattice
- `coord`: a matrix of `nHex` x 2, with each row corresponding to the coordinates of each "uOrder" rectangle in the 2D map grid
- `call`: the call that produced this result

Note

According to which features are used and whether nodes should be penalised by degrees, the feature data are constructed differently from the input data and input graph:

- When the node features are used, the feature data is the input data (or penalised data) with the same dimension.
- When the edge features are used, each entry (i.e. given an edge and a sample) in the feature data is the absolute difference between its two-end nodes (or after being penalised).
- After that, the constructed feature are subject to sample correlation analysis by `supraHex`. That is, a map grid (with sheet shape consisting of a rectangular lattice) is used to train either column-wise vectors of the feature data matrix or the covariance matrix thereof.
- As a result, similar samples are placed closer to each other within this map grid. More precisely, to ensure the unique placement, each sample mapped to the "sheet"-shape grid with rectangular lattice is determined iteratively in an order from the best matched to the next compromised one. If multiple samples are hit in the same rectangular lattice, the worse one is always sacrificed by moving to the next best one till all samples are placed somewhere exclusively on their own.

The size of "sheet"-shape rectangle grid depends on the input arguments:

- How the input parameters are used to determine `nHex` is taken priority in the following order: "`xdim & ydim`" > "`nHex`" > "`data`".
- If both of `xdim` and `ydim` are given, $nHex = xdim * ydim$.
- If only `data` is input, $nHex = 5 * sqrt(dlen)$, where `dlen` is the number of rows of the input data.
- After `nHex` is determined, `xy`-dimensions of rectangle grid are then determined according to the square root of the two biggest eigenvalues of the input data.

See Also

[visNetReorder](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 3) reorder the module with vertices being color-coded by input data
nnodes <- vcount(subg)
nsamples <- 10
```

```
data <- matrix(runif(nnodes*nsamples), nrow=nnodes, ncol=nsamples)
rownames(data) <- V(subg)$name
sReorder <- dNetReorder(g=subg, data, feature="node",
node.normalise="none")
```

dPvalAggregate

Function to aggregate p values

Description

dPvalAggregate is supposed to aggregate a input matrix p-values into a vector of aggregated p-values. The aggregate operation is applied to each row of input matrix, each resulting in an aggregated p-value. The method implemented can be based on the order statistics of p-values or according to Fisher's method or Z-transform method.

Usage

```
dPvalAggregate(pmatrix, method = c("orderStatistic", "fishers",
"Ztransform",
"logistic"), order = ncol(pmatrix), weight = rep(1, ncol(pmatrix)))
```

Arguments

pmatrix	a data frame or matrix of p-values
method	the method used. It can be either "orderStatistic" for the method based on the order statistics of p-values, or "fishers" for Fisher's method (summation of logs), or "Ztransform" for Z-transform test (summation of z values, Stouffer's method) and the weighted Z-test, or "logistic" for summation of logits
order	an integer specifying the order used for the aggregation according to the order statistics of p-values
weight	a vector specifying the weights used for the aggregation according to Z-transform method

Value

- ap: a vector with the length nrow(pmatrix), containing aggregated p-values

Note

For each row of input matrix with the c columns, there are c p-values that are uniformly independently distributed over $[0,1]$ under the null hypothesis (uniform distribution). According to the order statistics, they follow the Beta distribution with the parameters $a = order$ and $b = c - order + 1$. According to the Fisher's method, after transformation by $-2 * \sum^c \log(pvalue)$, they follow Chi-Squared distribution. According to the Z-transform method, first converts the one-tailed P-values into standard normal deviates Z , then combines Z via $\frac{\sum^c (w*Z)}{\sum^c (w^2)}$, where w is the weight (usually square root of the sample size if the weighted Z-test; 1 if Z-transform test), and finally the combined Z follows the standard normal distribution to test the cumulative/aggregated evidence on the common null hypothesis. The logistic method is defined as $\sum^c \log(\frac{pvalue}{1-pvalue}) * 1/C$, where $C = \sqrt{((k\pi^2(5k + 2))/(3(5k + 4)))}$, following Student's t distribution. Generally speaking, Fisher's method places greater emphasis on small p-values, while the Z-transform method on equal

footings, the logistic method provides a compromise between these two. In other words, the Z-transform method does well in problems where evidence against the combined null is spread more than a small fraction of the individual tests, or when the total evidence is weak; Fisher's method does best in problems where the evidence is concentrated in a relatively small fraction of the individual tests or when the evidence is at least moderately strong.

See Also

[dPvalAggregate](#)

Examples

```
# 1) generate an iid uniformly-distributed random matrix of 1000x3
pmatrix <- cbind(runif(1000), runif(1000), runif(1000))

# 2) aggregate according to the order statistics
ap <- dPvalAggregate(pmatrix, method="orderStatistic")

# 3) aggregate according to the Fisher's method
ap <- dPvalAggregate(pmatrix, method="fishers")

# 4) aggregate according to the Z-transform method
ap <- dPvalAggregate(pmatrix, method="Ztransform")

# 5) aggregate according to the logistic method
ap <- dPvalAggregate(pmatrix, method="logistic")
```

dRDataLoader

Function to load dnet built-in RData

Description

dRDataLoader is supposed to load the package built-in RData.

Usage

```
dRDataLoader(RData = c(NA, "TCGA_mutations", "ig.DO", "ig.GOBP",
"ig.GOCC",
"ig.GOMF", "ig.HPCM", "ig.HPMA", "ig.HPMI", "ig.HPPA", "ig.MP",
"org.At.eg",
"org.At.egGOBP", "org.At.egGOCC", "org.At.egGOMF", "org.At.egPS",
"org.At.egSF", "org.At.string", "org.Ce.eg", "org.Ce.egGOBP",
"org.Ce.egGOCC",
"org.Ce.egGOMF", "org.Ce.egPS", "org.Ce.egSF", "org.Ce.string",
"org.Da.eg",
"org.Da.egGOBP", "org.Da.egGOCC", "org.Da.egGOMF", "org.Da.egPS",
"org.Da.egSF", "org.Da.string", "org.Dm.eg", "org.Dm.egGOBP",
"org.Dm.egGOCC",
"org.Dm.egGOMF", "org.Dm.egPS", "org.Dm.egSF", "org.Dm.string",
"org.Gg.eg", "org.Gg.egGOBP", "org.Gg.egGOCC", "org.Gg.egGOMF",
"org.Gg.egPS",
"org.Gg.egSF", "org.Gg.string", "org.Hs.eg", "org.Hs.egDGIdb",
"org.Hs.egDO",
```

```

"org.Hs.egGOBP", "org.Hs.egGOCC", "org.Hs.egGOMF", "org.Hs.egHPCM",
"org.Hs.egHPMA", "org.Hs.egHPMI", "org.Hs.egHPPA", "org.Hs.egMP",
"org.Hs.egMsigdbC1", "org.Hs.egMsigdbC2BIOCARTA",
"org.Hs.egMsigdbC2CGP",
"org.Hs.egMsigdbC2CP", "org.Hs.egMsigdbC2KEGG",
"org.Hs.egMsigdbC2REACTOME",
"org.Hs.egMsigdbC3MIR", "org.Hs.egMsigdbC3TFT", "org.Hs.egMsigdbC4CGN",
"org.Hs.egMsigdbC4CM", "org.Hs.egMsigdbC5BP", "org.Hs.egMsigdbC5CC",
"org.Hs.egMsigdbC5MF", "org.Hs.egMsigdbC6", "org.Hs.egMsigdbC7",
"org.Hs.egMsigdbH", "org.Hs.egPS", "org.Hs.egSF", "org.Hs.string",
"org.Mm.eg", "org.Mm.egDO", "org.Mm.egGOBP", "org.Mm.egGOCC",
"org.Mm.egGOMF",
"org.Mm.egHPCM", "org.Mm.egHPMA", "org.Mm.egHPMI", "org.Mm.egHPPA",
"org.Mm.egMP", "org.Mm.egPS", "org.Mm.egSF", "org.Mm.string",
"org.Rn.eg",
"org.Rn.egGOBP", "org.Rn.egGOCC", "org.Rn.egGOMF", "org.Rn.egPS",
"org.Rn.egSF", "CLL", "org.Rn.string"), genome = c(NA, "Hs", "Mm",
"Rn",
"Gg", "Ce", "Dm", "Da", "At"), ontology = c(NA, "GOBP", "GOMF", "GOCC",
"PS", "PS2", "SF", "DO", "HPPA", "HPMI", "HPCM", "HPMA", "MP",
"MsigdbH",
"MsigdbC1", "MsigdbC2CGP", "MsigdbC2CP", "MsigdbC2KEGG",
"MsigdbC2REACTOME",
"MsigdbC2BIOCARTA", "MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN",
"MsigdbC4CM",
"MsigdbC5BP", "MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7",
"DGIdb"),
verbose = T,
RData.location =
"https://github.com/hfang-bristol/RDataCentre/blob/master/dnet/1.0.7")

```

Arguments

RData	<p>which built-in RData to load. It can be one of "TCGA_mutations", "ig.DO", "ig.GOBP", "ig.GOCC", "ig.GOMF", "ig.HPCM", "ig.HPMA", "ig.HPMI", "ig.HPPA", "ig.MP", "org.At.eg", "org.At.egGOBP", "org.At.egGOCC", "org.At.egGOMF", "org.At.egPS", "org.At.egSF", "org.At.string", "org.Ce.eg", "org.Ce.egGOBP", "org.Ce.egGOCC", "org.Ce.egGOMF", "org.Ce.egPS", "org.Ce.egSF", "org.Ce.string", "org.Da.eg", "org.Da.egGOBP", "org.Da.egGOCC", "org.Da.egGOMF", "org.Da.egPS", "org.Da.egSF", "org.Da.string", "org.Dm.eg", "org.Dm.egGOBP", "org.Dm.egGOCC", "org.Dm.egGOMF", "org.Dm.egPS", "org.Dm.egSF", "org.Dm.string", "org.Gg.eg", "org.Gg.egGOBP", "org.Gg.egGOCC", "org.Gg.egGOMF", "org.Gg.egPS", "org.Gg.egSF", "org.Gg.string", "org.Hs.eg", "org.Hs.egDGIdb", "org.Hs.egDO", "org.Hs.egGOBP", "org.Hs.egGOCC", "org.Hs.egGOMF", "org.Hs.egHPCM", "org.Hs.egHPMA", "org.Hs.egHPMI", "org.Hs.egHPPA", "org.Hs.egMP", "org.Hs.egMsigdbC1", "org.Hs.egMsigdbC2BIOCARTA", "org.Hs.egMsigdbC2CGP", "org.Hs.egMsigdbC2CP", "org.Hs.egMsigdbC2KEGG", "org.Hs.egMsigdbC2REACTOME", "org.Hs.egMsigdbC3MIR", "org.Hs.egMsigdbC3TFT", "org.Hs.egMsigdbC4CGN", "org.Hs.egMsigdbC4CM", "org.Hs.egMsigdbC5BP", "org.Hs.egMsigdbC5CC", "org.Hs.egMsigdbC5MF", "org.Hs.egMsigdbC6", "org.Hs.egMsigdbC7", "org.Hs.egMsigdbH", "org.Hs.egPS", "org.Hs.egSF", "org.Hs.string", "org.Mm.eg", "org.Mm.egDO", "org.Mm.egGOBP", "org.Mm.egGOCC", "org.Mm.egGOMF", "org.Mm.egHPCM", "org.Mm.egHPMA", "org.Mm.egHPMI", "org.Mm.egHPPA", "org.Mm.egMP", "org.Mm.egPS", "org.Mm.egSF", "org.Mm.string", "org.Rn.eg",</p>
-------	---

	"org.Rn.egGOBP", "org.Rn.egGOCC", "org.Rn.egGOMF", "org.Rn.egPS", "org.Rn.egSF", "CLL", "org.Rn.string". On the meanings, please refer to the Documentations at http://supfam.org/dnet/docs.html
genome	the genome identity. It can be one of "Hs" for human, "Mm" for mouse, "Rn" for rat, "Gg" for chicken, "Ce" for c.elegans, "Dm" for fruitfly, "Da" for zebrafish, and "At" for arabidopsis
ontology	the ontology supported currently. It can be "GOBP" for Gene Ontology Biological Process, "GOMF" for Gene Ontology Molecular Function, "GOCC" for Gene Ontology Cellular Component, "PS" for phylostratific age information, "PS2" for the collapsed PS version (inferred ancestors being collapsed into one with the known taxonomy information), "SF" for domain superfamily assignments, "DO" for Disease Ontology, "HPPA" for Human Phenotype Phenotypic Abnormality, "HPMI" for Human Phenotype Mode of Inheritance, "HPCM" for Human Phenotype Clinical Modifier, "HPMA" for Human Phenotype Mortality Aging, "MP" for Mammalian Phenotype, and Drug-Gene Interaction database (DGIdb) and the molecular signatures database (Msigdb) only in human (including "MsigdbH", "MsigdbC1", "MsigdbC2CGP", "MsigdbC2CP", "MsigdbC2KEGG", "MsigdbC2REACTOME", "MsigdbC2BIOCARTA", "MsigdbC3TFT", "MsigdbC3MIR", "MsigdbC4CGN", "MsigdbC4CM", "MsigdbC5BP", "MsigdbC5MF", "MsigdbC5CC", "MsigdbC6", "MsigdbC7"). Note: These four ("GOBP", "GOMF", "GOCC" and "PS") are available for all genomes/species; for "Hs" and "Mm", these six ("DO", "HPPA", "HPMI", "HPCM", "HPMA" and "MP") are also supported; all "Msigdb" are only supported in "Hs". For details on the eligibility for pairs of input genome and ontology, please refer to the online Documentations at http://supfam.org/dnet/docs.html
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to TRUE for display
RData.location	the characters to tell the location of built-in RData files. By default, it remotely locates at https://github.com/hfang-bristol/RDataCentre/blob/master/dnet and http://dnet.r-forge.r-project.org/RData . Be aware of several versions and the latest one is matched to the current package version. For the user equipped with fast internet connection, this option can be just left as default. But it is always advisable to download these files locally. Especially when the user needs to run this function many times, there is no need to ask the function to remotely download every time (also it will unnecessarily increase the runtime). For examples, these files (as a whole or part of them) can be first downloaded into your current working directory, and then set this option as: <code>RData.location = "."</code> . Surely, the location can be anywhere as long as the user provides the correct path pointing to (otherwise, the script will have to remotely download each time). Here is the UNIX command for downloading all RData files (preserving the directory structure): <code>wget -r -l2 -A "*.RData" -np -nH --cut-dirs = 0 http://dnet.r-forge.r-project.org/RData</code>

Value

any use-specified variable that is given on the right side of the assignment sign '<-', which contains the loaded RData.

Note

If there are no use-specified variable that is given on the right side of the assignment sign '<-', then no RData will be loaded onto the working environment.

See Also[dRDataLoader](#)**Examples**

```

org.Hs.egSF <- dRDataLoader(RData='org.Hs.egSF')
org.Hs.eg <- dRDataLoader(RData='org.Hs.eg')
org.Hs.egDGIdb <- dRDataLoader(RData='org.Hs.egDGIdb')
org.Hs.egMsigdbC2KEGG <- dRDataLoader(RData='org.Hs.egMsigdbC2KEGG')
org.Hs.egHPPA <- dRDataLoader(genome='Hs', ontology='HPPA')
ig.MP <- dRDataLoader(RData='ig.MP')

```

dRWR

Function to implement Random Walk with Restart (RWR) on the input graph

Description

dRWR is supposed to implement Random Walk with Restart (RWR) on the input graph. If the seeds (i.e. a set of starting nodes) are given, it intends to calculate the affinity score of all nodes in the graph to the seeds. If the seeds are not given, it will pre-compute affinity matrix for nodes in the input graph with respect to each starting node (as a seed) by looping over every node in the graph. Parallel computing is also supported for Linux or Mac operating systems.

Usage

```

dRWR(g, normalise = c("laplacian", "row", "column", "none"),
setSeeds = NULL, restart = 0.75, normalise.affinity.matrix = c("none",
"quantile"), parallel = TRUE, multicores = NULL, verbose = T)

```

Arguments

<code>g</code>	an object of class "igraph" or "graphNEL"
<code>normalise</code>	the way to normalise the adjacency matrix of the input graph. It can be 'laplacian' for laplacian normalisation, 'row' for row-wise normalisation, 'column' for column-wise normalisation, or 'none'
<code>setSeeds</code>	an input matrix used to define sets of starting seeds. One column corresponds to one set of seeds that a walker starts with. The input matrix must have row names, coming from node names of input graph, i.e. $V(g)$name$, since there is a mapping operation. The non-zero entries mean that the corresponding rows (i.e. the gene/row names) are used as the seeds, and non-zero values can be viewed as how to weight the relative importance of seeds. By default, this option sets to "NULL", suggesting each node in the graph will be used as a set of the seed to pre-compute affinity matrix for the input graph. This default does not scale for large input graphs since it will loop over every node in the graph; however, the pre-computed affinity matrix can be extensively reused for obtaining affinity scores between any combinations of nodes/seeds, allows for some flexibility in the downstream use, in particular when sampling a large number of random node combinations for statistical testing

restart	the restart probability used for RWR. The restart probability takes the value from 0 to 1, controlling the range from the starting nodes/seeds that the walker will explore. The higher the value, the more likely the walker is to visit the nodes centered on the starting nodes. At the extreme when the restart probability is zero, the walker moves freely to the neighbors at each step without restarting from seeds, i.e., following a random walk (RW)
normalise.affinity.matrix	the way to normalise the output affinity matrix. It can be 'none' for no normalisation, 'quantile' for quantile normalisation to ensure that columns (if multiple) of the output affinity matrix have the same quantiles
parallel	logical to indicate whether parallel computation with multicores is used. By default, it sets to true, but not necessarily does so. It will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: <code>source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach", "doParallel"))</code> . If not yet installed, this option will be disabled
multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer. This option only works when parallel computation is enabled
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

It returns a sparse matrix, called 'PTmatrix':

- When the seeds are NOT given: a pre-computed affinity matrix with the dimension of $n \times n$, where n is the number of nodes in the input graph. Columns stand for starting nodes walking from, and rows for ending nodes walking to. Therefore, a column for a starting node represents a steady-state affinity vector that the starting node will visit all the ending nodes in the graph
- When the seeds are given: an affinity matrix with the dimension of $n \times nset$, where n is the number of nodes in the input graph, and $nset$ for the number of the sets of seeds (i.e. the number of columns in `setSeeds`). Each column stands for the steady probability vector, storing the affinity score of all nodes in the graph to the starting nodes/seeds. This steady probability vector can be viewed as the "influential impact" over the graph imposed by the starting nodes/seeds.

Note

The input graph will treat as an unweighted graph if there is no 'weight' edge attribute associated with

See Also

[dRWRcontact](#), [dRWRpipeline](#), [dCheckParallel](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)
```

```
V(subg)$name <- 1:vcount(subg)

# 3) obtain the pre-computed affinity matrix
PTmatrix <- dRWR(g=subg, normalise="laplacian", restart=0.75,
parallel=FALSE)
# visualise affinity matrix
visHeatmapAdv(PTmatrix, Rowv=FALSE, Colv=FALSE, colormap="wyr",
KeyValName="Affinity")

# 4) obtain affinity matrix given sets of seeds
# define sets of seeds
# each seed with equal weight (i.e. all non-zero entries are '1')
aSeeds <- c(1,0,1,0,1)
bSeeds <- c(0,0,1,0,1)
setSeeds <- data.frame(aSeeds,bSeeds)
rownames(setSeeds) <- 1:5
# calculate affinity matrix
PTmatrix <- dRWR(g=subg, normalise="laplacian", setSeeds=setSeeds,
restart=0.75, parallel=FALSE)
PTmatrix
```

dRWRcontact

Function to estimate RWR-based contact strength between samples from an input gene-sample data matrix, an input graph and its pre-computed affinity matrix

Description

dRWRcontact is supposed to estimate sample relationships (ie. contact strength between samples) from an input gene-sample matrix, an input graph and its affinity matrix pre-computed according to random walk restart (RWR) of the input graph. It includes: 1) RWR-smoothed columns of input gene-sample matrix based on the pre-computed affinity matrix; 2) calculation of contact strength (inner products of RWR-smooth columns of input gene-sample matrix); 3) estimation of the contact significance by a randomisation procedure. Parallel computing is also supported for Linux or Mac operating systems.

Usage

```
dRWRcontact(data, g, Amatrix, permutation = c("random", "degree"),
num.permutation = 10, p.adjust.method = c("BH", "BY", "bonferroni",
"holm", "hochberg", "hommel"), adjp.cutoff = 0.05, parallel = TRUE,
multicores = NULL, verbose = T)
```

Arguments

data	an input gene-sample data matrix used for seeds. Each value in input gene-sample matrix does not necessarily have to be binary (non-zeros will be used as a weight, but should be non-negative for easy interpretation).
g	an object of class "igraph" or "graphNEL"
Amatrix	an affinity matrix pre-computed from the input graph. Notes: columns for starting nodes walking from, and rows for ending nodes walking to

permutation	how to do permutation. It can be 'degree' for degree-preserving permutation, 'random' for permutation purely in random
num.permutation	the number of permutations used to for generating the distribution of contact strength under randomisation
p.adjust.method	the method used to adjust p-values. It can be one of "BH", "BY", "bonferroni", "holm", "hochberg" and "hommel". The first two methods "BH" (widely used) and "BY" control the false discovery rate (FDR: the expected proportion of false discoveries amongst the rejected hypotheses); the last four methods "bonferroni", "holm", "hochberg" and "hommel" are designed to give strong control of the family-wise error rate (FWER). Notes: FDR is a less stringent condition than FWER
adjp.cutoff	the cutoff of adjusted pvalue to construct the contact graph
parallel	logical to indicate whether parallel computation with multicores is used. By default, it sets to true, but not necessarily does so. It will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: <code>source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach","doParallel"))</code> . If not yet installed, this option will be disabled
multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer. This option only works when parallel computation is enabled
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

an object of class "dContact", a list with following components:

- ratio: a symmetric matrix storing ratio (the observed against the expected) between pairwise samples
- zscore: a symmetric matrix storing zscore between pairwise samples
- pval: a symmetric matrix storing pvalue between pairwise samples
- adjpval: a symmetric matrix storing adjusted pvalue between pairwise samples
- cgraph: the constructed contact graph (as a 'igraph' object) under the cutoff of adjusted value
- call: the call that produced this result

Note

none

See Also

[dRWR](#), [dCheckParallel](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
```

```

subg <- dNetInduce(g, V(g), knn=0)
V(subg)$name <- 1:vcount(subg)

# 3) pre-compute affinity matrix from the input graph
Amatrix <- dRWR(g=subg, parallel=FALSE)

# 4) estimate RWR-based sample relationships
# define sets of seeds as data
# each seed with equal weight (i.e. all non-zero entries are '1')
aSeeds <- c(1,0,1,0,1)
bSeeds <- c(0,0,1,0,1)
data <- data.frame(aSeeds,bSeeds)
rownames(data) <- 1:5
# calculate their two contacts
dContact <- dRWRcontact(data=data, g=subg, Amatrix=Amatrix,
parallel=FALSE)
dContact

```

dRWRpipeline	<i>Function to setup a pipeline to estimate RWR-based contact strength between samples from an input gene-sample data matrix and an input graph</i>
--------------	---

Description

dRWRpipeline is supposed to estimate sample relationships (ie. contact strength between samples) from an input gene-sample matrix and an input graph. The pipeline includes: 1) random walk restart (RWR) of the input graph using the input matrix as seeds; 2) calculation of contact strength (inner products of RWR-smoothed columns of input matrix); 3) estimation of the contact significance by a randomisation procedure. It supports two methods how to use RWR: 'direct' for directly applying RWR in the given seeds; 'indirectly' for first pre-computing affinity matrix of the input graph, and then deriving the affinity score. Parallel computing is also supported for Linux or Mac operating systems.

Usage

```

dRWRpipeline(data, g, method = c("direct", "indirect"),
normalise = c("laplacian", "row", "column", "none"), restart = 0.75,
normalise.affinity.matrix = c("none", "quantile"),
permutation = c("random", "degree"), num.permutation = 10,
p.adjust.method = c("BH", "BY", "bonferroni", "holm", "hochberg",
"hommel"),
adjp.cutoff = 0.05, parallel = TRUE, multicores = NULL, verbose = T)

```

Arguments

data	an input gene-sample data matrix used for seeds. Each value in input gene-sample matrix does not necessarily have to be binary (non-zeros will be used as a weight, but should be non-negative for easy interpretation).
g	an object of class "igraph" or "graphNEL"
method	the method used to calculate RWR. It can be 'direct' for directly applying RWR, 'indirect' for indirectly applying RWR (first pre-compute affinity matrix and then derive the affinity score)

normalise	the way to normalise the adjacency matrix of the input graph. It can be 'laplacian' for laplacian normalisation, 'row' for row-wise normalisation, 'column' for column-wise normalisation, or 'none'
restart	the restart probability used for RWR. The restart probability takes the value from 0 to 1, controlling the range from the starting nodes/seeds that the walker will explore. The higher the value, the more likely the walker is to visit the nodes centered on the starting nodes. At the extreme when the restart probability is zero, the walker moves freely to the neighbors at each step without restarting from seeds, i.e., following a random walk (RW)
normalise.affinity.matrix	the way to normalise the output affinity matrix. It can be 'none' for no normalisation, 'quantile' for quantile normalisation to ensure that columns (if multiple) of the output affinity matrix have the same quantiles
permutation	how to do permutation. It can be 'degree' for degree-preserving permutation, 'random' for permutation in random
num.permutation	the number of permutations used to for generating the distribution of contact strength under randomisation
p.adjust.method	the method used to adjust p-values. It can be one of "BH", "BY", "bonferroni", "holm", "hochberg" and "hommel". The first two methods "BH" (widely used) and "BY" control the false discovery rate (FDR: the expected proportion of false discoveries amongst the rejected hypotheses); the last four methods "bonferroni", "holm", "hochberg" and "hommel" are designed to give strong control of the family-wise error rate (FWER). Notes: FDR is a less stringent condition than FWER
adjp.cutoff	the cutoff of adjusted pvalue to construct the contact graph
parallel	logical to indicate whether parallel computation with multicores is used. By default, it sets to true, but not necessarily does so. It will depend on whether these two packages "foreach" and "doParallel" have been installed. It can be installed via: <code>source("http://bioconductor.org/biocLite.R"); biocLite(c("foreach", "doParallel"))</code> . If not yet installed, this option will be disabled
multicores	an integer to specify how many cores will be registered as the multicore parallel backend to the 'foreach' package. If NULL, it will use a half of cores available in a user's computer. This option only works when parallel computation is enabled
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

an object of class "dContact", a list with following components:

- ratio: a symmetric matrix storing ratio (the observed against the expected) between pairwise samples
- zscore: a symmetric matrix storing zscore between pairwise samples
- pval: a symmetric matrix storing pvalue between pairwise samples
- adjpval: a symmetric matrix storing adjusted pvalue between pairwise samples
- cgraph: the constructed contact graph (as a 'igraph' object) under the cutoff of adjusted value
- Amatrix: a pre-computed affinity matrix when using 'indirect' method; NULL otherwise
- call: the call that produced this result

Note

The choice of which method to use RWR depends on the number of seed sets and the number of permutations for statistical test. If the total product of both numbers are huge, it is better to use 'indirect' method (for a single run). However, if the user wants to re-use pre-computed affinity matrix (ie. re-use the input graph a lot), then it is highly recommended to sequentially use [dRWR](#) and [dRWRcontact](#) instead.

See Also

[dRWR](#), [dRWRcontact](#), [dCheckParallel](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)
V(subg)$name <- 1:vcount(subg)

# 3) estimate RWR dating based sample relationships
# define sets of seeds as data
# each seed with equal weight (i.e. all non-zero entries are '1')
aSeeds <- c(1,0,1,0,1)
bSeeds <- c(0,0,1,0,1)
data <- data.frame(aSeeds,bSeeds)
rownames(data) <- 1:5
# calculate their two contact graph
dContact <- dRWRpipeline(data=data, g=subg, parallel=FALSE)
dContact
```

dSVDsignif

Function to obtain SVD-based gene significance from the input gene-sample matrix

Description

dSVDsignif is supposed to obtain gene significance from the given gene-sample matrix according to singular value decomposition (SVD)-based method. The method includes: 1) singular value decomposition of the input matrix; 2) determination of the eigens in consideration (if not given); 3) construction of the gene-specific project vector based on the considered eigens; 4) calculation of the distance statistic from the projection vector to zero point vector; and 5) based on distance statistic to obtain the gene significance.

Usage

```
dSVDsignif(data, num.eigen = NULL, pval.eigen = 0.01, signif = c("fdr",
"pval"), orient.permutation = c("row", "column", "both"),
num.permutation = 100, fdr.procedure = c("stepup", "stepdown"),
verbose = T)
```

Arguments

data	an input gene-sample data matrix used for singular value decomposition
num.eigen	an integer specifying the number of eigens in consideration. If NULL, this number will be automatically decided on based on the observed relative eigenexpression against randomised relative eigenexpression calculated from a list (here 100) of permuted input matrix
pval.eigen	p-value used to call those eigens as dominant. This parameter is used only when parameter 'num.eigen' is NULL. Here, p-value is calculated to assess how likely the observed relative eigenexpression are more than the maximum relative eigenexpression calculated from permuted matrix
signif	the significance to return. It can be either "pval" for using the p-value as the gene significance, or "fdr" for using the fdr as the gene significance
orient.permutation	the orientation of matrix being permuted. It can be either "row" to permute values within each row, or "column" to permute values within each column, or "both" to permute values both within rows and columns. Notably, when using the p-value as the gene significance, it is always to permute values within each row.
num.permutation	an integer specifying how many permutations are used
fdr.procedure	the procedure to adjust the fdr. To ensure that the high distance statistic the more significance, the fdr should be adjusted either using "stepup" for step-up procedure (from the most significant to the least significant) or using "stepdown" for step-down procedure (from the least significant to the most significant)
verbose	logical to indicate whether the messages will be displayed in the screen. By default, it sets to true for display

Value

a vector storing gene significance

Note

none

See Also

[dFDRscore](#)

Examples

```
# 1) generate data with an iid matrix of 1000 x 9
data <- cbind(matrix(rnorm(1000*3,mean=0,sd=1), nrow=1000, ncol=3),
matrix(rnorm(1000*3,mean=0.5,sd=1), nrow=1000, ncol=3),
matrix(rnorm(1000*3,mean=-0.5,sd=1), nrow=1000, ncol=3))

# 2) calculate the significance according to SVD
# using "fdr" significance
fdr <- dSVDsignif(data, signif="fdr", num.permutation=10)
# using "pval" significance
pval <- dSVDsignif(data, signif="pval", num.permutation=10)
```

GWAS2EF	<i>Annotations of GWAS Catalog SNPs by Experimental Factor Ontology (EF)</i>
---------	--

Description

This dataset involves GWAS Catalog SNPs and their traits mapped to Experimental Factor Ontology. This data is prepared based on <https://www.ebi.ac.uk/gwas/api/search/downloads/alternative>.

Usage

```
GWAS2EF <- dRDataLoader(RData='GWAS2EF')
```

Value

a sparse Matrix of class "dgCMatrix", with the columns for Experimental Factor Ontology terms and rows for GWAS SNPs.

References

Malone et al. (2010) Modeling sample variables with an Experimental Factor Ontology. *Bioinformatics*, 26(8):1112-8.
Welter et al. (2014) The NHGRI GWAS Catalog, a curated resource of SNP-trait associations. *Nucleic Acids Res*, 42(Database issue):D1001-6.

Examples

```
GWAS2EF <- dRDataLoader(RData='GWAS2EF')  
GWAS2EF[1:10, 1:33]
```

GWAS_LD	<i>Linkage Disequilibrium (LD) of GWAS Catalog SNPs according to the 1000 Genomics Project data (phase 3)</i>
---------	---

Description

This dataset involves LD of GWAS Catalog SNPs calculated by PLINK based on the 1000 Genomics Project data (phase 3).

Usage

```
GWAS_LD <- dRDataLoader(RData='GWAS_LD')
```


Value

a list of sparse Matrix of class "dgCMatrix". Each list represents one of 26 populations and 5 super populations, containing sparse matrix of GWAS Catalog SNPs (rows) and LD SNPs (columns). Non-zero values indicate r^2 (only those no less than 0.8). The population include 5 super populations ("AFR", "AMR", "EAS", "EUR", "SAS") and 26 populations ("ACB", "ASW", "BEB", "CDX", "CEU", "CHB", "CHS", "CLM", "ESN", "FIN", "GBR", "GIH", "GWD", "IBS", "ITU", "JPT", "KHV", "LWK", "MSL", "MXL", "PEL", "PJL", "PUR", "STU", "TSI", "YRI"). Explanations for population code can be found at <http://www.1000genomes.org/faq/which-populations-are-part-your->

References

Malone et al. (2010) Modeling sample variables with an Experimental Factor Ontology. *Bioinformatics*, 26(8):1112-8.
 Welter et al. (2014) The NHGRI GWAS Catalog, a curated resource of SNP-trait associations. *Nucleic Acids Res*, 42(Database issue):D1001-6.

Examples

```
GWAS_LD <- dRDataLoader(RData='GWAS_LD')
names(GWAS_LD)
# view the few first data for Great British population (GBR)
GWAS_LD$GBR[1:50,1:30]
```

Hiratani_TableS1

*Mouse multilayer omics dataset from Hiratani et al. (2010)***Description**

This multilayer omics dataset involves the information on DNA replication timing, promoter CpG classification and gene expression. It consists of digitised replication timing, promoter CpG status and expression levels of 17,292 genes in a variety of samples.

Usage

```
load(url("http://dnet.r-forge.r-project.org/data/Datasets/Hiratani_TableS1.RData"))
```

Value

- RT: a replication timing matrix of 17,292 genes X 22 samples. These 22 samples come from 22 cell lines during early mouse embryogenesis, and they can be categorised into: 1) pluripotent cells, including ESCs (ESC_46C, ESC_D3 and ESC_TT2) and iPSCs (iPSC, iPSC_1D4 and iPSC_2D4); 2) partially-reprogrammed iPSCs (piPSC_1A2, piPSC_1B3 and piPSC_V3); 3) early epiblast (EPL and EMB3_D3); 4) late epiblast (EpiSC5 and EpiSC7); 5) Ectoderm (EBM6_D3, EBM9_D3, NPC_46C and NPC_TT2); 6) Mesoderm and Endoderm; and 7) late Mesoderm (Myoblast, MEF_female and MEF_male).
- CpG: a matrix of 17,292 genes X 1 containing gene additional information on promoter CpG classification, with '1' for HCP (high CpG density promoters), '-1' for LCP (low CpG density promoters), '0' for ICP (intermediate CpG density promoters), and 'NA' for unclassified.
- EX: an expression matrix of 17,292 genes X 8 samples, and samples include pluripotent cells (ESC_D3); early epiblast (EMB3_D3); late epiblast (EpiSC7); Ectoderm (EBM6_D3 and EBM9_D3); Mesoderm and Endoderm.

References

Mikkelsen et al. (2007). Genome-wide maps of chromatin state in pluripotent and lineage-committed cells. *Nature*, 448:553-560.

Hiratani et al. (2010). Genome-wide dynamics of replication timing revealed by in vitro models of mouse embryogenesis. *Genome Research*, 20:155-169.

Examples

```
load(url("http://dnet.r-forge.r-project.org/RData/1.0.7/Hiratani_TableS1.RData"))
ls() # you should see three variables: 'RT', 'CpG' and 'EX'
```

ig.DO

Disease Ontology (DO).

Description

An R object that contains information on Disease Ontology terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on <http://sourceforge.net/p/diseaseontology/code/HEAD/tree/trunk/HumanDO.obo?format=raw>.

Usage

```
ig.DO <- dRDataLoader(RData='ig.DO')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Schriml et al. (2012) Disease Ontology: a backbone for disease semantic integration. *Nucleic Acids Res*, 40:D940-946.

Examples

```
ig.DO <- dRDataLoader(RData='ig.DO')
ig.DO
```

ig.GOBP

Gene Ontology Biological Process (GOBP).

Description

An R object that contains information on Gene Ontology Biological Process terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo.

Usage

```
ig.GOBP <- dRDataLoader(RData='ig.GOBP')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
ig.GOBP <- dRDataLoader(RData='ig.GOBP')
ig.GOBP
```

ig.GOCC

Gene Ontology Cellular Component (GOCC).

Description

An R object that contains information on Gene Ontology Cellular Component terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo.

Usage

```
ig.GOCC <- dRDataLoader(RData='ig.GOCC')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
ig.GOCC <- dRDataLoader(RData='ig.GOCC')
ig.GOCC
```

ig.GOMF

Gene Ontology Molecular Function (GOMF).

Description

An R object that contains information on Gene Ontology Molecular Function terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo.

Usage

```
ig.GOMF <- dRDataLoader(RData='ig.GOMF')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
ig.GOMF <- dRDataLoader(RData='ig.GOMF')
ig.GOMF
```

`ig.HPCM`*Human Phenotype Clinical Modifier (HPCM).*

Description

An R object that contains information on Human Phenotype Clinical Modifier terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on <http://purl.obolibrary.org/obo/hp.obo>.

Usage

```
ig.HPCM <- dRDataLoader(RData='ig.HPCM')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
ig.HPCM <- dRDataLoader(RData='ig.HPCM')
ig.HPCM
```

`ig.HPMA`*Human Phenotype Mortality Aging (HPMA).*

Description

An R object that contains information on Human Phenotype Mortality Aging terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on <http://purl.obolibrary.org/obo/hp.obo>.

Usage

```
data(ig.HPMA)
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
#ig.HPMA <- dRDataLoader(RData='ig.HPMA')
data(ig.HPMA)
ig.HPMA
```

 ig.HPMI

Human Phenotype Mode of Inheritance (HPMI).

Description

An R object that contains information on Human Phenotype Mode of Inheritance terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on <http://purl.obolibrary.org/obo/hp.obo>.

Usage

```
ig.HPMI <- dRDataLoader(RData='ig.HPMI')
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
ig.HPMI <- dRDataLoader(RData='ig.HPMI')
ig.HPMI
```

ig.HPPA

Human Phenotype Phenotypic Abnormality (HPPA).

Description

An R object that contains information on Human Phenotype Phenotypic Abnormality terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on <http://purl.obolibrary.org/obo/hp.obo>.

Usage

```
data(ig.HPPA)
```

Value

an object of class "igraph". As a direct graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
ig.HPPA
```

ig.MP

Mammalian Phenotype (MP).

Description

An R object that contains information on Mammalian Phenotype terms. These terms are organised as a direct acyclic graph (DAG), which is further stored as an object of the class 'igraph' (see <http://igraph.org/r/doc/aaa-igraph-package.html>). This data is prepared based on ftp://ftp.informatics.jax.org/pub/reports/MPheno_OBO.ontology.

Usage

```
ig.MP <- dRDataLoader(RData='ig.MP')
```

Value

an object of class "igraph". As a directed graph, it has attributes to vertices/nodes and edges:

- vertex attributes: "name" (i.e. "Term ID"), "term_id" (i.e. "Term ID"), "term_name" (i.e. "Term Name") and "term_distance" (i.e. Term Distance: the distance to the root; always 0 for the root itself)
- edge attributes: "relation" (either 'is_a' or 'part_of')

References

Smith et al. (2009) The Mammalian Phenotype Ontology: enabling robust annotation and comparative analysis. *Wiley Interdiscip Rev Syst Biol Med*, 1:390-399.

Examples

```
ig.MP <- dRDataLoader(RData='ig.MP')
ig.MP
```

IlluminaHumanHT

Illumina HumanHT-12 v4 annotation data

Description

This dataset contains annotation data for the Illumina HumanHT-12 v4 BeadChip gene expression array platform.

Usage

```
IlluminaHumanHT <- dRDataLoader(RData='IlluminaHumanHT')
```

Value

a list with 2 components:

- Info: a data frame. Notably, the column 'Probematch' of 1 indicates a probe sequence is uniquely mapped to genomic location
- GR: an object of class "GRanges", storing only those probes uniquely mapped to autosomal genomic locations

Examples

```
IlluminaHumanHT <- dRDataLoader(RData='IlluminaHumanHT')
str(IlluminaHumanHT)
IlluminaHumanHT$Info[1:10,]
IlluminaHumanHT$GR
```

IlluminaOmniExpress	<i>Illumina HumanOmniExpress-12 v1.0 annotation data</i>
---------------------	--

Description

This dataset contains annotation data for the Illumina HumanOmniExpress-12 v1.0 BeadChip array platform for genome-wide association studies.

Usage

```
IlluminaOmniExpress <- dRDataLoader(RData='IlluminaOmniExpress')
```

Value

a list with 2 components:

- Info: a data frame
- GR: an object of class "GRanges"

Examples

```
IlluminaOmniExpress <- dRDataLoader(RData='IlluminaOmniExpress')
str(IlluminaOmniExpress)
IlluminaOmniExpress$Info[1:10,]
IlluminaOmniExpress$GR
```

ImmunoBase	<i>Immune-disease associated variants, regions and genes from ImmunoBase (hg19)</i>
------------	---

Description

This dataset contains data obtained from ImmunoBase. For each of 20 immune-diseases, its associated variants, regions, and nearby genes (within 500kb) are stored.

Usage

```
ImmunoBase <- dRDataLoader(RData.customised='ImmunoBase')
```

Value

a list with 5 components:

- disease: a character of disease name
- variants: an object of class "GRanges", storing genomic locations of associated variants plus their significance and odd ratios
- regions: an object of class "GRanges", storing genomic locations of associated regions
- genes_variants: a named vector for nearby genes within 500kb of associated variants; the element names are gene symbols, the element values for the shortest distance to all associated variants

- `genes_regions`: a named vector for nearby genes within 500kb of associated regions; the element names are gene symbols, the element values for the shortest distance to all associated regions

Examples

```
ImmunoBase <- dRDataLoader(RData.customised='ImmunoBase')
names(ImmunoBase)
str(ImmunoBase$AS)
ImmunoBase$AS$disease
ImmunoBase$AS$variants
head(ImmunoBase$AS$genes_variants)
head(ImmunoBase$AS$genes_regions)
```

ImmunoBase_LD	<i>Linkage Disequilibrium (LD) of ImmunoBase lead SNPs according to the 1000 Genomics Project data (phase 3)</i>
---------------	--

Description

This dataset involves LD of ImmunoBase SNPs calculated by PLINK based on the 1000 Genomics Project data (phase 3).

Usage

```
ImmunoBase_LD <- dRDataLoader(RData.customised='ImmunoBase_LD')
```

Value

a list of sparse Matrix of class "dgCMatrix". Each list represents one of 5 super populations, containing sparse matrix of ImmunoBase lead SNPs (rows) and LD SNPs (columns). Non-zero values indicate r^2 (only those no less than 0.8). The population include 5 super populations ("AFR", "AMR", "EAS", "EUR", "SAS"). Explanations for these super-population code can be found at <http://www.1000genomes.org/faq/which-populations-are-part-your-study>.

References

Malone et al. (2010) Modeling sample variables with an Experimental Factor Ontology. *Bioinformatics*, 26(8):1112-8.

Examples

```
ImmunoBase_LD <- dRDataLoader(RData.customised='ImmunoBase_LD')
names(ImmunoBase_LD)
# view the few first data for European population (EUR)
ImmunoBase_LD$EUR[1:50,1:30]
```

JKscience_expression *Gene expression datasets across four conditions (shared by 228 individuals) from Benjamin et al. (2014)*

Description

This dataset involves 228 individuals with expression data for all four conditions/contexts, that is, in the naive state (CD14), after 2-hour LPS (LPS2), after 24-hour LPS (LPS24), and after exposure to IFN (IFN). Also included are the probe information and the demographics information about individuals. For genotype data for these individuals, please refer to [JKscience_genotype](#).

Usage

```
JKscience_expression <- dRDataLoader(RData.customised='JKscience_expression')
```

Value

a list with 3 components:

- eContext: a list of 4 components, each for one of four conditions/contexts (that is, "CD14", "LPS2", "LPS24" and "IFN") and each containing a matrix of probes X individuals
- probeInfo: a list of 2 components, both storing probe information including their genomic locations. The component JKscience_expression\$probeInfo\$Info contains a data frame, the second JKscience_expression\$probeInfo\$GR is an object of class "GRanges"
- demoInfo: a data frame containing demographics information about individuals

References

Fairfax et al. (2014). Innate immune activity conditions the effect of regulatory variants upon monocyte gene expression. *Science*, 343(6175):1246949.

Examples

```
JKscience_expression <- dRDataLoader(RData.customised='JKscience_expression')
names(JKscience_expression)
# for eContext
str(JKscience_expression$eContext)
dim(JKscience_expression$eContext$CD14)
JKscience_expression$eContext$CD14[1:5, 1:5]
# for probeInfo
names(JKscience_expression$probeInfo)
JKscience_expression$probeInfo$Info[1:5, ]
JKscience_expression$probeInfo$GR
# for demoInfo
JKscience_expression$demoInfo[1:5, ]
```

JKscience_genotype *Genotype datasets for 228 individuals from Benjamin et al. (2014)*

Description

This dataset involves 228 individuals with genotype data. These individuals also contain expression data for all four conditions/contexts; see [JKscience_expression](#). Also included are the SNP information and the demographics information about individuals.

Usage

```
JKscience_genotype <- dRDataLoader(RData.customised='JKscience_genotype')
```

Value

a list with 3 components:

- `sGenotype`: an object of the `dgCMatrix` class (a sparse matrix of SNP X individuals). The possible values are '0' (carrying both major alleles), '1' (carrying heterogeneous alleles, one major allele and one minor allele), '2' (carrying both minor alleles), and 'NA' (missing data)
- `snpInfo`: a list of 2 components, both storing SNP information including their genomic locations. The component `JKscience_genotype$snpInfo$Info` contains a data frame, the second `JKscience_genotype$snpInfo$GR` is an object of class "GRanges"
- `demoInfo`: a data frame containing demographics information about individuals

References

Fairfax et al. (2014). Innate immune activity conditions the effect of regulatory variants upon monocyte gene expression. *Science*, 343(6175):1246949.

Examples

```
JKscience_genotype <- dRDataLoader(RData.customised='JKscience_genotype')
names(JKscience_genotype)
# for sGenotype
dim(JKscience_genotype$sGenotype)
JKscience_genotype$sGenotype[1:5, 1:5]
# for snpInfo
names(JKscience_genotype$snpInfo)
JKscience_genotype$snpInfo$Info[1:5, ]
JKscience_genotype$snpInfo$GR
# for demoInfo
JKscience_genotype$demoInfo[1:5, ]
```

JKscience_TS2A	<i>Table S2A for cis-eQTLs among shared datasets from Benjamin et al. (2014)</i>
----------------	--

Description

This dataset involves 228 individuals with expression data for all four conditions, that is, in the naive state (Naive), after 2-hour LPS (LPS2), after 24-hour LPS (LPS24), and after exposure to IFN (IFN). Local, likely cis-acting eQTL (referred to as cis-eQTL) were defined as SNPs showing association with gene expression that were located within a 1-Mb window of the associated probe. The eQTL analysis was performed with the R package MatrixEQTL using an additive linear model, reporting both test statistic and FDR.

Usage

```
JKscience_TS2A <- dRDataLoader(RData.customised='JKscience_TS2A')
```

Value

a data frame. It has the following columns: "variant" (cis-eQTLs), "ArrayAddress" (illuminaHumanv4), "GeneID" (Entrez GeneID), "Symbol" (gene symbol), "Naive_t" (test statistic for naive samples), "LPS2_t", "LPS24_t", "IFN_t", "Naive_fdr" (FDR for naive samples), "LPS2_fdr", "LPS24_fdr" and "IFN_fdr".

References

Fairfax et al. (2014). Innate immune activity conditions the effect of regulatory variants upon monocyte gene expression. *Science*, 343(6175):1246949.

Examples

```
JKscience_TS2A <- dRDataLoader(RData.customised='JKscience_TS2A')
JKscience_TS2A[1:5,]
```

JKscience_TS2B	<i>Table S2B for cis-eQTLs among complete datasets from Benjamin et al. (2014)</i>
----------------	--

Description

This dataset involves the complete 432 individuals in four conditions, that is, in the naive state (Naive), after 2-hour LPS (LPS2), after 24-hour LPS (LPS24), and after exposure to IFN (IFN). Local, likely cis-acting eQTL (referred to as cis-eQTL) were defined as SNPs showing association with gene expression that were located within a 1-Mb window of the associated probe. The eQTL analysis was performed with the R package MatrixEQTL using an additive linear model, reporting both test statistic and FDR.

Usage

```
JKscience_TS2B <- dRDataLoader(RData.customised='JKscience_TS2B')
```

Value

a data frame. It has the following columns: "variant" (cis-eQTLs), "ArrayAddress" (illuminaHumanv4), "GeneID" (Entrez GeneID), "Symbol" (gene symbol), "Naive_t" (test statistic for naive samples), "LPS2_t", "LPS24_t", "IFN_t", "Naive_fdr" (FDR for naive samples), "LPS2_fdr", "LPS24_fdr" and "IFN_fdr".

References

Fairfax et al. (2014). Innate immune activity conditions the effect of regulatory variants upon monocyte gene expression. *Science*, 343(6175):1246949.

Examples

```
JKscience_TS2B <- dRDataLoader(RData.customised='JKscience_TS2B')
JKscience_TS2B[1:5,]
```

JKscience_TS3A	<i>Table S3A for trans-eQTLs among complete datasets from Benjamin et al. (2014)</i>
----------------	--

Description

This dataset involves the complete 432 individuals in four conditions, that is, in the naive state (Naive), after 2-hour LPS (LPS2), after 24-hour LPS (LPS24), and after exposure to IFN (IFN). Those SNPs showing association with gene expression that were outside within a 1-Mb window of the associated probe were deemed trans-eQTLs. The eQTL analysis was performed with the R package MatrixEQTL using an additive linear model, reporting both test statistic and FDR.

Usage

```
JKscience_TS3A <- dRDataLoader(RData.customised='JKscience_TS3A')
```

Value

a data frame. It has the following columns: "variant" (cis-eQTLs), "ArrayAddress" (illuminaHumanv4), "GeneID" (Entrez GeneID), "Symbol" (gene symbol), "Naive_t" (test statistic for naive samples), "LPS2_t", "LPS24_t", "IFN_t", "Naive_fdr" (FDR for naive samples), "LPS2_fdr", "LPS24_fdr" and "IFN_fdr".

References

Fairfax et al. (2014). Innate immune activity conditions the effect of regulatory variants upon monocyte gene expression. *Science*, 343(6175):1246949.

Examples

```
JKscience_TS3A <- dRDataLoader(RData.customised='JKscience_TS3A')
JKscience_TS3A[1:5,]
```

org.At.eg

Arabidopsis Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the arabidopsis. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.At.eg <- dRDataLoader(RData='org.At.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.At.eg <- dRDataLoader(RData='org.At.eg')
names(org.At.eg)
org.At.eg$gene_info[1:5,]
```

org.At.egGOBP

Annotations of Arabidopsis Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).

Description

An R object that contains associations between Gene Ontology Biological Process terms and Arabidopsis Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.At.egGOBP <- dRDataLoader(RData='org.At.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.At.egGOBP <- dRDataLoader(RData='org.At.egGOBP')
names(org.At.egGOBP)
```

org.At.egGOCC	<i>Annotations of Arabidopsis Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Arabidopsis Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.At.egGOCC <- dRDataLoader(RData='org.At.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.At.egGOCC <- dRDataLoader(RData='org.At.egGOCC')
names(org.At.egGOCC)
```

org.At.egGOMF	<i>Annotations of Arabidopsis Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Arabidopsis Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.At.egGOMF <- dRDataLoader(RData='org.At.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.At.egGOMF <- dRDataLoader(RData='org.At.egGOMF')
names(org.At.egGOMF)
```

 org.At.egPS

Annotations of Arabidopsis Entrez Genes (EG) by phylostratific age (PS).

Description

An R object that contains phylostratific age information for Arabidopsis Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Arabidopsis Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the arabidopsis, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.At.egPS <- dRDataLoader(RData='org.At.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.At.egPS <- dRDataLoader(RData='org.At.egPS')
names(org.At.egPS)
```

org.At.egSF	<i>Annotations of Arabidopsis Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for Arabidopsis Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Arabidopsis Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.At.egSF <- dRDataLoader(RData='org.At.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
 Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.At.egSF <- dRDataLoader(RData='org.At.egSF')
names(org.At.egSF)
```

org.At.string	<i>Arabidopsis functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in arabidopsis. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.At.string <- dRDataLoader(RData='org.At.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.At.string <- dRDataLoader(RData='org.At.string')
org.At.string
```

org.Ce.eg

C.elegans Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the c.elegans. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Ce.eg <- dRDataLoader(RData='org.Ce.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Ce.eg <- dRDataLoader(RData='org.Ce.eg')
names(org.Ce.eg)
org.Ce.eg$gene_info[1:5,]
```

org.Ce.egGOBP	<i>Annotations of C.elegans Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Biological Process terms and C.elegans Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Ce.egGOBP <- dRDataLoader(RData='org.Ce.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Ce.egGOBP <- dRDataLoader(RData='org.Ce.egGOBP')
names(org.Ce.egGOBP)
```

org.Ce.egGOCC *Annotations of C.elegans Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).*

Description

An R object that contains associations between Gene Ontology Cellular Component terms and C.elegans Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Ce.egGOCC <- dRDataLoader(RData='org.Ce.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Ce.egGOCC <- dRDataLoader(RData='org.Ce.egGOCC')
names(org.Ce.egGOCC)
```

org.Ce.egGOMF *Annotations of C.elegans Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).*

Description

An R object that contains associations between Gene Ontology Molecular Function terms and C.elegans Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Ce.egGOMF <- dRDataLoader(RData='org.Ce.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Ce.egGOMF <- dRDataLoader(RData='org.Ce.egGOMF')
names(org.Ce.egGOMF)
```

org.Ce.egPS

Annotations of C.elegans Entrez Genes (EG) by phylostratific age (PS).

Description

An R object that contains phylostratific age information for *C.elegans* Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a *C.elegans* Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the *C.elegans*, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Ce.egPS <- dRDataLoader(RData='org.Ce.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or

left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.

- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.

Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Ce.egPS <- dRDataLoader(RData='org.Ce.egPS')
names(org.Ce.egPS)
```

org.Ce.egSF	<i>Annotations of C.elegans Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for C.elegans Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for C.elegans Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Ce.egSF <- dRDataLoader(RData='org.Ce.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.

Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Ce.egSF <- dRDataLoader(RData='org.Ce.egSF')
names(org.Ce.egSF)
```

org.Ce.string	<i>C.elegans functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in c.elegans. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Ce.string <- dRDataLoader(RData='org.Ce.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Ce.string <- dRDataLoader(RData='org.Ce.string')
org.Ce.string
```

 org.Da.eg

Zebrafish Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the zebrafish. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Da.eg <- dRDataLoader(RData='org.Da.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Da.eg <- dRDataLoader(RData='org.Da.eg')
names(org.Da.eg)
org.Da.eg$gene_info[1:5,]
```

 org.Da.egGOBP

Annotations of Zebrafish Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).

Description

An R object that contains associations between Gene Ontology Biological Process terms and Zebrafish Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Da.egGOBP <- dRDataLoader(RData='org.Da.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Da.egGOBP <- dRDataLoader(RData='org.Da.egGOBP')
names(org.Da.egGOBP)
```

org.Da.egGOCC	<i>Annotations of Zebrafish Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Zebrafish Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Da.egGOCC <- dRDataLoader(RData='org.Da.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Da.egGOCC <- dRDataLoader(RData='org.Da.egGOCC')
names(org.Da.egGOCC)
```

org.Da.egGOMF	<i>Annotations of Zebrafish Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Zebrafish Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Da.egGOMF <- dRDataLoader(RData='org.Da.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Da.egGOMF <- dRDataLoader(RData='org.Da.egGOMF')
names(org.Da.egGOMF)
```

Description

An R object that contains phylostratific age information for Zebrafish Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Zebrafish Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the zebrafish, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Da.egPS <- dRDataLoader(RData='org.Da.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Da.egPS <- dRDataLoader(RData='org.Da.egPS')
names(org.Da.egPS)
```

org.Da.egSF	<i>Annotations of Zebrafish Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for Zebrafish Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Zebrafish Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Da.egSF <- dRDataLoader(RData='org.Da.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
 Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Da.egSF <- dRDataLoader(RData='org.Da.egSF')
names(org.Da.egSF)
```

org.Da.string	<i>Zebrafish functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in zebrafish. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (`score` ≥ 0.4) are retained.

Usage

```
org.Da.string <- dRDataLoader(RData='org.Da.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Da.string <- dRDataLoader(RData='org.Da.string')
org.Da.string
```

org.Dm.eg

Fruitfly Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the fruitfly. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Dm.eg <- dRDataLoader(RData='org.Dm.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Dm.eg <- dRDataLoader(RData='org.Dm.eg')
names(org.Dm.eg)
org.Dm.eg$gene_info[1:5,]
```

org.Dm.egGOBP	<i>Annotations of Fruitfly Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).</i>
---------------	--

Description

An R object that contains associations between Gene Ontology Biological Process terms and Fruitfly Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Dm.egGOBP <- dRDataLoader(RData='org.Dm.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Dm.egGOBP <- dRDataLoader(RData='org.Dm.egGOBP')
names(org.Dm.egGOBP)
```

org.Dm.egGOCC	<i>Annotations of Fruitfly Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	--

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Fruitfly Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Dm.egGOCC <- dRDataLoader(RData='org.Dm.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Dm.egGOCC <- dRDataLoader(RData='org.Dm.egGOCC')
names(org.Dm.egGOCC)
```

org.Dm.egGOMF	<i>Annotations of Fruitfly Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	--

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Fruitfly Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Dm.egGOMF <- dRDataLoader(RData='org.Dm.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Dm.egGOMF <- dRDataLoader(RData='org.Dm.egGOMF')
names(org.Dm.egGOMF)
```

org.Dm.egPS

Annotations of Fruitfly Entrez Genes (EG) by phylostratific age (PS).

Description

An R object that contains phylostratific age information for Fruitfly Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Fruitfly Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the fruitfly, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Dm.egPS <- dRDataLoader(RData='org.Dm.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or

left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.

- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.

Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Dm.egPS <- dRDataLoader(RData='org.Dm.egPS')
names(org.Dm.egPS)
```

org.Dm.egSF	<i>Annotations of Fruitfly Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	--

Description

An R object that contains domain superfamily information for Fruitfly Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Fruitfly Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Dm.egSF <- dRDataLoader(RData='org.Dm.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.

Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Dm.egSF <- dRDataLoader(RData='org.Dm.egSF')
names(org.Dm.egSF)
```

org.Dm.string	<i>Fruitfly functional protein association network from STRING (version 10).</i>
---------------	--

Description

An igraph object that contains a functional protein association network in fruitfly. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Dm.string <- dRDataLoader(RData='org.Dm.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Dm.string <- dRDataLoader(RData='org.Dm.string')
org.Dm.string
```

org.Gg.eg	<i>Chicken Entrez Genes (EG).</i>
-----------	-----------------------------------

Description

An R object that contains Entrez Gene information for the chicken. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Gg.eg <- dRDataLoader(RData='org.Gg.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Gg.eg <- dRDataLoader(RData='org.Gg.eg')
names(org.Gg.eg)
org.Gg.eg$gene_info[1:5,]
```

org.Gg.egGOBP	<i>Annotations of Chicken Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Biological Process terms and Chicken Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Gg.egGOBP <- dRDataLoader(RData='org.Gg.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Gg.egGOBP <- dRDataLoader(RData='org.Gg.egGOBP')
names(org.Gg.egGOBP)
```

org.Gg.egGOCC	<i>Annotations of Chicken Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Chicken Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Gg.egGOCC <- dRDataLoader(RData='org.Gg.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Gg.egGOCC <- dRDataLoader(RData='org.Gg.egGOCC')
names(org.Gg.egGOCC)
```

org.Gg.egGOMF	<i>Annotations of Chicken Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Chicken Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Gg.egGOMF <- dRDataLoader(RData='org.Gg.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Gg.egGOMF <- dRDataLoader(RData='org.Gg.egGOMF')
names(org.Gg.egGOMF)
```

`org.Gg.egPS`*Annotations of Chicken Entrez Genes (EG) by phylostratific age (PS).*

Description

An R object that contains phylostratific age information for Chicken Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Chicken Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the chicken, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Gg.egPS <- dRDataLoader(RData='org.Gg.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Gg.egPS <- dRDataLoader(RData='org.Gg.egPS')
names(org.Gg.egPS)
```

org.Gg.egSF	<i>Annotations of Chicken Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for Chicken Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Chicken Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Gg.egSF <- dRDataLoader(RData='org.Gg.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
 Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Gg.egSF <- dRDataLoader(RData='org.Gg.egSF')
names(org.Gg.egSF)
```

org.Gg.string	<i>Chicken functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in chicken. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Gg.string <- dRDataLoader(RData='org.Gg.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Gg.string <- dRDataLoader(RData='org.Gg.string')
org.Gg.string
```

org.Hs.eg

Human Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the human. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Hs.eg <- dRDataLoader(RData='org.Hs.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of nGene X 7 containing gene information, where nGene is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
# not run
org.Hs.eg <- dRDataLoader(RData='org.Hs.eg')
names(org.Hs.eg)
org.Hs.eg$gene_info[1:5,]
```

org.Hs.egDGIdb

Annotations of Human Entrez Genes (EG) by DGIdb categories.

Description

An R object that contains associations between DGIdb categories and Human Entrez Genes. This data is prepared based on <http://dgidb.genome.wustl.edu/downloads/categories.tsv>.

Usage

```
org.Hs.egDGIdb <- dRDataLoader(RData='org.Hs.egDGIdb')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Griffith et al. (2013) DGIdb: mining the druggable genome. *Nature methods*, 10(12):1209-10.

Examples

```
org.Hs.egDGIdb <- dRDataLoader(RData='org.Hs.egDGIdb')
names(org.Hs.egDGIdb)
```

 org.Hs.egDO

Annotations of Human Entrez Genes (EG) by Disease Ontology (DO).

Description

An R object that contains associations between Disease Ontology terms and Human Entrez Genes. This data is first prepared based on <http://sourceforge.net/p/diseaseontology/code/HEAD/tree/trunk/HumanDO.obo?format=raw> and <http://dga.nubic.northwestern.edu/ajax/Download.ajax.php>, which results in annotations of Human Entrez Genes.

Usage

```
org.Hs.egDO <- dRDataLoader(RData='org.Hs.egDO')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets (i.e. DO terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Schriml et al. (2012) Disease Ontology: a backbone for disease semantic integration. *Nucleic Acids Res*, 40:D940-946.
- Peng et al. (2012) The Disease and Gene Annotations (DGA): an annotation resource for human disease. *Nucleic Acids Res*, 41:D553-560.
- Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Hs.egDO <- dRDataLoader(RData='org.Hs.egDO')
names(org.Hs.egDO)
```

 org.Hs.egGOBP

Annotations of Human Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).

Description

An R object that contains associations between Gene Ontology Biological Process terms and Human Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Hs.egGOBP <- dRDataLoader(RData='org.Hs.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Hs.egGOBP <- dRDataLoader(RData='org.Hs.egGOBP')
names(org.Hs.egGOBP)
```

org.Hs.egGOCC	<i>Annotations of Human Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Human Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Hs.egGOCC <- dRDataLoader(RData='org.Hs.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Hs.egGOCC <- dRDataLoader(RData='org.Hs.egGOCC')
names(org.Hs.egGOCC)
```

org.Hs.egGOMF	<i>Annotations of Human Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Human Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Hs.egGOMF <- dRDataLoader(RData='org.Hs.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Hs.egGOMF <- dRDataLoader(RData='org.Hs.egGOMF')
names(org.Hs.egGOMF)
```

org.Hs.egHPCM	<i>Annotations of Human Entrez Genes (EG) by Human Phenotype Clinical Modifier (HPCM).</i>
---------------	--

Description

An R object that contains associations between HPCM terms and Human Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt.

Usage

```
org.Hs.egHPCM <- dRDataLoader(RData='org.Hs.egHPCM')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPCM terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
org.Hs.egHPCM <- dRDataLoader(RData='org.Hs.egHPCM')
names(org.Hs.egHPCM)
```

org.Hs.egHPMA	<i>Annotations of Human Entrez Genes (EG) by Human Phenotype Mortality Aging (HPMA).</i>
---------------	--

Description

An R object that contains associations between HPMA terms and Human Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt.

Usage

```
data(org.Hs.egHPMA)
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPMA terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
data(org.Hs.egHPMA)
names(org.Hs.egHPMA)
```

org.Hs.egHPMI	<i>Annotations of Human Entrez Genes (EG) by Human Phenotype Mode of Inheritance (HPMI).</i>
---------------	--

Description

An R object that contains associations between HPMI terms and Human Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt.

Usage

```
org.Hs.egHPMI <- dRDataLoader(RData='org.Hs.egHPMI')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPMI terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
org.Hs.egHPMI <- dRDataLoader(RData='org.Hs.egHPMI')
names(org.Hs.egHPMI)
```

org.Hs.egHPPA	<i>Annotations of Human Entrez Genes (EG) by Human Phenotype Phenotypic Abnormality (HPPA).</i>
---------------	---

Description

An R object that contains associations between HPPA terms and Human Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt.

Usage

```
data(org.Hs.egHPPA)
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPPA terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Examples

```
org.Hs.egHPPA <- dRDataLoader(RData='org.Hs.egHPPA')
names(org.Hs.egHPPA)
```

org.Hs.egMP	<i>Annotations of Human Entrez Genes (EG) by Mammalian Phenotype (MP).</i>
-------------	--

Description

An R object that contains associations between Mammalian Phenotype terms and Human Entrez Genes. This data is prepared based on ftp://ftp.informatics.jax.org/pub/reports/MPheno_OBO.ontology and ftp://ftp.informatics.jax.org/pub/reports/MGI_PhenoGenoMP.rpt, which results in annotations of Mouse Entrez Genes. Then, these annotations are transferred to Human Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Hs.egMP <- dRDataLoader(RData='org.Hs.egMP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. MP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Smith et al. (2009) The Mammalian Phenotype Ontology: enabling robust annotation and comparative analysis. *Wiley Interdiscip Rev Syst Biol Med*, 1:390-399.

Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Hs.egMP <- dRDataLoader(RData='org.Hs.egMP')
names(org.Hs.egMP)
```

org.Hs.egMsigdbC1 *Annotations of Human Entrez Genes (EG) by C1 collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C1 positional gene sets and Human Entrez Genes. C1 collections are about positional gene sets for each human chromosome and cytogenetic band, each gene set corresponding to each human chromosome and each cytogenetic band that has at least one gene. These gene sets are helpful in identifying effects related to chromosomal deletions or amplifications, dosage compensation, epigenetic silencing, and other regional effects.

Usage

```
org.Hs.egMsigdbC1 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC1')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC1 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC1')
names(org.Hs.egMsigdbC1)
```

```
org.Hs.egMsigdbC2BIOCARTA
```

Annotations of Human Entrez Genes (EG) by C2:BIOCARTA collections.

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:BIOCARTA (BioCarta pathways) gene sets and Human Entrez Genes. C2:BIOCARTA gene sets are derived from the BioCarta pathway database <http://www.biocarta.com/genes/index.asp>.

Usage

```
org.Hs.egMsigdbC2BIOCARTA <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2BIOCARTA')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2BIOCARTA <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2BIOCARTA')
names(org.Hs.egMsigdbC2BIOCARTA)
```

org.Hs.egMsigdbC2CGP *Annotations of Human Entrez Genes (EG) by C2:CGP collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:CGP (chemical and genetic perturbations) gene sets and Human Entrez Genes. C2:CGP gene sets are about expression signatures of genetic and chemical perturbations. A number of these gene sets come in pairs: an xxx_UP (xxx_DN) gene set representing genes induced (repressed) by the perturbation.

Usage

```
org.Hs.egMsigdbC2CGP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CGP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2CGP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CGP')
names(org.Hs.egMsigdbC2CGP)
```

org.Hs.egMsigdbC2CP *Annotations of Human Entrez Genes (EG) by C2:CP collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:CP (Canonical pathways) gene sets and Human Entrez Genes. C2:CP gene sets are from the pathway databases, and usually are canonical representations of a biological process compiled by domain experts.

Usage

```
org.Hs.egMsigdbC2CP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2CP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CP')
names(org.Hs.egMsigdbC2CP)
```

```
org.Hs.egMsigdbC2CPall
```

Annotations of Human Entrez Genes (EG) by C2:CP collections.

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:CPall (all pathways) gene sets and Human Entrez Genes. C2:CP gene sets are from the pathway databases, and usually are canonical representations of a biological process compiled by domain experts.

Usage

```
org.Hs.egMsigdbC2CPall <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CPall')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2CPa11 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2CPa11')
names(org.Hs.egMsigdbC2CPa11)
```

org.Hs.egMsigdbC2KEGG *Annotations of Human Entrez Genes (EG) by C2:KEGG collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:KEGG (KEGG pathways) gene sets and Human Entrez Genes. C2:KEGG gene sets are derived from the KEGG pathway database <http://www.genome.jp/kegg/pathway.html>.

Usage

```
org.Hs.egMsigdbC2KEGG <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2KEGG')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet X 4` containing gene set information, where `nSet` is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2KEGG <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2KEGG')
names(org.Hs.egMsigdbC2KEGG)
```

org.Hs.egMsigdbC2REACTOME

Annotations of Human Entrez Genes (EG) by C2:REACTOME collections.

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C2:REACTOME (Reactome pathways) gene sets and Human Entrez Genes. C2:REACTOME gene sets are derived from the Reactome pathway database <http://www.reactome.org/>.

Usage

```
org.Hs.egMsigdbC2REACTOME <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2REACTOME')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC2REACTOME <- dRDataLoader(RData.customised='org.Hs.egMsigdbC2REACTOME')
names(org.Hs.egMsigdbC2REACTOME)
```

org.Hs.egMsigdbC3MIR *Annotations of Human Entrez Genes (EG) by C3:MIR collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C3:MIR (microRNA targets) gene sets and Human Entrez Genes. C3 collections are about motif gene sets that contain genes that share a cis-regulatory motif that is conserved across the human, mouse, rat, and dog genomes, and represent known or likely regulatory elements in promoters and 3'-UTRs. C3:MIR gene sets contain genes that share a 3'-UTR microRNA binding motif.

Usage

```
org.Hs.egMsigdbC3MIR <- dRDataLoader(RData.customised='org.Hs.egMsigdbC3MIR')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC3MIR <- dRDataLoader(RData.customised='org.Hs.egMsigdbC3MIR')
names(org.Hs.egMsigdbC3MIR)
```

org.Hs.egMsigdbC3TFT *Annotations of Human Entrez Genes (EG) by C3:TFT collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C3:TFT (transcription factor targets) gene sets and Human Entrez Genes. C3 collections are about motif gene sets that contain genes that share a cis-regulatory motif that is conserved across the human, mouse, rat, and dog genomes, and represent known or likely regulatory elements in promoters and 3'-UTRs. C3:TFT gene sets contain genes that share a transcription factor binding site defined in the TRANSFAC (version 7.4, <http://www.gene-regulation.com/>) database.

Usage

```
org.Hs.egMsigdbC3TFT <- dRDataLoader(RData.customised='org.Hs.egMsigdbC3TFT')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC3TFT <- dRDataLoader(RData.customised='org.Hs.egMsigdbC3TFT')
names(org.Hs.egMsigdbC3TFT)
```

org.Hs.egMsigdbC4CGN *Annotations of Human Entrez Genes (EG) by C4:CGN collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C4:CGN (cancer gene neighborhoods) gene sets and Human Entrez Genes. C4:CGN gene sets are defined by expression neighborhoods centered on 380 cancer-associated genes (see <http://www.ncbi.nlm.nih.gov/pubmed/14593198>).

Usage

```
org.Hs.egMsigdbC4CGN <- dRDataLoader(RData.customised='org.Hs.egMsigdbC4CGN')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of `nSet` X 4 containing gene set information, where `nSet` is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC4CGN <- dRDataLoader(RData.customised='org.Hs.egMsigdbC4CGN')
names(org.Hs.egMsigdbC4CGN)
```

org.Hs.egMsigdbC4CM *Annotations of Human Entrez Genes (EG) by C4:CM collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C4:CM (cancer modules) gene sets and Human Entrez Genes. C4:CM gene sets are defined in <http://www.ncbi.nlm.nih.gov/pubmed/15448693>; the authors first compiled gene sets ('modules') from a variety of resources such as KEGG, GO, and others, and then by mining a large compendium of cancer-related microarray data, they identified 456 such modules as significantly changed in a variety of cancer conditions.

Usage

```
org.Hs.egMsigdbC4CM <- dRDataLoader(RData.customised='org.Hs.egMsigdbC4CM')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC4CM <- dRDataLoader(RData.customised='org.Hs.egMsigdbC4CM')
names(org.Hs.egMsigdbC4CM)
```

org.Hs.egMsigdbC5BP *Annotations of Human Entrez Genes (EG) by C5:BP collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C5:BP (GO biological process) gene sets and Human Entrez Genes.

Usage

```
org.Hs.egMsigdbC5BP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5BP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC5BP <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5BP')
names(org.Hs.egMsigdbC5BP)
```

org.Hs.egMsigdbC5CC *Annotations of Human Entrez Genes (EG) by C5:CC collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C5:CC (GO cellular component) gene sets and Human Entrez Genes.

Usage

```
org.Hs.egMsigdbC5CC <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5CC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC5CC <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5CC')
names(org.Hs.egMsigdbC5CC)
```

org.Hs.egMsigdbC5MF *Annotations of Human Entrez Genes (EG) by C5:MF collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C5:MF (GO molecular function) gene sets and Human Entrez Genes.

Usage

```
org.Hs.egMsigdbC5MF <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5MF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC5MF <- dRDataLoader(RData.customised='org.Hs.egMsigdbC5MF')
names(org.Hs.egMsigdbC5MF)
```

org.Hs.egMsigdbC6 *Annotations of Human Entrez Genes (EG) by C6 collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C6 oncogenic signature gene sets and Human Entrez Genes. C6 collections contain gene sets that represent signatures of cellular pathways which are often dis-regulated in cancer.

Usage

```
org.Hs.egMsigdbC6 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC6')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC6 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC6')
names(org.Hs.egMsigdbC6)
```

org.Hs.egMsigdbC7 *Annotations of Human Entrez Genes (EG) by C7 collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb C7 immunologic signature gene sets and Human Entrez Genes. C7 collections contain gene sets that represent cell states and perturbations within the immune system.

Usage

```
org.Hs.egMsigdbC7 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC7')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbC7 <- dRDataLoader(RData.customised='org.Hs.egMsigdbC7')
names(org.Hs.egMsigdbC7)
```

`org.Hs.egMsigdbH`*Annotations of Human Entrez Genes (EG) by H hallmark collections.*

Description

This data is prepared based on the molecular signatures database (Msigdb; <http://www.broadinstitute.org/gsea/msigdb/index.jsp>). An R object that contains associations between Msigdb H hallmark gene sets and Human Entrez Genes. This collection is the starting point for the exploration of the MSigDB resource. Hallmark gene sets summarize and represent specific well-defined biological states or processes and display coherent expression. These gene sets were generated by a computational methodology based on identifying gene set overlaps and retaining genes that display coordinate expression. The hallmarks reduce noise and redundancy and provide a better delineated biological space.

Usage

```
org.Hs.egMsigdbH <- dRDataLoader(RData.customised='org.Hs.egMsigdbH')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets, and the 4 columns are "setID" (i.e. "Geneset standard name"), "name" (i.e. "Geneset brief description"), "namespace" (i.e. Geneset category code) and "distance" (i.e. "Geneset full description")
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Subramanian et al. (2005) Gene set enrichment analysis: a knowledge-based approach for interpreting genome-wide expression profiles. *Proc Natl Acad Sci U S A.*, 102(43):15545-50.

Examples

```
org.Hs.egMsigdbH <- dRDataLoader(RData.customised='org.Hs.egMsigdbH')
names(org.Hs.egMsigdbH)
```

`org.Hs.egPS`*Annotations of Human Entrez Genes (EG) by phylostratific age (PS).*

Description

An R object that contains phylostratific age information for Human Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Human Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the human, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Hs.egPS <- dRDataLoader(RData='org.Hs.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Hs.egPS <- dRDataLoader(RData='org.Hs.egPS')  
names(org.Hs.egPS)
```

org.Hs.egSF	<i>Annotations of Human Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for Human Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Human Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Hs.egSF <- dRDataLoader(RData='org.Hs.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Hs.egSF <- dRDataLoader(RData='org.Hs.egSF')  
names(org.Hs.egSF)
```

org.Hs.PCommons_DN	<i>Human protein interaction directed network from Pathway Commons (version 7).</i>
--------------------	---

Description

An igraph object that contains a human protein interaction (directed) network. The network is extracted from Pathway Commons (version 7; a comprehensive collection of public biological interactions/pathways from multiple data sources). For each interaction and each relation type, data sources in support are: BIND (see <http://bond.unleashedinformatics.com> and <http://www.ncbi.nlm.nih.gov/pubmed/12519993>), BioGRID (see <http://thebiogrid.org> and <http://www.ncbi.nlm.nih.gov/pubmed/16381927>), CORUM (see <http://mips.helmholtz-muenchen.de/genre/proj/corum> and <http://www.ncbi.nlm.nih.gov/pubmed/19884131>), DIP (see <http://dip.doe-mbi.ucla.edu> and <http://www.ncbi.nlm.nih.gov/pubmed/14681454>), HPRD (see <http://www.hprd.org> and <http://www.ncbi.nlm.nih.gov/pubmed/18988627>), IntAct (see <http://www.ebi.ac.uk/intact> and <http://www.ncbi.nlm.nih.gov/pubmed/24234451>), CTD (see <http://ctdbase.org> and <http://www.ncbi.nlm.nih.gov/pubmed/25326323>), HumanCyc (see <http://www.humancyc.org> and <http://www.ncbi.nlm.nih.gov/pubmed/15642094>), KEGG (see <http://www.genome.jp/kegg> and <http://www.ncbi.nlm.nih.gov/pubmed/23433509>), PANTHER (see <http://www.pantherdb.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23193289>), PhosphoSite (see <http://www.phosphosite.org> and <http://www.ncbi.nlm.nih.gov/pubmed/22135298>), PID (see <http://pid.nci.nih.gov> and <http://www.ncbi.nlm.nih.gov/pubmed/18832364>), Reactome (see <http://www.reactome.org> and <http://www.ncbi.nlm.nih.gov/pubmed/24243840>), ReconX (see <http://humanmetabolism.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23455439>), TRANSFAC (see <http://www.gene-regulation.com> and <http://www.ncbi.nlm.nih.gov/pubmed/18436575>). Only those interactions with directed relations (including relation types: "catalysis_precedes", "controls_expression_of", "controls_phosphorylation_of", "controls_state_change_of" and "controls_transport_of") are retained. For undirected network, please refer to [org.Hs.PCommons_UN](#).

Usage

```
org.Hs.PCommons_DN <- dRDataLoader(RData='org.Hs.PCommons_DN')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: gene symbol for the vertices
- geneid: Entrez geneid for the vertices
- symbol: gene symbol for the vertices
- description: gene description for the vertices

Below are attributes for the edges:

- catalysis_precedes: an integer code indicating support evidence for "catalysis_precedes" relation, that is, the first protein (from) controls a reaction whose output molecule is input to another reaction controlled by the second protein (to)
- controls_expression_of: an integer code indicating support evidence for "controls_expression_of" relation, that is, the first protein (from) controls a conversion or a template reaction that changes expression of the second protein (to)
- controls_phosphorylation_of: an integer code indicating support evidence for "controls_phosphorylation_of" relation, that is, the first protein (from) controls a reaction that changes the phosphorylation status of the second protein (to)
- controls_state_change_of: an integer code indicating support evidence for "controls_state_change_of" relation, that is, the first protein (from) controls a reaction that changes the state of the second protein (to)

- controls_transport_of: an integer code indicating support evidence for "controls_transport_of" relation, that is, the first protein (from) controls a reaction that changes the cellular location of the second protein (to)
- Notably, there are two supporting evidences: with the PubMed references (assigned with 100), and the number of different data sources. The integer code is the sum of these two. A value of 0 means no supporting evidences. For examples, a value of 105 means that the relation is supported by the PubMed references and by 5 different data sources.

References

Cerami et al. (2011) Pathway Commons, a web resource for biological pathway data. *Nucleic Acids Res*, 39(Database issue):D685-90.

Examples

```
org.Hs.PCommons_DN <- dRDataLoader(RData='org.Hs.PCommons_DN')
org.Hs.PCommons_DN
```

```
org.Hs.PCommons_DN.source
```

Human protein interaction directed network for each data source from Pathway Commons (version 7).

Description

A list of igraph objects, each object storing a human protein interaction (directed) network for one of 9 data sources. These data sources are downloaded from from Pathway Commons (version 7; a comprehensive collection of public biological interactions/pathways from multiple data sources). Data sources are: CTD (see <http://ctdbase.org> and <http://www.ncbi.nlm.nih.gov/pubmed/25326323>), HumanCyc (see <http://www.humancyc.org> and <http://www.ncbi.nlm.nih.gov/pubmed/15642094>), KEGG (see <http://www.genome.jp/kegg> and <http://www.ncbi.nlm.nih.gov/pubmed/23433509>), PANTHER (see <http://www.pantherdb.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23193289>), PhosphoSite (see <http://www.phosphosite.org> and <http://www.ncbi.nlm.nih.gov/pubmed/22135298>), PID (see <http://pid.nci.nih.gov> and <http://www.ncbi.nlm.nih.gov/pubmed/18832364>), Reactome (see <http://www.reactome.org> and <http://www.ncbi.nlm.nih.gov/pubmed/24243840>), ReconX (see <http://humanmetabolism.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23455439>), TRANSFAC (see <http://www.gene-regulation.com> and <http://www.ncbi.nlm.nih.gov/pubmed/18436575>). Only those interactions with directed relations (including relation types: "catalysis_precedes", "controls_expression_of", "controls_phosphorylation_of", "controls_state_change_of" and "controls_transport_of") are retained. For the pooled version of this network, please refer to [org.Hs.PCommons_DN](#).

Usage

```
org.Hs.PCommons_DN.source <- dRDataLoader(RData.customised='org.Hs.PCommons_DN.source')
```

Value

A list of igraph objects. For details about the object of class "igraph", please see <http://igraph.org/r/doc/aaa-igraph-package.html>. It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: gene symbol for the vertices
- geneid: Entrez geneid for the vertices
- symbol: gene symbol for the vertices
- description: gene description for the vertices

Below are attributes for the edges:

- catalysis_precedes: an integer code indicating support evidence for "catalysis_precedes" relation, that is, the first protein (from) controls a reaction whose output molecule is input to another reaction controlled by the second protein (to)
- controls_expression_of: an integer code indicating support evidence for "controls_expression_of" relation, that is, the first protein (from) controls a conversion or a template reaction that changes expression of the second protein (to)
- controls_phosphorylation_of: an integer code indicating support evidence for "controls_phosphorylation_of" relation, that is, the first protein (from) controls a reaction that changes the phosphorylation status of the second protein (to)
- controls_state_change_of: an integer code indicating support evidence for "controls_state_change_of" relation, that is, the first protein (from) controls a reaction that changes the state of the second protein (to)
- controls_transport_of: an integer code indicating support evidence for "controls_transport_of" relation, that is, the first protein (from) controls a reaction that changes the cellular location of the second protein (to)
- Notably, there are two supporting evidences: with the PubMed references (assigned with 100), and the number of different data sources. The integer code is the sum of these two. A value of 0 means no supporting evidences. For examples, a value of 105 means that the relation is supported by the PubMed references and by 5 different data sources.

References

Cerami et al. (2011) Pathway Commons, a web resource for biological pathway data. *Nucleic Acids Res*, 39(Database issue):D685-90.

Examples

```
org.Hs.PCommons_DN.source <- dRDataLoader(RData.customised='org.Hs.PCommons_DN.source')
names(org.Hs.PCommons_DN.source)
org.Hs.PCommons_DN.source$KEGG
```

org.Hs.PCommons_UN *Human protein interaction undirected network from Pathway Commons (version 7).*

Description

An igraph object that contains a human protein interaction (undirected) network. The network is extracted from Pathway Commons (version 7; a comprehensive collection of public biological interactions/pathways from multiple data sources). For each interaction and each relation type, data sources in support are: BIND (see <http://bond.unleashedinformatics.com> and <http://www.ncbi.nlm.nih.gov/pubmed/12519993>), BioGRID (see <http://thebiogrid.org> and <http://www.ncbi.nlm.nih.gov/pubmed/16381927>), CORUM (see <http://mips.helmholtz-muenchen>).

de/genre/proj/corum and <http://www.ncbi.nlm.nih.gov/pubmed/19884131>), DIP (see <http://dip.doe-mbi.ucla.edu> and <http://www.ncbi.nlm.nih.gov/pubmed/14681454>), HPRD (see <http://www.hprd.org> and <http://www.ncbi.nlm.nih.gov/pubmed/18988627>), IntAct (see <http://www.ebi.ac.uk/intact> and <http://www.ncbi.nlm.nih.gov/pubmed/24234451>), CTD (see <http://ctdbase.org> and <http://www.ncbi.nlm.nih.gov/pubmed/25326323>), HumanCyc (see <http://www.humancyc.org> and <http://www.ncbi.nlm.nih.gov/pubmed/15642094>), KEGG (see <http://www.genome.jp/kegg> and <http://www.ncbi.nlm.nih.gov/pubmed/23433509>), PANTHER (see <http://www.pantherdb.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23193289>), PhosphoSite (see <http://www.phosphosite.org> and <http://www.ncbi.nlm.nih.gov/pubmed/22135298>), PID (see <http://pid.nci.nih.gov> and <http://www.ncbi.nlm.nih.gov/pubmed/18832364>), Reactome (see <http://www.reactome.org> and <http://www.ncbi.nlm.nih.gov/pubmed/24243840>), ReconX (see <http://humanmetabolism.org> and <http://www.ncbi.nlm.nih.gov/pubmed/23455439>), TRANSFAC (see <http://www.gene-regulation.com> and <http://www.ncbi.nlm.nih.gov/pubmed/18436575>). Only those interactions with undirected relations (including relation types: "interacts_with", "in_complex_with" and "neighbor_of") are retained. For directed network, please refer to [org.Hs.PCommons_DN](#).

Usage

```
org.Hs.PCommons_UN <- dRDataLoader(RData='org.Hs.PCommons_UN')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: gene symbol for the vertices
- geneid: Entrez geneid for the vertices
- symbol: gene symbol for the vertices
- description: gene description for the vertices

Below are attributes for the edges:

- in_complex_with: an integer code indicating support evidence for "in_complex_with" relation, that is, both proteins are members of the same complex
- interacts_with: an integer code indicating support evidence for "interacts_with" relation, that is, both proteins are participants of the same interaction
- neighbor_of: an integer code indicating support evidence for "neighbor_of" relation, that is, both proteins are participants or controllers of the same interaction
- Notably, there are two supporting evidences: with the PubMed references (assigned with 100), and the number of different data sources. The integer code is the sum of these two. A value of 0 means no supporting evidences. For examples, a value of 105 means that the relation is supported by the PubMed references and by 5 different data sources.

References

Cerami et al. (2011) Pathway Commons, a web resource for biological pathway data. *Nucleic Acids Res*, 39(Database issue):D685-90.

Examples

```
org.Hs.PCommons_UN <- dRDataLoader(RData='org.Hs.PCommons_UN')
org.Hs.PCommons_UN
```

org.Hs.string	<i>Human functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in human. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Hs.string <- dRDataLoader(RData='org.Hs.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Hs.string <- dRDataLoader(RData='org.Hs.string')  
org.Hs.string
```

org.Mm.eg

Mouse Entrez Genes (EG).

Description

An R object that contains Entrez Gene information for the mouse. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Mm.eg <- dRDataLoader(RData='org.Mm.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of `nGene X 7` containing gene information, where `nGene` is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Mm.eg <- dRDataLoader(RData='org.Mm.eg')
names(org.Mm.eg)
org.Mm.eg$gene_info[1:5,]
```

org.Mm.egDO

Annotations of Mouse Entrez Genes (EG) by Disease Ontology (DO).

Description

An R object that contains associations between Disease Ontology terms and Mouse Entrez Genes. This data is first prepared based on <http://sourceforge.net/p/diseaseontology/code/HEAD/tree/trunk/HumanDO.obo?format=raw> and <http://dga.nubic.northwestern.edu/ajax/Download.ajax.php>, which results in annotations of Human Entrez Genes. Then, these annotations are transferred to Mouse Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Mm.egDO <- dRDataLoader(RData='org.Mm.egDO')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. DO terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Schriml et al. (2012) Disease Ontology: a backbone for disease semantic integration. *Nucleic Acids Res*, 40:D940-946.

Peng et al. (2012) The Disease and Gene Annotations (DGA): an annotation resource for human disease. *Nucleic Acids Res*, 41:D553-560.

Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Mm.egDO <- dRDataLoader(RData='org.Mm.egDO')
names(org.Mm.egDO)
```

org.Mm.egGOBP	<i>Annotations of Mouse Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Biological Process terms and Mouse Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Mm.egGOBP <- dRDataLoader(RData='org.Mm.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Mm.egGOBP <- dRDataLoader(RData='org.Mm.egGOBP')
names(org.Mm.egGOBP)
```

org.Mm.egGOCC	<i>Annotations of Mouse Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Mouse Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Mm.egGOCC <- dRDataLoader(RData='org.Mm.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Mm.egGOCC <- dRDataLoader(RData='org.Mm.egGOCC')
names(org.Mm.egGOCC)
```

org.Mm.egGOMF	<i>Annotations of Mouse Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Mouse Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Mm.egGOMF <- dRDataLoader(RData='org.Mm.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Mm.egGOMF <- dRDataLoader(RData='org.Mm.egGOMF')
names(org.Mm.egGOMF)
```

org.Mm.egHPCM	<i>Annotations of Mouse Entrez Genes (EG) by Human Phenotype Clinical Modifier (HPCM).</i>
---------------	--

Description

An R object that contains associations between HPCM terms and Mouse Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt, which results in annotations of Human Entrez Genes. Then, these annotations are transferred to Mouse Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Mm.egHPCM <- dRDataLoader(RData='org.Mm.egHPCM')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPCM terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.

Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Mm.egHPCM <- dRDataLoader(RData='org.Mm.egHPCM')
names(org.Mm.egHPCM)
```

org.Mm.egHPMA	<i>Annotations of Mouse Entrez Genes (EG) by Human Phenotype Mortality Aging (HPMA).</i>
---------------	--

Description

An R object that contains associations between HPMA terms and Mouse Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt, which results in annotations of Human Entrez Genes. Then, these annotations are transferred to Mouse Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Mm.egHPMA <- dRDataLoader(RData='org.Mm.egHPMA')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPMA terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.
- Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Mm.egHPMA <- dRDataLoader(RData='org.Mm.egHPMA')
names(org.Mm.egHPMA)
```

org.Mm.egHPMI	<i>Annotations of Mouse Entrez Genes (EG) by Human Phenotype Mode of Inheritance (HPMI).</i>
---------------	--

Description

An R object that contains associations between HPMI terms and Mouse Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt, which results in annotations of Human Entrez Genes. Then, these annotations are transferred to Mouse Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Mm.egHPMI <- dRDataLoader(RData='org.Mm.egHPMI')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPMI terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.
- Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Mm.egHPMI <- dRDataLoader(RData='org.Mm.egHPMI')
names(org.Mm.egHPMI)
```

org.Mm.egHPPA	<i>Annotations of Mouse Entrez Genes (EG) by Human Phenotype Phenotypic Abnormality (HPPA).</i>
---------------	---

Description

An R object that contains associations between HPPA terms and Mouse Entrez Genes. This data is first prepared based on <http://purl.obolibrary.org/obo/hp.obo> and http://compbio.charite.de/hudson/job/hpo.annotations.monthly/lastStableBuild/artifact/annotation/ALL_SOURCES_ALL_FREQUENCIES_genes_to_phenotype.txt, which results in annotations of Human Entrez Genes. Then, these annotations are transferred to Mouse Entrez Genes based on <ftp://anonymous@ftp.ncbi.nih.gov/pub/HomoloGene/build67/homologene.data>.

Usage

```
org.Mm.egHPPA <- dRDataLoader(RData='org.Mm.egHPPA')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. HPPA terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Robinson et al. (2012) The Human Phenotype Ontology: a tool for annotating and analyzing human hereditary disease. *Am J Hum Genet*, 83:610-615.
 Sayers et al. (2011) Database resources of the National Center for Biotechnology Information. *Nucleic Acids Res*, 39:D38-51.

Examples

```
org.Mm.egHPPA <- dRDataLoader(RData='org.Mm.egHPPA')
names(org.Mm.egHPPA)
```

org.Mm.egMP	<i>Annotations of Mouse Entrez Genes (EG) by Mammalian Phenotype (MP).</i>
-------------	--

Description

An R object that contains associations between Mammalian Phenotype terms and Mouse Entrez Genes. This data is prepared based on ftp://ftp.informatics.jax.org/pub/reports/MPheno_OBO.ontology and ftp://ftp.informatics.jax.org/pub/reports/MGI_PhenoGenoMP.rpt.

Usage

```
org.Mm.egMP <- dRDataLoader(RData='org.Mm.egMP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. MP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Smith et al. (2009) The Mammalian Phenotype Ontology: enabling robust annotation and comparative analysis. *Wiley Interdiscip Rev Syst Biol Med*, 1:390-399.

Examples

```
org.Mm.egMP <- dRDataLoader(RData='org.Mm.egMP')
names(org.Mm.egMP)
```

org.Mm.egPS

Annotations of Mouse Entrez Genes (EG) by phylostratific age (PS).

Description

An R object that contains phylostratific age information for Mouse Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Mouse Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the mouse, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Mm.egPS <- dRDataLoader(RData='org.Mm.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL

is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.

- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Mm.egPS <- dRDataLoader(RData='org.Mm.egPS')
names(org.Mm.egPS)
```

org.Mm.egSF	<i>Annotations of Mouse Entrez Genes (EG) by domain superfamilies (SF).</i>
-------------	---

Description

An R object that contains domain superfamily information for Mouse Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Mouse Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Mm.egSF <- dRDataLoader(RData='org.Mm.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Mm.egSF <- dRDataLoader(RData='org.Mm.egSF')
names(org.Mm.egSF)
```

org.Mm.string	<i>Mouse functional protein association network from STRING (version 10).</i>
---------------	---

Description

An igraph object that contains a functional protein association network in mouse. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Mm.string <- dRDataLoader(RData='org.Mm.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Mm.string <- dRDataLoader(RData='org.Mm.string')
org.Mm.string
```

org.Rn.eg	<i>Rat Entrez Genes (EG).</i>
-----------	-------------------------------

Description

An R object that contains Entrez Gene information for the rat. This data is prepared based on ftp://ftp.ncbi.nih.gov/gene/DATA/gene_info.gz.

Usage

```
org.Rn.eg <- dRDataLoader(RData='org.Rn.eg')
```

Value

an object of class "EG", a list with following components:

- `gene_info`: a matrix of `nGene X 7` containing gene information, where `nGene` is the number of Entrez Genes, and the 7 columns are "GeneID", "Symbol", "description", "chromosome", "map_location", "Synonyms" and "dbXrefs"

References

Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.

Examples

```
org.Rn.eg <- dRDataLoader(RData='org.Rn.eg')
names(org.Rn.eg)
org.Rn.eg$gene_info[1:5,]
```

org.Rn.egGOBP	<i>Annotations of Rat Entrez Genes (EG) by Gene Ontology Biological Process (GOBP).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Biological Process terms and Rat Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Rn.egGOBP <- dRDataLoader(RData='org.Rn.egGOBP')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOBP terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Rn.egGOBP <- dRDataLoader(RData='org.Rn.egGOBP')
names(org.Rn.egGOBP)
```

org.Rn.egGOCC	<i>Annotations of Rat Entrez Genes (EG) by Gene Ontology Cellular Component (GOCC).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Cellular Component terms and Rat Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Rn.egGOCC <- dRDataLoader(RData='org.Rn.egGOCC')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOCC terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Rn.egGOCC <- dRDataLoader(RData='org.Rn.egGOCC')
names(org.Rn.egGOCC)
```

org.Rn.egGOMF	<i>Annotations of Rat Entrez Genes (EG) by Gene Ontology Molecular Function (GOMF).</i>
---------------	---

Description

An R object that contains associations between Gene Ontology Molecular Function terms and Rat Entrez Genes. This data is prepared based on http://www.geneontology.org/ontology/obo_format_1_2/gene_ontology.1_2.obo and <ftp://ftp.ncbi.nih.gov/gene/DATA/gene2go.gz>.

Usage

```
org.Rn.egGOMF <- dRDataLoader(RData='org.Rn.egGOMF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. GOMF terms), and the 4 columns are "setID" (i.e. "Term ID"), "name" (i.e. "Term Name"), "namespace" and "distance"
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Maglott et al. (2011) Entrez Gene: gene-centered information at NCBI. *Nucleic Acids Res*, 39:D52-57.
- Ashburner et al. (2000) Gene ontology: tool for the unification of biology. *Nat Genet*, 25:25-29.

Examples

```
org.Rn.egGOMF <- dRDataLoader(RData='org.Rn.egGOMF')
names(org.Rn.egGOMF)
```

Description

An R object that contains phylostratific age information for Rat Entrez Genes. This data is prepared based on 1) SUPERFAMILY database which provides domain architecture assignments to all completely sequenced genomes including eukaryotic genomes; 2) ancestral domain architecture repertoires inferred by applying Dollo parsimony to eukaryotic part of species tree of life (sTOL), from which the most recent common ancestor of each domain architecture is determined. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, phylostratific age for a Rat Entrez gene is the first appearance of its domain architecture along the branch from the eukaryotic ancestor to the rat, and thus can be measured by: i) the most recent common ancestor, ii) how many steps it is away starting from the eukaryotic ancestor, and how far it is in the terms of the branch length from the eukaryotic ancestor.

Usage

```
org.Rn.egPS <- dRDataLoader(RData='org.Rn.egPS')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. phylogenetic placement along the branch starting from the eukaryotic ancestor). The 4 columns are "setID" (i.e. "phylogenetic placement ID"), "name" (i.e. name for that placement in the form of "TaxonID:Name"), "namespace" (i.e. Rank for that placement) and "distance" (i.e. the branch length from the eukaryotic ancestor). Notably, since the sTOL is bifurcating with exactly two descendants (unlike the multifurcating nature of the NCBI taxonomy), an internal node in sTOL is either mapped onto a unique taxonomic identifier or left empty (assumedly a hypothetical unknown ancestor). In the latter case, hypothetical unknown ancestor is filled with the information in its nearest descendant with known taxonomic information.
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

- Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
- Fang et al. (2013) A daily-updated tree of (sequenced) life as a reference for genome research. *Scientific reports*, 3:2015.

Examples

```
org.Rn.egPS <- dRDataLoader(RData='org.Rn.egPS')
names(org.Rn.egPS)
```

 org.Rn.egSF

Annotations of Rat Entrez Genes (EG) by domain superfamilies (SF).

Description

An R object that contains domain superfamily information for Rat Entrez Genes. This data is prepared based on SUPERFAMILY database, which provides SCOP domain architecture assignments to all completely sequenced genomes including eukaryotic genomes. The domain architecture for an Entrez gene is the protein product with the longest length of amino acids. Thus, domain superfamily information for Rat Entrez gene is a list of domain superfamilies (excluding unknown gap) appearing in its domain architecture.

Usage

```
org.Rn.egSF <- dRDataLoader(RData='org.Rn.egSF')
```

Value

an object of class "GS", a list with following components:

- `set_info`: a matrix of nSet X 4 containing gene set information, where nSet is the number of gene sets (i.e. SCOP domain superfamilies). The 4 columns are "setID" (i.e. "SCOP domain identifier"), "name" (i.e. "SCOP domain description"), "namespace" (i.e. "SCOP domain level") and "distance" (i.e. "SCOP domain classification").
- `gs`: a list of gene sets, each storing gene members thereof. Always, gene sets are identified by "setID" and gene members identified by "Entrez ID"

References

Morais et al. (2011) SUPERFAMILY 1.75 including a domain-centric gene ontology method. *Nucleic Acids Res*, 39(Database issue):D427-34.
 Andreeva et al. (2008) Data growth and its impact on the SCOP database: new developments. *Nucleic Acids Res*, 36(Database issue):D419-425

Examples

```
org.Rn.egSF <- dRDataLoader(RData='org.Rn.egSF')
names(org.Rn.egSF)
```

 org.Rn.string

Rat functional protein association network from STRING (version 10).

Description

An igraph object that contains a functional protein association network in rat. The network is extracted from the STRING database (version 10). Only those associations with medium confidence (score \geq 0.4) are retained.

Usage

```
org.Rn.string <- dRDataLoader(RData='org.Rn.string')
```

Value

an object of class "igraph" (see <http://igraph.org/r/doc/aaa-igraph-package.html>). It has attributes for both vertices and edges. Below are attributes for the vertices:

- name: unique id for the vertices
- seqid: protein seqid for the vertices
- geneid: Entrez geneid (if any) for the vertices
- symbol: gene symbol (if any) for the vertices
- description: gene description (if any) for the vertices

Below are attributes for the edges:

- neighborhood_score: predictive score based on neighborhood data
- fusion_score: predictive score based on fusion data
- cooccurrence_score: predictive score based on cooccurrence data
- coexpression_score: predictive score based on coexpression
- experimental_score: predictive score based on experimental data
- database_score: predictive score based on database
- textmining_score: predictive score based on text mining
- combined_score: combined score from all above predictive scores

References

Szklarczyk et al. (2015) STRING v10: protein-protein interaction networks, integrated over the tree of life. *Nucleic Acids Res*, 43:D447-52.

Examples

```
org.Rn.string <- dRDataLoader(RData='org.Rn.string')
org.Rn.string
```

RegulomeDB_SNPs	<i>RegulomeDB SNPs restricted to GWAS SNPs and their LD SNPs (hg19)</i>
-----------------	---

Description

An R object that contains RegulomeDB SNPs (together with genomic locations; hg19) but are restricted to those in GWAS Catalogs (GWAS SNPs) and their LD SNPs based on the phase 3 1000 Genomics Project data.

Usage

```
RegulomeDB_SNPs <- dRDataLoader(RData.customised='RegulomeDB_SNPs')
```

Value

an object of class "GRanges".

Examples

```

RegulomeDB_SNPs <- dRDataLoader(RData.customised='RegulomeDB_SNPs')
RegulomeDB_SNPs
# the first 5 rows of metadata
mcols(RegulomeDB_SNPs)[1:5,]

```

TCGA_mutations	<i>TCGA mutational profiles across 12 major cancer types from Kandoth et al. (2013)</i>
----------------	---

Description

This dataset is available from TCGA, containing somatic mutational profiles for 3096 cancer samples with survival data. These cancer samples belong to one of 12 major cancer types, including breast adenocarcinoma (BRCA), lung adenocarcinoma (LUAD), lung squamous cell carcinoma (LUSC), uterine corpus endometrial carcinoma (UCEC), glioblastoma multiforme (GBM), head and neck squamous cell carcinoma (HNSC), colon and rectal carcinoma (COAD/READ), bladder urothelial carcinoma (BLCA), kidney renal clear cell carcinoma (KIRC), ovarian serous carcinoma (OV) and acute myeloid leukaemia (LAML). For each patient sample, somatic mutations are represented as a profile of states on genes, where non-zero entry indicates a gene for which how many mutations have occurred in the tumor relative to germ line. The dataset is provided as an 'ExpressionSet' object.

Usage

```
data(TCGA_mutations)
```

Value

an object of class "ExpressionSet". It has slots for "assayData", "phenoData", and "featureData":

- assayData: a matrix of 19171 genes X 3096 samples
- phenoData: variables describing sample phenotypes (i.e. columns in assayData), including clinical/survival information about samples: "time" (i.e. survival time in days), "status" (i.e., survival status: 0=alive; 1=dead), "Age" (the patient age in years), "Gender" (the patient gender: male/female), "TCGA_tumor_type", "Tumor_stage", "Tumor_grade"
- featureData: variables describing features (i.e. rows in assayData), including information about features/genes: "EntrezID" for gene EntrezID, "Symbol" for gene symbol, "Desc" for gene description, "Synonyms" for gene symbol alias

References

Kandoth et al. (2013). Mutational landscape and significance across 12 major cancer types. *Nature*, 502(7471):333-9.

Examples

```
#TCGA_mutations <- dRDataLoader(RData='TCGA_mutations')
data(TCGA_mutations)
TCGA_mutations
library(Biobase)
# extract information about the first 5 samples
pData(TCGA_mutations)[1:5,]
# extract information about the first 5 features
fData(TCGA_mutations)[1:5,]
# number of samples for each cancer type
table(pData(TCGA_mutations)$TCGA_tumor_type)
```

UCSC_genes

UCSC known canonical genes (hg19)

Description

An R object that contains UCSC known canonical genes (together with genomic locations) based on human genome assembly hg19.

Usage

```
UCSC_genes <- dRDataLoader(RData.customised='UCSC_genes')
```

Value

an object of class "GRanges".

Examples

```
UCSC_genes <- dRDataLoader(RData.customised='UCSC_genes')
UCSC_genes
# the first 5 rows of metadata
mcols(UCSC_genes)[1:5,]
```

visBoxplotAdv

Function to visualise a data frame using advanced boxplot

Description

visBoxplotAdv is supposed to visualise a data frame using advanced boxplot. In addition to boxplot, a scatter plot is also drawn with various methods to avoid co-incident points so that each point is visible (with fine-controlling the color and plotting character). Also, these points can be pies or thermometers, which allows an additional proportion data to be visualised as well.

Usage

```
visBoxplotAdv(formula, data, orientation = c("vertical", "horizontal"),
method = c("center", "hex", "square", "swarm"), corral = c("none",
" gutter", "wrap", "random", "omit"), corralWidth, cex = 1, spacing = 1,
breaks = NULL, labels, at = NULL, add = FALSE, log = FALSE,
xlim = NULL, ylim = NULL, xlab = NULL, ylab = NULL,
pch = c("circles", "thermometers", "pies")[1], col =
graphics::par("col"),
bg = NA, pwpch = NULL, pwcol = NULL, pwbg = NULL, pwpie = NULL,
do.plot = TRUE, do.boxplot = TRUE, boxplot.notch = FALSE,
boxplot.border = "#888888C0", boxplot.col = "transparent", ...)
```

Arguments

formula	a formula, such as 'y ~ grp', where 'y' is a numeric vector of data values to be split into groups according to the grouping variable 'grp' (usually a factor)
data	a data.frame (or list) from which the variables in 'formula' should be taken.
orientation	the orientation. It can be one of "vertical" for the vertical orientation, "horizontal" for the horizontal orientation
method	the method for arranging the points. It can be one of "swarm" for arranging points in increasing order (if a point would overlap an existing point, it is shifted sideways (along the group axis) by a minimal amount sufficient to avoid overlap), "center" for first discretizing the values along the data axis (in order to create more efficient packing) and then using a square grid to produce a symmetric swarm, "hex" for first discretization and then arranging points in a hexagonal grid, and "square" for first discretization and then arranging points in a square grid
corral	the method to adjust points that would be placed outside their own group region. It can be one of "none" for not adjusting runaway points, "gutter" for collecting runaway points along the boundary between groups, "wrap" for wrapping runaway points to produce periodic boundaries, "random" for placing runaway points randomly in the region, and "omit" for omitting runaway points
corralWidth	the width of the "corral" in user coordinates
cex	size of points relative to the default. This must be a single value
spacing	relative spacing between points
breaks	breakpoints (optional). If NULL, breakpoints are chosen automatically
labels	labels for each group. Recycled if necessary. By default, these are inferred from the data
at	numeric vector giving the locations where the swarms should be drawn; defaults to '1:n' where n is the number of groups
add	whether to add to an existing plot
log	whether to use a logarithmic scale on the data axis
xlim	limits for x-axis
ylim	limits for y-axis
xlab	labels for x-axis
ylab	labels for y-axis

pch	plotting characters, specified by group and recycled if necessary. In addition to the conventional pch values, it can also be "circles", "thermometers", or "pies". For "pies" (or "thermometers"), users can also specify the proportional values (see below "pwpie") to visualise another information in the pie (or thermometer) chart
col	plotting colors, specified by group and recycled if necessary
bg	plotting background, specified by group and recycled if necessary
pwpch	point-wise version of pch
pwcol	point-wise version of col
pwbg	point-wise version of bg
pwpie	point-wise proportion used when drawing pies or thermometers
do.plot	whether to draw main plot
do.boxplot	whether to draw boxplot. It only works when the main plot is drawn
boxplot.notch	whether to draw a notch in the boxplot. If the notches of two plots do not overlap this is 'strong evidence' that the two medians differ
boxplot.border	the color for the outlines of the boxplots
boxplot.col	the color for the bodies of the boxplots
...	additional graphic parameters for the plot

Value

A data frame with plotting information. It has the same row names as the input data

Note

none

See Also

[visBoxplotAdv](#)

Examples

```
data(TCGA_mutations)
pd <- Biobase::pData(TCGA_mutations)
# only tumor types "LAML" or "BLCA"
data <- pd[pd$TCGA_tumor_type=="LAML" | pd$TCGA_tumor_type=="BLCA",]
labels <- levels(as.factor(data$TCGA_tumor_type))
# colors for gender
pwcol <- as.numeric((data$Gender))
# pie for relative age
pwpie <- data$Age/(max(data$Age))
out <- visBoxplotAdv(formula=time ~ TCGA_tumor_type, data=data,
pch="pies", pwcol=pwcol, pwpie=pwpie)
legend("topright", legend=levels(data$Gender), box.col="transparent",
pch=19, col=unique(pwcol))
```

visDAG	<i>Function to visualise a direct acyclic graph (DAG) with node colorings according to a named input data vector (if provided)</i>
--------	--

Description

visDAG is supposed to visualise a direct acyclic graph (DAG) with node colorings according to a named input data vector (if provided)

Usage

```
visDAG(g, data = NULL, height = 7, width = 7, margin = rep(0.1, 4),
  colormap = c("yr", "bwr", "jet", "gbr", "wyr", "br", "rainbow", "wb",
  "lightyellow-orange"), ncolors = 40, zlim = NULL, colorbar = T,
  colorbar.fraction = 0.1, newpage = T,
  layout.orientation = c("left_right", "top_bottom", "bottom_top",
  "right_left"), node.info = c("none", "term_id", "term_name", "both",
  "full_term_name"), numChar = 15, graph.node.attrs = NULL,
  graph.edge.attrs = NULL, node.attrs = NULL)
```

Arguments

g	an object of class "igraph"
data	a named input data vector used to color-code vertices/nodes. The input data vector must have names, and these names should include all node names of input graph, i.e. $V(g)$name$, since there is a mapping operation. The way of how to color-code is to map values in the data onto the whole colormap (see the next arguments: colormap, ncolors, zlim and colorbar)
height	a numeric value specifying the height of device
width	a numeric value specifying the width of device
margin	margins as units of length 4 or 1
colormap	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "lightyellow-orange" (by default), "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names
ncolors	the number of colors specified over the colormap
zlim	the minimum and maximum z/data values for which colors should be plotted, defaulting to the range of the finite values of z. Each of the given colors will be used to color an equispaced interval of this range. The midpoints of the intervals cover the range, so that values just outside the range will be plotted
colorbar	logical to indicate whether to append a colorbar. If data is null, it always sets to false
colorbar.fraction	the relative fraction of colorbar block against the device size

<code>newpage</code>	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
<code>layout.orientation</code>	the orientation of the DAG layout. It can be one of "left_right" for the left-right layout (viewed from the DAG root point), "top_bottom" for the top-bottom layout, "bottom_top" for the bottom-top layout, and "right_left" for the right-left layout
<code>node.info</code>	tells the ontology term information used to label nodes. It can be one of "none" for no node labeling, "term_id" for using Term ID, "term_name" for using Term Name (the first 15 characters), "both" for using both of Term ID and Name (the first 15 characters), and "full_term_name" for using the full Term Name
<code>numChar</code>	a positive integer specifying wrap width of node labelling
<code>graph.node.attrs</code>	a list of global node attributes. These node attributes will be changed globally. See 'Note' below for details on the attributes
<code>graph.edge.attrs</code>	a list of global edge attributes. These edge attributes will be changed globally. See 'Note' below for details on the attributes
<code>node.attrs</code>	a list of local edge attributes. These node attributes will be changed locally; as such, for each attribute, the input value must be a named vector (i.e. using Term ID as names). See 'Note' below for details on the attributes

Value

An object of class 'Ragraph'

Note

A list of global node attributes used in "graph.node.attrs":

- "shape": the shape of the node: "circle", "rectangle", "rect", "box" and "ellipse"
- "fixedsize": the logical to use only width and height attributes. By default, it sets to true for not expanding for the width of the label
- "fillcolor": the background color of the node
- "color": the color for the node, corresponding to the outside edge of the node
- "fontcolor": the color for the node text/labelings
- "fontsize": the font size for the node text/labelings
- "height": the height (in inches) of the node: 0.5 by default
- "width": the width (in inches) of the node: 0.75 by default
- "style": the line style for the node: "solid", "dashed", "dotted", "invis" and "bold"

A list of global edge attributes used in "graph.edge.attrs":

- "color": the color of the edge: gray by default
- "weight": the weight of the edge: 1 by default
- "style": the line style for the edge: "solid", "dashed", "dotted", "invis" and "bold"

A list of local node attributes used in "node.attrs" (only those named Term IDs will be changed locally!):

- "label": a named vector specifying the node text/labelings
- "shape": a named vector specifying the shape of the node: "circle", "rectangle", "rect", "box" and "ellipse"
- "fixedsize": a named vector specifying whether it sets to true for not expanding for the width of the label
- "fillcolor": a named vector specifying the background color of the node
- "color": a named vector specifying the color for the node, corresponding to the outside edge of the node
- "fontcolor": a named vector specifying the color for the node text/labelings
- "fontsize": a named vector specifying the font size for the node text/labelings
- "height": a named vector specifying the height (in inches) of the node: 0.5 by default
- "width": a named vector specifying the width (in inches) of the node: 0.75 by default
- "style": a named vector specifying the line style for the node: "solid", "dashed", "dotted", "invis" and "bold"

See Also

[dDAGreverse](#), [dDAGroot](#), [dDAGinduce](#), [dDAGlevel](#)

Examples

```
# 1) load HPPA as igraph object
ig.HPPA <- dRDataLoader(RData='ig.HPPA')
g <- ig.HPPA

# 2) randomly select vertices as the query nodes
# the more common, the query nodes can be term id
nodes_query <- V(g)[sample(V(g),5)]$name

# 3) obtain the induced subgraph based on all possible paths
subg <- dDAGinduce(g, nodes_query, path.mode="all_paths")

# 4) just visualise the induced subgraph
visDAG(g=subg, node.info="both")

# 5) color-code nodes/terms according to its level
data <- dDAGlevel(subg)
visDAG(g=subg, data=data, node.info="both")
# 5a) globally change the node and edge attributes
visDAG(g=subg, data=data, layout.orientation="top_bottom",
node.info="both",
graph.node.attrs=list(fixedsize=FALSE,shape="box",color="transparent"),
graph.edge.attrs=list(color="black"))
# 5b) locally highlight the root by changing its shape into "box"
root <- dDAGroot(subg)
root.shape <- "box"
names(root.shape) <- V(subg)[root]$name
visDAG(g=subg, data=data, node.info="both",
node.attrs=list(shape=root.shape))
# 5c) further locally remove the root labelling
root.label <- ""
names(root.label) <- V(subg)[root]$name
visDAG(g=subg, data=data, node.info="both",
node.attrs=list(shape=root.shape,label=root.label))
```

visGSEA	<i>Function to visualise running enrichment score for a given sample and a gene set</i>
---------	---

Description

visGSEA is supposed to visualise running enrichment score for a given sample and a gene set. To help understand the underlying running enrichment score, the input gene scores are also displayed. Positions for members in the given gene set are color-coded in both displays (red line for the positive gene scores, and green line for the negative).

Usage

```
visGSEA(eTerm, which_sample = 1, which_term = "GO:0006281", plot = T,  
orientation = c("vertical", "horizontal"), hit.linewidth = 0.5,  
newpage = T)
```

Arguments

eTerm	an object of class "eTerm"
which_sample	which sample will be used. It can be index or sample names
which_term	which term will be used. It can be index or term ID or term names
plot	logical to indicate whether to plot
orientation	the orientation of the plots. It can be either "vertical" (default) or "horizontal"
hit.linewidth	the line width for the hits (ie genes in the gene set)
newpage	logical to indicate whether to open a new page. By default, it sets to true for opening a new page

Value

leading genes (being sorted)

Note

none

See Also

[dGSEA](#), [dGSEAvuew](#)

Examples

```
#visGSEA(eTerm, which_sample=1, which_term=1)
```

visNet

*Function to visualise a graph object of class "igraph" or "graphNEL"***Description**

visNet is supposed to visualise a graph object of class "igraph" or "graphNEL". It also allows the color-coding of vertices by providing the input pattern.

Usage

```
visNet(g, pattern = NULL, colormap = c("bwr", "jet", "gbr", "wyr",
"br",
"yr", "rainbow", "wb"), ncolors = 40, zlim = NULL, colorbar = T,
newpage = T, glayout = layout.fruchterman.reingold,
vertex.frame.color = NA, vertex.size = NULL, vertex.color = NULL,
vertex.shape = NULL, vertex.label = NULL, vertex.label.cex = NULL,
vertex.label.dist = NULL, vertex.label.color = "black", ...)
```

Arguments

<code>g</code>	an object of class "igraph" or "graphNEL"
<code>pattern</code>	a numeric vector used to color-code vertices/nodes. Notably, if the input vector contains names, then these names should include all node names of input graph, i.e. $V(g)$name$, since there is a mapping operation. After mapping, the length of the pattern vector should be the same as the number of nodes of input graph; otherwise, this input pattern will be ignored. The way of how to color-code is to map values in the pattern onto the whole colormap (see the next arguments: colormap, ncolors, zlim and colorbar)
<code>colormap</code>	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names
<code>ncolors</code>	the number of colors specified over the colormap
<code>zlim</code>	the minimum and maximum z /pattern values for which colors should be plotted, defaulting to the range of the finite values of z . Each of the given colors will be used to color an equispaced interval of this range. The midpoints of the intervals cover the range, so that values just outside the range will be plotted
<code>colorbar</code>	logical to indicate whether to append a colorbar. If pattern is null, it always sets to false
<code>newpage</code>	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
<code>glayout</code>	either a function or a numeric matrix configuring how the vertices will be placed on the plot. If layout is a function, this function will be called with the graph as the single parameter to determine the actual coordinates. This function can

be one of "layout.auto", "layout.random", "layout.circle", "layout.sphere", "layout.fruchterman.reingold", "layout.kamada.kawai", "layout.spring", "layout.reingold.tilford", "layout.fruchterman.reingold.grid", "layout.lgl", "layout.graphopt", "layout.svd" and "layout.norm". A full explanation of these layouts can be found in http://igraph.org/r/doc/layout_nicely.html

<code>vertex.frame.color</code>	the color of the frame of the vertices. If it is NA, then there is no frame
<code>vertex.size</code>	the size of each vertex. If it is a vector, each vertex may differ in size
<code>vertex.color</code>	the fill color of the vertices. If it is NA, then there is no fill color. If the pattern is given, this setup will be ignored
<code>vertex.shape</code>	the shape of each vertex. It can be one of "circle", "square", "csquare", "rectangle", "crectangle", "vrectangle", "pie" (http://igraph.org/r/doc/vertex.shape.pie.html), "sphere", and "none". If it sets to NULL, these vertices with negative will be "csquare" and the rest "circle".
<code>vertex.label</code>	the label of the vertices. If it is NA, then there is no label. The default vertex labels are the name attribute of the nodes
<code>vertex.label.cex</code>	the font size of vertex labels.
<code>vertex.label.dist</code>	the distance of the label from the center of the vertex. If it is 0 then the label is centered on the vertex. If it is 1 then the label is displayed beside the vertex.
<code>vertex.label.color</code>	the color of vertex labels.
...	additional graphic parameters. See http://igraph.org/r/doc/plot.common.html for the complete list.

Value

invisible

Note

none

See Also

[dNetFind](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 3) visualise the subg with vertices being color-coded by the pattern
pattern <- runif(vcount(subg))
names(pattern) <- V(subg)$name
visNet(g=subg, pattern=pattern, colormap="bwr", vertex.shape="sphere")
```

visNetAnimate	<i>Function to animate the same graph but with multiple graph node colorings according to input data matrix</i>
---------------	---

Description

visNetAnimate is supposed to animate the same graph but with multiple colorings according to input data matrix. The output can be a pdf file containing a list of frames/images, a mp4 video file or a gif file. To support video output file, the software 'ffmpeg' must be first installed (also put its path into the system PATH variable; see Note). To support gif output file, the software 'ImageMagick' must be first installed (also put its path into the system PATH variable; see Note).

Usage

```
visNetAnimate(g, data, filename = "visNetAnimate", filetype = c("pdf",
"mp4", "gif"), image.type = c("jpg", "png"), num.frame = ncol(data),
sec_per_frame = 1, height.device = 7, margin = rep(0.1, 4),
border.color = "#EEEEEE", colormap = c("bwr", "jet", "gbr", "wyr",
"br",
"yr", "rainbow", "wb"), ncolors = 40, zlim = NULL, colorbar = T,
colorbar.fraction = 0.25, glayout = layout.fruchterman.reingold,
glayout.dynamics = F, mtext.side = 3, mtext.adj = 0, mtext.cex = 1,
mtext.font = 2, mtext.col = "black", ...)
```

Arguments

g	an object of class "igraph" or "graphNEL"
data	an input data matrix used to color-code vertices/nodes. One column corresponds to one graph node coloring. The input matrix must have row names, and these names should include all node names of input graph, i.e. $V(g)\$name$, since there is a mapping operation. After mapping, the length of the pattern vector should be the same as the number of nodes of input graph. The way of how to color-code is to map values in the pattern onto the whole colormap (see the next arguments: colormap, ncolors, zlim and colorbar)
filename	the without-extension part of the name of the output file. By default, it is 'vis-NetAnimate'
filetype	the type of the output file, i.e. the extension of the output file name. It can be one of either 'pdf' for the pdf file, 'mp4' for the mp4 video file, 'gif' for the gif file
image.type	the type of the image files temporarily generated. It can be one of either 'jpg' or 'png'. These temporary image files are used for producing mp4/gif output file. The reason doing so is to accommodate that sometimes only one of image types is supported so that you can choose the right one
num.frame	a numeric value specifying the number of frames/images. By default, it sets to the number of columns in the input data matrix
sec_per_frame	a numeric value specifying how long (seconds) it takes to stream a frame/image. This argument only works when producing mp4 video or gif file.
height.device	a numeric value specifying the height (or width) of device/frame/image.
margin	margins as units of length 4 or 1

<code>border.color</code>	the border color of each figure
<code>colormap</code>	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names
<code>ncolors</code>	the number of colors specified over the colormap
<code>zlim</code>	the minimum and maximum <code>z/pattern</code> values for which colors should be plotted, defaulting to the range of the finite values of <code>z</code> . Each of the given colors will be used to color an equispaced interval of this range. The midpoints of the intervals cover the range, so that values just outside the range will be plotted
<code>colorbar</code>	logical to indicate whether to append a colorbar. If <code>pattern</code> is null, it always sets to false
<code>colorbar.fraction</code>	the relative fraction of colorbar block against the figure block
<code>layout</code>	either a function or a numeric matrix configuring how the vertices will be placed on the plot. If <code>layout</code> is a function, this function will be called with the <code>graph</code> as the single parameter to determine the actual coordinates. This function can be one of "layout.auto", "layout.random", "layout.circle", "layout.sphere", "layout.fruchterman.reingold", "layout.kamada.kawai", "layout.spring", "layout.reingold.tilford", "layout.fruchterman.reingold.grid", "layout.lgl", "layout.graphopt", "layout.svd" and "layout.norm". A full explanation of these layouts can be found in http://igraph.org/r/doc/layout_nicely.html
<code>layout.dynamics</code>	logical to indicate whether graph layout should be dynamic. By default, it always sets to false. If YES, the Fruchterman-Reingold layout algorithm http://igraph.org/r/doc/layout_with_fr.html will be used to stimulate the dynamic layout
<code>mtext.side</code>	on which side of the <code>mtext</code> plot (1=bottom, 2=left, 3=top, 4=right)
<code>mtext.adj</code>	the adjustment for <code>mtext</code> alignment (0 for left or bottom alignment, 1 for right or top alignment)
<code>mtext.cex</code>	the font size of <code>mtext</code> labels
<code>mtext.font</code>	the font weight of <code>mtext</code> labels
<code>mtext.col</code>	the color of <code>mtext</code> labels
<code>...</code>	additional graphic parameters. See http://igraph.org/r/doc/plot.common.html for the complete list.

Value

If specifying the output file name (see argument 'filename' above), the output file is either 'filename.pdf' or 'filename.mp4' or 'filename.gif' in the current working directory. If no output file name specified, by default the output file is either 'visNetAnimate.pdf' or 'visNetAnimate.mp4' or 'visNetAnimate.gif'

Note

When producing mp4 video, this function requires the installation of the software 'ffmpeg' at <https://www.ffmpeg.org>. Shell command lines for ffmpeg installation in Terminal (for both Linux and Mac) are:

- 1) `wget -O ffmpeg.tar.gz http://www.ffmpeg.org/releases/ffmpeg-2.7.1.tar.gz`
- 2) `mkdir ~/ffmpeg | tar xvfz ffmpeg.tar.gz -C ~/ffmpeg --strip-components=1`
- 3) `cd ffmpeg`
- 4a) # Assuming you want installation with a ROOT (sudo) privilege:
`./configure --disable-yasm`
- 4b) # Assuming you want local installation without ROOT (sudo) privilege:
`./configure --disable-yasm --prefix=$HOME/ffmpeg`
- 5) `make`
- 6) `make install`
- 7) # add the system PATH variable to your ~/.bash_profile file if you follow 4b) route:
`export PATH=$HOME/ffmpeg:$PATH`
- 8) # make sure ffmpeg has been installed successfully:
`ffmpeg -h`

When producing gif file, this function requires the installation of the software 'ImageMagick' at <http://www.imagemagick.org>. Shell command lines for ImageMagick installation in Terminal are:

- 1) `wget http://www.imagemagick.org/download/ImageMagick.tar.gz`
- 2) `mkdir ~/ImageMagick | tar xvzf ImageMagick.tar.gz -C ~/ImageMagick --strip-components=1`
- 3) `cd ImageMagick`
- 4) `./configure --prefix=$HOME/ImageMagick`
- 5) `make`
- 6) `make install`
- 7) # add the system PATH variable to your ~/.bash_profile file.
For Linux:
`export MAGICK_HOME=$HOME/ImageMagick`
`export PATH=$MAGICK_HOME/bin:$PATH`
`export LD_LIBRARY_PATH=${LD_LIBRARY_PATH:+$LD_LIBRARY_PATH:}$MAGICK_HOME/lib`
For Mac:
`export MAGICK_HOME=$HOME/ImageMagick`
`export PATH=$MAGICK_HOME/bin:$PATH`
`export DYLD_LIBRARY_PATH=$MAGICK_HOME/lib/`
- 8a) # check configuration:
`convert -list configure`
- 8b) # check image format supported:
`identify -list format`
- Tips:
Prior to 4), please make sure libjpeg and libpng are installed. If NOT, for Mac try this:
`brew install libjpeg libpng`
To check whether ImageMagick does work, please get additional information from:
`identify -list format`
`convert -list configure`
On details, please refer to <http://www.imagemagick.org/script/advanced-unix-installation.php>

See Also[visNetMul](#)**Examples**

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 3) visualise the module with vertices being color-coded by scores
nnodes <- vcount(subg)
nsamples <- 10
data <- matrix(runif(nnodes*nsamples), nrow=nnodes, ncol=nsamples)
rownames(data) <- V(subg)$name
# output as a <a href="visNetAnimate.pdf">pdf</a> file
visNetAnimate(g=subg, data=data, filetype="pdf")
# output as a <a href="visNetAnimate.mp4">mp4</a> file but with dynamic layout
visNetAnimate(g=subg, data=data, filetype="mp4", glayout.dynamics=TRUE)
# output as a <a href="visNetAnimate.gif">gif</a> file but with dynamic layout
visNetAnimate(g=subg, data=data, filetype="gif", glayout.dynamics=TRUE)
```

visNetArc

*Function to visualise an igraph object via arc diagram***Description**

visNetArc is supposed to visualise a graph object of class "igraph" via arc diagram in one-dimensional layout. More precisely, it displays vertices (nodes) along an axis, with edges linked by arcs. With proper ordering of vertices (e.g. according to communities and degrees), arc diagram is able to identify clusters and bridges (as effective as two-dimensional layout). One advantage of using arc diagram is to allow for easy annotations along vertices.

Usage

```
visNetArc(g, orientation = c("vertical", "horizontal"), newpage = T,
ordering = NULL, labels = V(g)$name, vertex.label.color = "black",
vertex.label.cex = 1, vertex.color = "transparent",
vertex.frame.color = "black", vertex.size = log(degree(g)) + 0.1,
vertex.pch = 21, vertex.lwd = 1, edge.color = "grey", edge.width = 1,
edge.lty = 1, ...)
```

Arguments

g	an object of class "igraph"
orientation	the orientation of the plots. It can be either "vertical" (default) or "horizontal"
newpage	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
ordering	a numeric vector about the ordering of vertices. It is optional. It is highly recommend to order vertices according to communities and degrees

labels	the label of the vertices. The default vertex labels are the name attribute of the nodes
vertex.label.color	the color of vertex labels
vertex.label.cex	the font size of vertex labels
vertex.color	the fill color of the vertices. The default vertex colors are transparent
vertex.frame.color	the color of the frame of the vertices. The default vertex frame colors are black
vertex.size	the size of each vertex. By default, it is decided according to node degrees
vertex.pch	the shape of each vertex. Either an integer specifying a symbol or a single character to be used as the default in plotting points. See http://www.statmethods.net/advgraphs/parameters.html
vertex.lwd	line width for the vertices (default 1)
edge.color	the color of the edges (default "grey")
edge.width	line width for the edges (default 1)
edge.lty	line type for the edges (default 1)
...	additional graphic parameters associated with 'mtext'

Value

invisible

Note

none

See Also[visNet](#)**Examples**

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/80)

# 2) produce the induced subgraph only based on the nodes in query
g <- dNetInduce(g, V(g), knn=0)

# 3) color nodes according to communities identified via a spin-glass model and simulated annealing
com <- spinglass.community(g, spins=4)
vgroups <- com$membership
palette.name <- visColormap(colormap="rainbow")
vcolors <- palette.name(length(com))[vgroups]

# 4) size nodes according to degrees
vdegrees <- igraph::degree(g)

# 5) sort nodes: first by communities and then degrees
tmp <- data.frame(ind=1:vcount(g), vgroups, vdegrees)
ordering <- tmp[order(vgroups,vdegrees),]$ind
```

```
# 6) visualise graph using 1-dimensional arc diagram
visNetArc(g, ordering=ordering, labels=V(g)$name,
vertex.label.color=vcolors,
vertex.color=vcolors, vertex.frame.color=vcolors,
vertex.size=log(vdegrees)+0.1)

# 7) as comparison, also visualise graph on 2-dimensional layout
visNet(g, colormap="bwr", layout=layout.kamada.kawai(g),
vertex.label=V(g)$name,
vertex.color=vcolors, vertex.frame.color=vcolors,
vertex.shape="sphere")
```

visNetCircle

Function to visualise an igraph object via circle diagram

Description

visNetCircle is supposed to visualise a graph object of class "igraph" via circle diagram. For better visualisation, ordering of vertices is determined according to communities and degrees.

Usage

```
visNetCircle(g, com, circles = c("single", "multiple"), newpage = T,
ordering = NULL, colormap = c("rainbow", "bwr", "jet", "gbr", "wyr",
"br",
"yr", "wb"), vertex.label = V(g)$name,
vertex.size = log(igraph::degree(g)) + 2, vertex.label.color = "black",
vertex.label.cex = 0.6, vertex.label.dist = 0.75,
vertex.shape = "sphere", edge.width = 1, edge.lty = 1,
edge.color.within = "grey", edge.color.crossing = "black",
mark.shape = 1, mark.expand = 10, ...)
```

Arguments

g	an object of class "igraph"
com	an object of class "communities" (see http://igraph.org/r/doc/communities.html)
circles	how circles are drawn in the plot. It can be either "single" for all communities being drawn in a single circle (by default) or "multiple" for communities being drawn in the different circles (i.e. one circle per community)
newpage	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
ordering	a numeric vector about the ordering of vertices. It is optional. It is highly recommend to order vertices according to communities and degrees
colormap	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names

<code>vertex.label</code>	the label of the vertices. The default vertex labels are the name attribute of the nodes
<code>vertex.size</code>	the size of each vertex. By default, it is decided according to node degrees
<code>vertex.label.color</code>	the color of vertex labels
<code>vertex.label.cex</code>	the font size of vertex labels
<code>vertex.label.dist</code>	the distance of the label from the center of the vertex. If it is 0 then the label is centered on the vertex. If it is 1 then the label is displayed beside the vertex.
<code>vertex.shape</code>	the shape of each vertex. It can be one of "circle", "square", "csquare", "rectangle", "crectangle", "vrectangle", "pie" (http://igraph.org/r/doc/vertex.shape.pie.html), "sphere", and "none". If it sets to NULL, these vertices with negative will be "csquare" and the rest "circle".
<code>edge.width</code>	line width for the edges (default 1)
<code>edge.lty</code>	line type for the edges (default 1)
<code>edge.color.within</code>	the color for edges within a community (default "grey")
<code>edge.color.crossing</code>	the color for edges between communities (default "black")
<code>mark.shape</code>	a numeric scalar or vector controlling the smoothness of the vertex group marking polygons. Its possible values are between -1 (fully polygons) and 1 (fully smoothness)
<code>mark.expand</code>	a numeric scalar or vector, the size of the border around the marked vertex groups
<code>...</code>	additional graphic parameters. See http://igraph.org/r/doc/plot.common.html for the complete list.

Value

invisible

Note

none

See Also[visNet](#)**Examples**

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/80)

# 2) produce the induced subgraph only based on the nodes in query
g <- dNetInduce(g, V(g), knn=0)

# 3) color nodes according to communities identified via a spin-glass model and simulated annealing
com <- spinglass.community(g, spins=4)
vgroups <- com$membership
```

```

palette.name <- visColormap(colormap="rainbow")
mcolors <- palette.name(length(com))
vcolors <- mcolors[vgroups]

# 4) size nodes according to degrees
vdegrees <- igraph::degree(g)

# 5) sort nodes: first by communities and then degrees
tmp<-data.frame(ind=1:vcount(g), vgroups, vdegrees)
ordering <- tmp[order(vgroups,vdegrees),]$ind

# 6) visualise graph using circle diagram
# 6a) drawn into a single circle
visNetCircle(g=g, colormap="bwr", com=com, ordering=ordering)

# 6b) drawn into multiple circles (one circle per community)
visNetCircle(g=g, colormap="bwr", com=com, circles="multiple",
ordering=ordering)

# 7) as comparison, also visualise graph on 2-dimensional layout
mark.groups <- communities(com)
mark.col <- visColoralpha(mcolors, alpha=0.2)
mark.border <- visColoralpha(mcolors, alpha=0.2)
edge.color <- c("grey", "black")[crossing(com,g)+1]
visNet(g, colormap="bwr", glayout=layout.fruchterman.reingold,
vertex.color=vcolors,
vertex.frame.color=vcolors, vertex.shape="sphere",
mark.groups=mark.groups, mark.col=mark.col,
mark.border=mark.border, mark.shape=1, mark.expand=10,
edge.color=edge.color)

```

visNetMul

Function to visualise the same graph but with multiple graph node colorings according to input data matrix

Description

visNetMul is supposed to visualise the same graph but with multiple colorings according to input data matrix

Usage

```

visNetMul(g, data, height = 7, margin = rep(0.1, 4),
border.color = "#EEEEEE", colormap = c("bwr", "jet", "gbr", "wyr",
"br",
"yr", "rainbow", "wb"), ncolors = 40, zlim = NULL, colorbar = T,
colorbar.fraction = 0.25, newpage = T,
glayout = layout.fruchterman.reingold, mtext.side = 3, mtext.adj = 0,
mtext.cex = 1, mtext.font = 2, mtext.col = "black", ...)

```

Arguments

g an object of class "igraph" or "graphNEL"

data	an input data matrix used to color-code vertices/nodes. One column corresponds to one graph node coloring. The input matrix must have row names, and these names should include all node names of input graph, i.e. $V(g)$ name, since there is a mapping operation. After mapping, the length of the pattern vector should be the same as the number of nodes of input graph. The way of how to color-code is to map values in the pattern onto the whole colormap (see the next arguments: colormap, ncolors, zlim and colorbar)
height	a numeric value specifying the height of device
margin	margins as units of length 4 or 1
border.color	the border color of each figure
colormap	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names
ncolors	the number of colors specified over the colormap
zlim	the minimum and maximum z/pattern values for which colors should be plotted, defaulting to the range of the finite values of z. Each of the given colors will be used to color an equispaced interval of this range. The midpoints of the intervals cover the range, so that values just outside the range will be plotted
colorbar	logical to indicate whether to append a colorbar. If pattern is null, it always sets to false
colorbar.fraction	the relative fraction of colorbar block against the figure block
newpage	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
glayout	either a function or a numeric matrix configuring how the vertices will be placed on the plot. If layout is a function, this function will be called with the graph as the single parameter to determine the actual coordinates. This function can be one of "layout.auto", "layout.random", "layout.circle", "layout.sphere", "layout.fruchterman.reingold", "layout.kamada.kawai", "layout.spring", "layout.reingold.tilford", "layout.fruchterman.reingold.grid", "layout.lgl", "layout.graphopt", "layout.svd" and "layout.norm". A full explanation of these layouts can be found in http://igraph.org/r/doc/layout_nicely.html
mtext.side	on which side of the mtext plot (1=bottom, 2=left, 3=top, 4=right)
mtext.adj	the adjustment for mtext alignment (0 for left or bottom alignment, 1 for right or top alignment)
mtext.cex	the font size of mtext labels
mtext.font	the font weight of mtext labels
mtext.col	the color of mtext labels
...	additional graphic parameters. See http://igraph.org/r/doc/plot.common.html for the complete list.

Value

invisible

Note

none

See Also

[visNet](#), [visNetAnimate](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/80)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 3) visualise the module with vertices being color-coded by scores
nnodes <- vcount(subg)
nsamples <- 10
data <- matrix(runif(nnodes*nsamples), nrow=nnodes, ncol=nsamples)
rownames(data) <- V(subg)$name
visNetMul(g=subg, colormap="bwr", data=data,
glayout=layout.fruchterman.reingold)
```

visNetReorder

Function to visualise the multiple graph colorings reorded within a sheet-shape rectangle grid

Description

visNetReorder is supposed to visualise the multiple graph colorings reorded within a sheet-shape rectangle grid

Usage

```
visNetReorder(g, data, sReorder, height = 7, margin = rep(0.1, 4),
border.color = "#EEEEEE", colormap = c("bwr", "jet", "gbr", "wyr",
"br",
"yr", "rainbow", "wb"), ncolors = 40, zlim = NULL, colorbar = T,
colorbar.fraction = 0.5, newpage = T,
glayout = layout.fruchterman.reingold, mtext.side = 3, mtext.adj = 0,
mtext.cex = 1, mtext.font = 2, mtext.col = "black", ...)
```

Arguments

g	an object of class "igraph" or "graphNEL"
data	an input data matrix used to color-code vertices/nodes. One column corresponds to one graph node coloring. The input matrix must have row names, and these names should include all node names of input graph, i.e. V(g)\$name, since there is a mapping operation. After mapping, the length of the pattern vector should be the same as the number of nodes of input graph. The way of how to color-code is to map values in the pattern onto the whole colormap (see the next arguments: colormap, ncolors, zlim and colorbar)

sReorder	an object of class "sReorder"
height	a numeric value specifying the height of device
margin	margins as units of length 4 or 1
border.color	the border color of each figure
colormap	short name for the colormap. It can be one of "jet" (jet colormap), "bwr" (blue-white-red colormap), "gbr" (green-black-red colormap), "wyr" (white-yellow-red colormap), "br" (black-red colormap), "yr" (yellow-red colormap), "wb" (white-black colormap), and "rainbow" (rainbow colormap, that is, red-yellow-green-cyan-blue-magenta). Alternatively, any hyphen-separated HTML color names, e.g. "blue-black-yellow", "royalblue-white-sandybrown", "darkgreen-white-darkviolet". A list of standard color names can be found in http://html-color-codes.info/color-names
ncolors	the number of colors specified over the colormap
zlim	the minimum and maximum z/pattern values for which colors should be plotted, defaulting to the range of the finite values of z. Each of the given colors will be used to color an equispaced interval of this range. The midpoints of the intervals cover the range, so that values just outside the range will be plotted
colorbar	logical to indicate whether to append a colorbar. If pattern is null, it always sets to false
colorbar.fraction	the relative fraction of colorbar block against the figure block
newpage	logical to indicate whether to open a new page. By default, it sets to true for opening a new page
glayout	either a function or a numeric matrix configuring how the vertices will be placed on the plot. If layout is a function, this function will be called with the graph as the single parameter to determine the actual coordinates. This function can be one of "layout.auto", "layout.random", "layout.circle", "layout.sphere", "layout.fruchterman.reingold", "layout.kamada.kawai", "layout.spring", "layout.reingold.tilford", "layout.fruchterman.reingold.grid", "layout.lgl", "layout.graphopt", "layout.svd" and "layout.norm". A full explanation of these layouts can be found in http://igraph.org/r/doc/layout_nicely.html
mtext.side	on which side of the mtext plot (1=bottom, 2=left, 3=top, 4=right)
mtext.adj	the adjustment for mtext alignment (0 for left or bottom alignment, 1 for right or top alignment)
mtext.cex	the font size of mtext labels
mtext.font	the font weight of mtext labels
mtext.col	the color of mtext labels
...	additional graphic parameters. See http://igraph.org/r/doc/plot.common.html for the complete list.

Value

invisible

Note

none

See Also

[visNet](#), [dNetReorder](#)

Examples

```
# 1) generate a random graph according to the ER model
g <- erdos.renyi.game(100, 1/100)

# 2) produce the induced subgraph only based on the nodes in query
subg <- dNetInduce(g, V(g), knn=0)

# 3) reorder the module with vertices being color-coded by input data
nnodes <- vcount(subg)
nsamples <- 10
data <- matrix(runif(nnodes*nsamples), nrow=nnodes, ncol=nsamples)
rownames(data) <- V(subg)$name
sReorder <- dNetReorder(g=subg, data, feature="node",
node.normalise="none")

# 4) visualise the module with vertices being color-coded by input data
visNetReorder(g=subg, colormap="bwr", data=data, sReorder)
```

Index

*Topic **datasets**

CLL, [5](#)
GWAS2EF, [56](#)
GWAS_LD, [56](#)
Hiratani_TableS1, [57](#)
ig.DO, [58](#)
ig.GOBP, [59](#)
ig.GOCC, [59](#)
ig.GOMF, [60](#)
ig.HPCM, [61](#)
ig.HPMA, [61](#)
ig.HPMI, [62](#)
ig.HPPA, [63](#)
ig.MP, [63](#)
IlluminaHumanHT, [64](#)
IlluminaOmniExpress, [65](#)
ImmunoBase, [65](#)
ImmunoBase_LD, [66](#)
JKscience_expression, [67](#)
JKscience_genotype, [68](#)
JKscience_TS2A, [69](#)
JKscience_TS2B, [69](#)
JKscience_TS3A, [70](#)
org.At.eg, [71](#)
org.At.egGOBP, [71](#)
org.At.egGOCC, [72](#)
org.At.egGOMF, [73](#)
org.At.egPS, [74](#)
org.At.egSF, [75](#)
org.At.string, [75](#)
org.Ce.eg, [76](#)
org.Ce.egGOBP, [77](#)
org.Ce.egGOCC, [78](#)
org.Ce.egGOMF, [78](#)
org.Ce.egPS, [79](#)
org.Ce.egSF, [80](#)
org.Ce.string, [81](#)
org.Da.eg, [82](#)
org.Da.egGOBP, [82](#)
org.Da.egGOCC, [83](#)
org.Da.egGOMF, [84](#)
org.Da.egPS, [85](#)
org.Da.egSF, [86](#)
org.Da.string, [86](#)
org.Dm.eg, [87](#)
org.Dm.egGOBP, [88](#)
org.Dm.egGOCC, [89](#)
org.Dm.egGOMF, [89](#)
org.Dm.egPS, [90](#)
org.Dm.egSF, [91](#)
org.Dm.string, [92](#)
org.Gg.eg, [93](#)
org.Gg.egGOBP, [93](#)
org.Gg.egGOCC, [94](#)
org.Gg.egGOMF, [95](#)
org.Gg.egPS, [96](#)
org.Gg.egSF, [97](#)
org.Gg.string, [97](#)
org.Hs.eg, [98](#)
org.Hs.egDGIdb, [99](#)
org.Hs.egDO, [100](#)
org.Hs.egGOBP, [100](#)
org.Hs.egGOCC, [101](#)
org.Hs.egGOMF, [102](#)
org.Hs.egHPCM, [103](#)
org.Hs.egHPMA, [103](#)
org.Hs.egHPMI, [104](#)
org.Hs.egHPPA, [105](#)
org.Hs.egMP, [105](#)
org.Hs.egMsigdbC1, [106](#)
org.Hs.egMsigdbC2BIOCARTA, [107](#)
org.Hs.egMsigdbC2CGP, [108](#)
org.Hs.egMsigdbC2CP, [108](#)
org.Hs.egMsigdbC2CPall, [109](#)
org.Hs.egMsigdbC2KEGG, [110](#)
org.Hs.egMsigdbC2REACTOME, [111](#)
org.Hs.egMsigdbC3MIR, [111](#)
org.Hs.egMsigdbC3TFT, [112](#)
org.Hs.egMsigdbC4CGN, [113](#)
org.Hs.egMsigdbC4CM, [114](#)
org.Hs.egMsigdbC5BP, [114](#)
org.Hs.egMsigdbC5CC, [115](#)
org.Hs.egMsigdbC5MF, [116](#)
org.Hs.egMsigdbC6, [116](#)
org.Hs.egMsigdbC7, [117](#)
org.Hs.egMsigdbH, [118](#)

- org.Hs.egPS, 118
 - org.Hs.egSF, 120
 - org.Hs.PCommons_DN, 120
 - org.Hs.PCommons_DN.source, 122
 - org.Hs.PCommons_UN, 123
 - org.Hs.string, 125
 - org.Mm.eg, 126
 - org.Mm.egDO, 126
 - org.Mm.egGOBP, 127
 - org.Mm.egGOCC, 128
 - org.Mm.egGOMF, 129
 - org.Mm.egHPCM, 129
 - org.Mm.egHPMA, 130
 - org.Mm.egHPMI, 131
 - org.Mm.egHPPA, 132
 - org.Mm.egMP, 132
 - org.Mm.egPS, 133
 - org.Mm.egSF, 134
 - org.Mm.string, 135
 - org.Rn.eg, 136
 - org.Rn.egGOBP, 137
 - org.Rn.egGOCC, 137
 - org.Rn.egGOMF, 138
 - org.Rn.egPS, 139
 - org.Rn.egSF, 140
 - org.Rn.string, 140
 - RegulomeDB_SNPs, 141
 - TCGA_mutations, 142
 - UCSC_genes, 143
- CLL, 5
- CpG (Hiratani_TableS1), 57
- dBUMfit, 6, 9, 41
- dBUMscore, 7, 8, 41
- dCheckParallel, 9, 16, 22, 49, 51, 54
- dCommSignif, 10, 11
- dContrast, 11
- dDAGancestor, 12, 22
- dDAGannotate, 13, 16
- dDAGgeneSim, 10, 15, 22
- dDAGinduce, 13, 14, 16, 17, 22, 148
- dDAGlevel, 14, 18, 148
- dDAGreverse, 19, 19, 148
- dDAGroot, 17, 19, 20, 20, 148
- dDAGtermSim, 10, 16, 21
- dDAGtip, 16, 22, 23
- dEnricher, 23, 27
- dEnricherView, 26, 27
- dFDRscore, 28, 41, 55
- dFunArgs, 29
- dGSEA, 30, 34, 35, 149
- dGSEAvIEW, 33, 33, 149
- dGSEAwrite, 33, 35
- dNetConfidence, 36
- dNetFind, 37, 38, 41, 151
- dNetInduce, 39, 39
- dNetPipeline, 28, 29, 40
- dNetReorder, 41, 163
- dPvalAggregate, 44, 45
- dRDataLoader, 45, 48
- dRWR, 10, 48, 51, 54
- dRWRcontact, 10, 49, 50, 54
- dRWRpipeline, 10, 49, 52
- dSVDsignif, 28, 54
- EX (Hiratani_TableS1), 57
- GWAS2EF, 56
- GWAS_LD, 56
- Hiratani_TableS1, 57
- ig.DO, 58
- ig.GOBP, 59
- ig.GOCC, 59
- ig.GOMF, 60
- ig.HPCM, 61
- ig.HPMA, 61
- ig.HPMI, 62
- ig.HPPA, 63
- ig.MP, 63
- IlluminaHumanHT, 64
- IlluminaOmniExpress, 65
- ImmunoBase, 65
- ImmunoBase_LD, 66
- JKscience_expression, 67, 68
- JKscience_genotype, 67, 68
- JKscience_TS2A, 69
- JKscience_TS2B, 69
- JKscience_TS3A, 70
- org.At.eg, 71
- org.At.egGOBP, 71
- org.At.egGOCC, 72
- org.At.egGOMF, 73
- org.At.egPS, 74
- org.At.egSF, 75
- org.At.string, 75
- org.Ce.eg, 76
- org.Ce.egGOBP, 77
- org.Ce.egGOCC, 78
- org.Ce.egGOMF, 78
- org.Ce.egPS, 79
- org.Ce.egSF, 80
- org.Ce.string, 81

- org.Da.eg, [82](#)
- org.Da.egGOBP, [82](#)
- org.Da.egGOCC, [83](#)
- org.Da.egGOMF, [84](#)
- org.Da.egPS, [85](#)
- org.Da.egSF, [86](#)
- org.Da.string, [86](#)
- org.Dm.eg, [87](#)
- org.Dm.egGOBP, [88](#)
- org.Dm.egGOCC, [89](#)
- org.Dm.egGOMF, [89](#)
- org.Dm.egPS, [90](#)
- org.Dm.egSF, [91](#)
- org.Dm.string, [92](#)
- org.Gg.eg, [93](#)
- org.Gg.egGOBP, [93](#)
- org.Gg.egGOCC, [94](#)
- org.Gg.egGOMF, [95](#)
- org.Gg.egPS, [96](#)
- org.Gg.egSF, [97](#)
- org.Gg.string, [97](#)
- org.Hs.eg, [98](#)
- org.Hs.egDGIdb, [99](#)
- org.Hs.egDO, [100](#)
- org.Hs.egGOBP, [100](#)
- org.Hs.egGOCC, [101](#)
- org.Hs.egGOMF, [102](#)
- org.Hs.egHPCM, [103](#)
- org.Hs.egHPMA, [103](#)
- org.Hs.egHPMI, [104](#)
- org.Hs.egHPPA, [105](#)
- org.Hs.egMP, [105](#)
- org.Hs.egMsigdbC1, [106](#)
- org.Hs.egMsigdbC2BIOCARTA, [107](#)
- org.Hs.egMsigdbC2CGP, [108](#)
- org.Hs.egMsigdbC2CP, [108](#)
- org.Hs.egMsigdbC2CPall, [109](#)
- org.Hs.egMsigdbC2KEGG, [110](#)
- org.Hs.egMsigdbC2REACTOME, [111](#)
- org.Hs.egMsigdbC3MIR, [111](#)
- org.Hs.egMsigdbC3TFT, [112](#)
- org.Hs.egMsigdbC4CGN, [113](#)
- org.Hs.egMsigdbC4CM, [114](#)
- org.Hs.egMsigdbC5BP, [114](#)
- org.Hs.egMsigdbC5CC, [115](#)
- org.Hs.egMsigdbC5MF, [116](#)
- org.Hs.egMsigdbC6, [116](#)
- org.Hs.egMsigdbC7, [117](#)
- org.Hs.egMsigdbH, [118](#)
- org.Hs.egPS, [118](#)
- org.Hs.egSF, [120](#)
- org.Hs.PCommons_DN, [120](#), [122](#), [124](#)
- org.Hs.PCommons_DN.source, [122](#)
- org.Hs.PCommons_UN, [121](#), [123](#)
- org.Hs.string, [125](#)
- org.Mm.eg, [126](#)
- org.Mm.egDO, [126](#)
- org.Mm.egGOBP, [127](#)
- org.Mm.egGOCC, [128](#)
- org.Mm.egGOMF, [129](#)
- org.Mm.egHPCM, [129](#)
- org.Mm.egHPMA, [130](#)
- org.Mm.egHPMI, [131](#)
- org.Mm.egHPPA, [132](#)
- org.Mm.egMP, [132](#)
- org.Mm.egPS, [133](#)
- org.Mm.egSF, [134](#)
- org.Mm.string, [135](#)
- org.Rn.eg, [136](#)
- org.Rn.egGOBP, [137](#)
- org.Rn.egGOCC, [137](#)
- org.Rn.egGOMF, [138](#)
- org.Rn.egPS, [139](#)
- org.Rn.egSF, [140](#)
- org.Rn.string, [140](#)

- RegulomeDB_SNPs, [141](#)
- RT (Hiratani_TableS1), [57](#)

- TCGA_mutations, [142](#)

- UCSC_genes, [143](#)

- visBoxplotAdv, [143](#), [145](#)
- visDAG, [146](#)
- visGSEA, [33](#), [149](#)
- visNet, [36](#), [150](#), [156](#), [158](#), [161](#), [163](#)
- visNetAnimate, [152](#), [161](#)
- visNetArc, [155](#)
- visNetCircle, [157](#)
- visNetMul, [155](#), [159](#)
- visNetReorder, [43](#), [161](#)